



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## T18R4-10K2



**Article Number:** 111-00433

**Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Yellow/White Striped, 50/bag**



Download spec sheet

### Base Data

**Local Order Number** T18R4-10K2

**Type** T18R

**Color** White (WH)

- Features and Benefits**
- Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Yellow/White Striped, 50/bag

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 18.0 lbs

**Minimum Tensile Strength (Metric)** 80.0 N

**Length L (Imperial)** 4.0 "

**Length L (Metric)** 100.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Variant** Inside Serrated

**Width W (Imperial)** 0.1 "

**Width W (Metric)** 2.45 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 0.86 "

**Bundle Diameter Max. (Metric)** 22.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 50

**Carton Quantity** 10000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-ZODZ2.E64139 MIL 53421
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No