



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## P/N: T199362ACC

### Copyright

© 2016, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: T199362ACC

Release:

Commit: 35682

Language: en-US

Modified: 2016-05-17

Formatted: 2016-07-01



General description	
High capacity battery for the IR camera.	
Power system	
Battery type	Rechargeable Li ion battery
Battery voltage	3.7 V
Battery capacity	2.6 Ah at +20°C (+68°F)
Battery note	Approximate lithium content: 0.7 g
Charging system	Battery is charged inside the camera or in separate charger
Charging temperature	0°C to +45°C (+32°F to +113°F)
Environmental data	
Battery storage temperature range	-40°C to +70°C (-40°F to +158°F)
Shipping information	
Packaging, weight	0.125 kg
Packaging, size	170 × 75 × 65 mm
EAN-13	4743254002432
UPC-12	845188012748
Country of origin	Estonia

### Compatible with the following products

- 63901-0101; FLIR E4
- 63905-0501; FLIR E5
- 63902-0202; FLIR E6
- 63902-0207; FLIR E6 with Educational kit (DE)
- 63902-0204; FLIR E6 with Educational kit (EN)
- 63902-0208; FLIR E6 with Educational kit (ES)
- 63902-0206; FLIR E6 with Educational kit (FR)
- 63902-0205; FLIR E6 with Educational kit (IT)
- 63902-0209; FLIR E6 with Educational kit (JA)
- 63902-0210; FLIR E6 with Educational kit (KO)
- 63903-0303; FLIR E8