imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



4	3	2			1				
	R PUBLICATION 20 RIGHTS RESERVED.				REVISIONS				
C COPYRIGHT 20 BY - ALL	RIGHIS RESERVED.		P LT		DESCRIPTION	DATE	DWN	APVD	
			A	INITIAL		11MAY2015	DW	CW	
			A 1	ECR-17-018	3349	14DEC2017	DW	CW	D
									D
	40.1			NOTES:					
				I. TECHNIC	CAL CHARACTERISTICS:				
				SURFAC	CT MATERIAL: BRASS CE PLATING:				
				S	LVER PLATING: >=2µm CT RESISTANCE: <=0.5m				
Ø12.5 -	+++			WIRE F	ANGE: 35 mm²	2			ľ
↓ ↓				OPERAT	ION TEMPERATURE: -40~	+ 25°C			
			S	主释:					
				. 技术参数 :	- /				
С				公针材料: 5 表面电镀:	र मिन्				С
				镀银: 2	>=2μm <=0.5mΩ				
		Ø 1 8 —		接线范围: 〔	35 mm ²				ľ
▲ ↓				工作温度:	40~+ 25°C				
								-	
Ø17 Ø8.2 —	┝┝╶─╴╴──╶╶╫┝╶┼╒══╪══╼┥╴	-+++{₩+{}+++++++							
									l
	2 0 —								
	1 1								
В									В

T2060002035-000						
?	PART DESCRIPTION 描述					
ONTROL	LLED DOCUMENT	<u>David Wang</u> снк 11МАҮ2015				
OTHE 0 PLC 1 PLC 2 PLC 3 PLC	ERWISE SPECIFIED: ±- ±- ±- ±- ±- ±-	APVD 11MAY2015 Xiang Xu PRODUCT SPEC 108-137057 APPLICATION SPEC	C H HM			
ANGLES FINISH	<u>±-</u>	<u>114-137057</u> weight – Д Customer Drawing	3007			
	CONTROI OTHI O PLC 1 PLC 2 PLC 3 PLC 4 PLC ANGLES	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-	R PART DESCRIPTION B B CONTROLLED DOCUMENT. DWN DWN 11MAY2015 David Wang CHK 11MAY2015 CHK 11MAY2015 CHK 11MAY2015 CHK 11MAY2015 CHK 11MAY2015 CHK 11MAY2015 NAME OPLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±- FINISH			

А

35 20 STRIPPING LENGTH (mm) 剥线长度 (mm) WIRE GAUGE (mm²) 线规 (mm²) **≤**TE TE Connectivity CHF-35 HM SOCKET CONTACT А E CODE DRAWING NO RESTRICTED TO 779 C-T2060002035000 _ 2:1 SHEET SCALE

^{rev}A1

1 ^{OF} 1