



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	10MAR2015	DL	CW

PANEL CUT OUT FOR INSERT FOR USING
WITHOUT HOODS/HOUSINGS

NOTES:

1. TECHNICAL CHARACTERISTICS:

INSULATION MATERIAL: PA

RATED VOLTAGE: 200 V

RATED CURRENT: 16 A

INSULATION RESISTANCE: $\geq 400M\Omega$

RATED IMPULSE VOLTAGE: 3 KV

FLAMMABILITY: UL94V-0

MATING CYCLES: 200 FOR SILVER PLATED

500 FOR GOLD PLATED

OPERATION TEMPERATURE: $-40-+125^{\circ}C$ WIRE RANGE: 1.5 mm² (16 AWG)

CONTACT TYPE: SOLDERING

注释:

1. 技术参数:

绝缘材料: PA

额定电压: 200V

额定电流: 16A

绝缘电阻: $\geq 400M\Omega$

额定脉冲电压: 3 KV

阻燃等级: UL94V-0

插拔次数: 镀银端子: 200次

镀金端子: 500次

工作温度: $-40-+125^{\circ}C$ 接线范围: 1.5 mm² (16 AWG)

接线类型: 焊接(电路焊接形式)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL

FINISH

DWN DAVID LI 10MAR2015

CHK CHRIS WANG 10MAR2015

APVD XU XIANG 10MAR2015

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

Customer Drawing

HEE-015-M

T2800152101-000

DESCRIPTION

PART NUMBER

TE Connectivity

NAME

HEE-015-M

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

-

©-T2800152101000

-

SCALE

1:1

SHEET

1 OF 1

REV A

1470-19 (3/13)