



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Industrial M8 and M12 Series Circular Connector

1. Scope

1.1 Contents

This specification covers the requirements for product performance, test methods and quality assurance provisions of M Series Connector family.

2. Applicable Documents :

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of this specification and the referenced documents, this specification shall take precedence.

2.1 TE Specifications:

- 501-106140: Qualification Test Report For M12 Screw Type Connector (T411XXXXXXXX-XXX)
- 501-106140-1: Qualification Test Report For M12 Cable Assembly (T415XXXXXXXX-XXX and T416XXXXXXXX-XXX)
- 501-106140-2: Qualification Test Report For M8 Cable Assembly (T405XXXXXXXX-XXX and T406XXXXXXXX-XXX)
- 501-106140-3: Qualification Test Report For M12 Panel mount (T413XXXXXXXX-XXX and T414XXXXXXXX-XXX and T417XXXXXXXX-XXX)
- 501-106140-4: Qualification Test Report For M8 Screw Assembly (T401XXXXXXXX-XXX)

2.2 Commercial Standards and Specifications:

- IEC 61076-2-101: Detail specification for M12 connectors with screw-locking
- IEC 61076-2-104: Detail specification with M8 screw-locking or snap-locking
- IEC 60512: Electromechanical Components For Electronic Equipment; Basic Testing Procedure and Measuring Methods
- IEC-60529: Degree of Protection Provided by Enclosures(IP Code)



PRODUCT SPECIFICATION

108-106140
27th Sep. 16 Rev. A2

3. Requirements:

3.1 Design and Construction:

Product shall be of the design, construction and physical dimensions specified on the applicable product drawing.

3.2 Materials:

Material used in the construction of this product should be as specified on the applicable product drawing.

3.3 Ratings:

3.3.1 Electrical

A. Voltage Rating : M12: 250V (≤ 4 way)/60V (5 way)/30V (> 5 way)
M8: 60V (3 way)/30V (4 and 5 way)

B. Current Rating: Refer to Fig.3.

C. Temperature Rating : -25° C to 85° C

D. Insulation Resistance: 100M Ω Min.

3.3.2 Environmental

Sealing Requirements: IP65/IP67

Durability: 100 cycles

3.4 Performance Requirements and Test Descriptions :

The product shall be designed to meet the electrical, mechanical and environmental performance requirements specified in Fig 1.

All tests shall be performed at the ambient environmental conditions per IEC 512, unless otherwise specified.



PRODUCT SPECIFICATION

108-106140
27th Sep. 16 Rev. A2

3.5 Test Requirements and Procedures Summary

Para	Test Items	Requirements	Procedures
3.5.1	Examination of product	No defect would impair normal operation	Visual inspection No physical damage. IEC 60512, Test 1a
Electrical Requirements			
3.5.2	Voltage proof (withstanding voltage)	1 minute hold with no breakdown or flashover.	For M8: 650 volts AC or DC, hold for 1 minute between adjacent contacts/between contacts and shield For M12: 1400(4 pins) /1000(5 pins) /650(8 pins) volts AC or DC, hold for 1 minute between adjacent contacts/ between contacts and shield IEC 60512-4-1
3.5.3	Insulation Resistance	100MΩMin.	500V DC between adjacent contacts IEC 60512, Test 3a, Method A
3.5.4	LLCR	Initial value: 10mΩ max.	Subject specimens to 100 milliamps maximum and 20 millivolts maximum open circuit voltage Test points refer to Fig.4 IEC 60512-2-1, Test 2a
3.5.5	Temperature Rising	30° C MAX under loaded rating current. (See fig.3)	Stabilize at rate current level until 3 readings at 5 minutes intervals are within 1°C IEC 60512-5-2
Mechanical Requirements			
3.5.6	Impacting water	No ingress of water	IEC 60529, Test 14.2.7
3.5.7	Dust (IP6X)	No deposit dust on contact	IEC 60529, Test 6, table 7
3.5.8	Durability	Contact resistance: Δ15mΩ max.	Mate and un-mate specimens for cycles at a maximum speed of operations=10mm/s, Rest:30s,unmated 100 cycles for gold plating 50 cycles for silver plating 20 cycles for tin plating EIA364-09-1
3.5.9	Mating/Un-mating Force	15N/15N Max. for 2-5 pins 23N/30N Max. for 6-12 pins 30N/30N Max. for 13-17 pins	Operation speed: 10mm/min. Measure force necessary to mate samples. EIA364-13



PRODUCT SPECIFICATION

108-106140
27th Sep. 16 Rev. A2

3.5.10	Sinusoidal vibration	1: Duration of disturbance 1μs max. 2: Contact resistance: Δ15mΩ max. 3: There shall be no defect that would impair normal operation	10Hz to 500Hz and 0.35mm or 50 m/s ² Sweep cycles:10 Full duration:6H IEC60512, Test 6d
3.5.11	Mechanical Shock	1: No discontinuities of 1 microsecond or longer duration 2: Contact resistance: Δ15mΩ max. 3: There shall be no defect that would impair normal operation	Subject mated specimens to 50G's half-sine shock pulses of 11 milliseconds duration with 3.44m/s velocity change. Three shocks in each direction applied along 3 mutually perpendicular planes, 18 total shocks. EIA364-27
Environmental Requirements			
3.5.12	Rapid change in temperature	See Note.	IEC 60512-11-4 Subject specimens to 5 cycles between -25°C to 85°C with 30 minutes dwells at temperature extremes
3.5.13	Dry heat	See Note. Insulation resistance at high temperature	IEC 50512-11-9 Subject mated specimens to 85°C for 16 hours
3.5.14	Damp heat, cyclic	See Note.	IEC 60512-11-12 Subject specimens to 5 cycles(5 days) Temperature:40°C Recovery time:2h
3.5.15	Cold	See Note.	IEC 60512-11 Temp.: -25°C Duration:2h Recovery time:2h
3.5.16	Mixed flowing gas	See Note.	IEC 60068-2-60, Method 4 Subject mated specimens to flowing mixed gas corrosion-4 days



NOTE Shall meet visual requirements, show no physical damage, and meet requirements of additional tests as specified in the Product Qualification and Re qualification Test Sequence shown in Figure 2.

Fig. 1 (END)

3.6 Product Qualification Test Sequence

Test or Examination	Test Group				
	A(a)	B	C	D	E(f)
	Test Sequence				
Examination of product	1	3,6,11,20,26	8	9	1
Voltage proof(withstanding voltage)	4	10,19,25	4,7	4,8	
Insulation resistance	3	9,13,18,24	3,6	3,7	
LLCR	2	2,5,8,17,23	2	2	2,6
Temperature Rising				5(e)	
Impacting water		21	5	6	
Dust(IP6X)		22(b)			
Durability					4
Mating and Un-mating Force					3,5
Sinusoidal vibration		1			
Mechanical shock		4			
Rapid change in temperature		7		1	
Dry heat		12			
Damp heat, cyclic		14(c),16(d)			
Cold		15			
Mixed flowing gas			1		

NOTE:

- (a) When the initial test group A has been completed, the specimens are divided in the 3 groups B, C, D. All connectors in each group shall undergo the tests specified for the relevant group numbers indicate sequence in which tests are performed.
- (b) It's allowed to perform with an additional specimen, extending the total number of specimen by 1.
- (c) First cycle
- (d) Remaining cycles
- (e) Test with additional specimen for over-molding type cable assembly
- (f) This test group should be tested without the screw nut

Fig.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Qualification Testing

A. Specimen Selection



PRODUCT SPECIFICATION

108-106140
27th Sep. 16 Rev. A2

Plugs and receptacles should be prepared in accordance with applicable Instruction Sheet and should be elected at random from current production. Each test group shall consist of 3 specimens Min. unless otherwise stated.

B. Test Sequence

Qualification inspection shall be verified by testing specimens as specified in figure 2.

4.2 Requalification testing

If changes significantly affecting form, fit or function are made to the product or manufacturing process or controlling industry specification, product assurance, shall coordinate requalification testing, consisting of all or part of the original testing sequence as determined by development/product, quality and reliability engineering.

4.3 Acceptance

Acceptance is based on verification that the product meets the requirements of Figure 1. Failures attributed to equipment, test setup or operator deficiencies shall not disqualify the product. If product failure occurs, corrective action shall be taken and samples resubmitted for qualification. Testing to confirm corrective action is required before resubmitted.

4.4 Quality conformance Inspection

The applicable quality inspection plan shall specify the sampling acceptable quality level to be used. Dimensional and functional requirements shall be in accordance with the applicable product drawing and this specification.

For M12:	
A-coding 2- 5 ways	=4 A
6- 8 ways	=2 A
9- 17 ways	=1.5 A
B-coding 5 ways	=4A
C-coding 3 ways (2+PE)	=4A
4 ways (3+PE)	=4A
5 ways (4+PE)	=2A
6 ways (5+PE)	=2A
D-coding 4 ways	=4A
P-coding 5 ways (4+PE)	=4A
For M8: 3A	

Fig.3 (Rating Current)




Fig.4 Contact resistance arrangement