



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: T50R4UVM4



UV Resistant Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66UV, Yellow, 1000/pkg

Article Number	111-04920
Type	T50R
Color	Yellow (YE)
Features & Benefits	• Engineered and manufactured for maximum performance and quality. • Made from 100% high-quality plastic to ensure efficient recycling. • Inside serration for a strong hold onto bundles. • Easy application either manually or with a tensioning tool. • Bent tail allows for simpler insertion.
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	UV Resistant Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66UV, Yellow, 1000/pkg
Global Part Name	T50R-PA66UV-YE
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	202.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0

Thickness T (Metric)	1.2
Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66UV
US MIL SPEC	MIL 53421
	Flammability
UL 94 V2	Halogen free
Yes	Operating Temperature (Metric)
-40°F to +185°F (-40°C to +85°C)	ROHS Complaint
Yes	Certification/Specification WEB
UL-ZODZ2.E64139	UL Recognized (US)
Yes	UL Recognized (US and Canada)
Yes	
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909987
Content Unit(BMEcat)	bag

