



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





TAG13-400

Dot Matrix Label, .75" X .25", 9 Across, Polyester, White, 5000/PK

Article Number: 595-13400

Part Number: TAG13-400

Type: TAG13

Base Data


Part No.	TAG13-400
Type	TAG13
Color	White (WH)
Features	<ul style="list-style-type: none">• Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.• Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.
Application Method	Labels are printed using a HellermannTyton thermal transfer printer and then applied by hand.

Product Dimensions

Length (L)	0.25" / 6.4mm
Width (W) (imperial)	0.75"
Width (W)	19.05mm
Height (H)	0.2" / 5.08mm
HR	22.86mm / .900"
Print Method	Dot-Matrix
Vertical Repeat	.333" / 8.45mm
Width of Liner (WL)	9.000" / 228.60mm

Material and Specifications

Material	Type 400, Polyester, white (WH)
Adhesive	Acrylic / Acryl
Adhesive Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Curing Temperature	from +50 °F (from +10 °C)

Material Specification	RoHS
Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
ROHS Conformity	 RoHS
Specification	UL-Recognized

Logistic and Packaging

Packaging Type	pack
Pkg. Qty.	5000 / 5000
Carton Qty.	5000Pieces
EAN code	4031026175232
Labels per Row	9
Minimum Order Quantity	5000
UPC	089306093329

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001 Certified](#)
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512