



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





TAG14-400

Dot Matrix Label, 1.0" X .375", 7 Across, Polyester, White, 5000/PK

Article Number: 595-14400

Part Number: TAG14-400

Type: TAG14

Base Data

Part No.	TAG14-400
Type	TAG14
Color	White (WH)
Features	• Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing. • Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.
Application Method	Labels are printed using a HellermannTyton thermal transfer printer and then applied by hand.

Product Dimensions

Length (L)	0.375" / 9.52mm
Width (W) (imperial)	1.0"
Width (W)	25.4mm
Height (H)	0.375" / 9.52mm
HR	27.94mm / 1.100"
Print Method	Dot-Matrix
Vertical Repeat	.500" / 12.70mm
Width of Liner (WL)	8.600" / 218.40mm

Material and Specifications

Material	Type 400, Polyester, white (WH)
Adhesive	Acrylic / Acryl
Adhesive Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Curing Temperature	from +50 °F (from +10 °C)

Material Specification	RoHS
Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
ROHS Conformity	 RoHS
Specification	UL-Recognized

Logistic and Packaging

Packaging Type	pack
Pkg. Qty.	5000 / 5000
Carton Qty.	5000Pieces
EAN code	4031026175256
Labels per Row	7
Minimum Order Quantity	5000
UPC	089306093404

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001 Certified](#)
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512