



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Specification Sheet

Part Number: TAG53L-788

**HellermannTyton** Laser Tag Label, 8.5" x 11", 1 Per Sheet, PET, White, 250/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 594-53788  |
| <b>Type</b>                    | TAG53L   |
| <b>Color</b>                   | White (WH)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>•White polyester has a smooth surface, allowing for the highest resolution and print contrast.</li><li>•The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.</li><li>•LaserTags are sheet fed for easy loading and fast printing.</li></ul>  |
| <b>Quantity Per</b>            | pack   |
| <b>Product Description</b>     | HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking. |

**Short Description**

Laser Tag Label, 8.5" x 11", 1 Per Sheet, PET, White, 250/pkg

**Global Part Name**

TAG53L-788-WH

**Width W (Imperial)**

8.5

**Width W (Metric)**

215.9

**Bundle Diameter Min (Imperial)**

0.24

**Bundle Diameter Min (Metric)**

6.10

**Thickness T (Metric)**

64.0

**Height H (Imperial)**

10.81

**Height H (Metric)**

274.60

**Material**

Type 788, Polyester (PET)

**Material Shortcut**

788

**Adhesive**

Acrylic

**Halogen free**

No

**Adhesive Operating Temperature**

-40°F to +199°F (-40°C to +93°C)

**Operating Temperature (Metric)**

-40°F to +199°F (-40°C to +93°C)

|                                    |            |
|------------------------------------|------------|
| <b>Reach Complaint(Article 33)</b> | Yes        |
| <b>ROHS Complaint</b>              | Yes        |
| <b>Package Quantity(Imperial)</b>  | 250        |
| <b>Package Quantity (Metric)</b>   | 250        |
| <b>Customs Number</b>              | 3919905060 |
| <b>Labels per Column</b>           | 1          |
| <b>Labels per Row</b>              | 1          |
| <b>Weight (Metric)</b>             | 0.521      |
| <b>Weight (Imperial)</b>           | 1.14       |