



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: TAG55L-788

HellermannTyton Laser Tag Label, 5.5" x 4.25", 4 Per Sheet, PET, White, 1000/pkg

Article Number	594-55788
Type	TAG55L
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none"><li>• LaserTags are sheet fed for easy loading and fast printing.</li><li>• LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.</li><li>• LaserTags are printable using toner for long term UV exposure.</li><li>• LaserTags come in a variety of label sizes and types to fit most applications.</li></ul>
Quantity Per	pack
Product Description	<p>LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.</p>

Short Description	Laser Tag Label, 5.5" x 4.25", 4 Per Sheet, PET, White, 1000/pkg
Global Part Name	TAG55L-788-WH
Width W (Imperial)	4.25
Width W (Metric)	107.9
Thickness T (Metric)	64.0
Height H (Imperial)	5.5
Height H (Metric)	139.7
Material	Type 788, Polyester (PET)
Material Shortcut	788
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +199°F (-40°C to +93°C)
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919905060
Labels per Column	2
Labels per Row	2
Weight (Metric)	0.521
Weight (Imperial)	1.14