

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








HellermannTyton

Specification Sheet

Part Number: TAG96L-789



survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high

Article Number	594-96789
Туре	TAG96L
Color	White (WH)
Features & Benefits	•Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast. •The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term. •Lasertags are not affected by the high heat required in a laser printer.
Quantity Per	pack
Product Description	HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and

temperature and UV resistant marking.

Short Description	Laser Tag Label, 1.875" x .25", 144 Per Sheet, PET, White, 1000/pkg
Global Part Name	TAG96L-789-WH
Width W (Imperial)	1.875
Width W (Metric)	47.62
Thickness T (Metric)	64.0
Height H (Imperial)	0.25
Height H (Metric)	6.35
Material	Type 789, Polyester (PET)
Material Shortcut	789
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +300°F (-40°C to +149°C)
Reach Complaint(Article 33)	Yes

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919905060
Labels per Column	36
Labels per Row	4
Weight (Metric)	0.521
Weight (Imperial)	1.14

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $[\]hbox{@ 2018 HellermannTyton. All rights reserved.}$