



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Article Number:** 557-00011

**Spirit Self-Laminating Printer Label, .5" X .5" X 1.43", Vinyl, White, 250/RL**



Download spec sheet

### Base Data

**Local Order Number** TAGH2-100  
**Type** TAGH2  
**Color** White (WH)

**Features and Benefits**

- HellermannTyton 100 self-laminating vinyl utilizes an aggressive acrylic adhesive that allows the label to stay wrapped on wire gauges as small as .06" in diameter without starting to unwrap or flag.
- The label material is best printed with HellermannTyton HHHST series ribbons on the Spirit portable printing system for optimal print clarity.
- All Spirit self-laminating labels meet the requirements of UL-969 STANDARD FOR MARKING AND LABELING SYSTEMS edition - 4, under UL file number MH18396 to achieve long label life and print durability when used indoors or outdoors.

**Color Marking Field** White (WH)

**Product Description** The HellermannTyton Spirit printing system is easy to use and features a "What You See Is What You Get" (WYSIWYG) user interface that shows the outline of the label on the LCD screen for quick and easy editing and printing. The Spirit 2100 provides a fast, high quality, thermal transfer printing of labels that are designed to survive industrial environments. A wide variety of label materials, sizes and types are available to fit most applications.

**Mounting method Identification ETIM** Pasting / Stick

**Short Description** Spirit Self-Laminating Printer Label, .5" X .5" X 1.43", Vinyl, White, 250/RL

### Product Dimensions

**Length L (Imperial)** 0.5 "  
**Length L (Metric)** 12.7 mm  
**Variant** Roller form

**Width W (Imperial)** 0.5 "  
**Width W (Metric)** 12.7 mm  
**Height H (Imperial)** 0.5 "  
**Height H (Metric)** 12.7 mm

**Height H2 (Imperial)** 1.435 "  
**Height H2 (Metric)** 36.5 mm

**Height of printable area (metric)** 0.5 mm

**Bundle Diameter Min. (Imperial)** 0.133 "  
**Bundle Diameter Min. (Metric)** 3.40 mm

**Bundle Diameter Max. (Imperial)** 0.29 "  
**Bundle Diameter Max. (Metric)** 7.50 mm

**Print Method** Thermal Transfer

**Width of Liner WL (metric)** 22.22 mm

Width of Liner WL (imperial) 0.875 "

## Logistics and Packaging

---

**Quantity Per** reel  
**Package Quantity** 250  
**Package Quantity (Metric)** 250  
**Carton Quantity** 1  
**Weight (Metric)** 0.3 kg

## Material and Specifications

---

**Material** Type 100, Vinyl (PVC), white (WH), self laminating  
**Material Shortcut** 100  
**Adhesive** Acrylic  
**Adhesive Shortcut** Acrylic  
**Adhesive Operating Temperature** -40°F to +194°F (-40°C to +90°C)  
**Operating Temperature** -40°F to +176°F (-40°C to +80°C)  
**ROHS Compliant** Yes  
**Certification/Specification** UL-Recognized