



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




### ●Features

- 1) Small package, large capacitance chip tantalum capacitor.
- 2) Low impedance capacitors.
- 3) Screening by thermal shock.

### ●Dimensions



### ●Part No. Explanation



① Series name  
TC

② Case style  
A : 3216-18 (1206) size

③ Rated voltage

|                   |    |     |    |    |    |    |
|-------------------|----|-----|----|----|----|----|
| Rated voltage (V) | 4  | 6.3 | 10 | 16 | 20 | 25 |
| CODE              | 0G | 0J  | 1A | 1C | 1D | 1E |

④ Nominal capacitance

Nominal capacitance in pF in 3 digits:  
2 significant figures followed by the figure  
representing the number of 0's.

⑤ Capacitance tolerance  
M : ± 20%

⑥ Taping

8 : Real width : 8mm  
R : Positive electrode on the side opposite to sprocket hole

●Rated table

| Capacitance (μF) | Rated voltage (V.DC) |     |    |    |    |    |
|------------------|----------------------|-----|----|----|----|----|
|                  | 4                    | 6.3 | 10 | 16 | 20 | 25 |
| 1.0 (105)        |                      |     |    | A  | A  | A  |
| 2.2 (225)        |                      |     | A  | A  |    |    |
| 3.3 (335)        |                      | A   | A  | A  |    | A  |
| 4.7 (475)        |                      | A   | A  | A  | A  | A  |
| 10 (106)         | A                    | A   | A  | A  |    |    |
| 15 (156)         |                      | A   | A  |    |    |    |
| 22 (226)         | A                    | A   | A  |    |    |    |
| 33 (336)         | A                    | A   |    |    |    |    |
| 47 (476)         | A                    | A   |    |    |    |    |
| 100 (107)        | A                    |     |    |    |    |    |

Remark) Case size codes (A) in the above show products line-up.

●Marking

The indications listed below should be given on the surface of a capacitor.

- (1) Polarity : The polarity should be shown by □ bar. (on the anode side)
- (2) Rated DC voltage : A voltage code is shown as below table.
- (3) Capacitance : A capacitance code is shown as below table.

| Voltage Code | Rated DC Voltage (V) |
|--------------|----------------------|
| g            | 4                    |
| j            | 6.3                  |
| A            | 10                   |
| C            | 16                   |
| D            | 20                   |
| E            | 25                   |


| Capacitance Code | Nominal Capacitance (μF) |
|------------------|--------------------------|
| A                | 1.0                      |
| E                | 1.5                      |
| J                | 2.2                      |
| N                | 3.3                      |
| S                | 4.7                      |
| a                | 10                       |
| e                | 15                       |
| j                | 22                       |
| n                | 33                       |
| s                | 47                       |
| ā                | 100                      |

Visual typical example  
voltage code and capacitance code are variable with parts number.

[A case]

EX.)  $\frac{j}{(1)}$   $\frac{a}{(2)}$

(1) voltage code (2) capacitance code



●Characteristics

| Item   |            | Performance   | Test conditions (based on JIS C 5101-1 and JIS C 5101-3)   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|--|------------|---|--|--|-------|------|---|---------|----------|---|------------|--------------|---|---------|----------|---|------------|--------------|
| Operating Temperature                                  |            | -55°C~+125°C  | Voltage reduction when temperature exceeds +85°C   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Maximum operating temperature with no voltage derating |            | +85°C   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Rated voltage (V.DC)                                   |            | 4 6.3 10 16 20 25   | at 85°C  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Category voltage (V.DC)                                |            | 2.5 4 6.3 10 13 16  | at 125°C   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Surge voltage (V.DC)                                   |            | 5 8 13 20 26 32   | at 85°C  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| DC Leakage current                                     |            | Shall be satisfied the value on " Standard list "   | As per 4.9 JIS C 5101-1<br>As per 4.5.1 JIS C 5101-3<br>Voltage : Rated voltage for 1min   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Capacitance tolerance                                  |            | Shall be satisfied allowance range. ±20%  | As per 4.7 JIS C 5101-1<br>As per 4.5.2 JIS C 5101-3<br>Measuring frequency : 120±12Hz<br>Measuring voltage : 0.5Vrms +1.5V.DC<br>Measuring circuit : DC Equivalent series circuit   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Tangent of loss angle (Df, tan δ)                      |            | Shall be satisfied the value on " Standard list "   | As per 4.8 JIS C 5101-1<br>As per 4.5.3 JIS C 5101-3<br>Measuring frequency : 120±12Hz<br>Measuring voltage : 0.5Vrms +1.5V.DC<br>Measuring circuit : DC Equivalent series circuit   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Impedance  |            | Shall be satisfied the value on " Standard list "   | As per 4.10 JIS C 5101-1<br>As per 4.5.4 JIS C 5101-3<br>Measuring frequency : 100±10kHz<br>Measuring voltage : 0.5Vrms or less<br>Measuring circuit : DC Equivalent series circuit  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Resistance to Soldering heat                           | Appearance | There should be no significant abnormality. The indications should be clear.  | As per 4.14 JIS C 5101-1<br>As per 4.6 JIS C 5101-3<br>Dip in the solder bath<br>Solder temp : 260±10°C<br>Duration : 5±0.5s<br>Repetition : 1<br>After the specimens, leave it at room temperature for over 24h and then measure the sample.                                    |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | L.C.       | Less than initial limit   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | ΔC / C     | TCA0G107M8R : Within ±20% of initial value<br>Others : Within ±5% of initial value  |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | Df (tan δ) | Less than initial limit   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Temperature cycle                                      | Appearance | There should be no significant abnormality. The indications should be clear.  | As per 4.16 JIS C 5101-1<br>As per 4.10 JIS C 5101-3<br>Repetition : 5 cycles<br>(1 cycle : steps 1 to 4) without discontinuation.   |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | L.C.       | Less than initial limit   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | ΔC / C     | TCA0G107M8R : Within ±20% of initial value<br>TCA0J476M8R : Within ±15% of initial value<br>TCA1A226M8R : Within ±15% of initial value<br>Others : Within ±10% of initial value   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | Df (tan δ) | Less than initial limit   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  |            | <table border="1"> <thead> <tr> <th></th> <th>Temp.</th> <th>Time</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-55±3°C</td> <td>30±3min.</td> </tr> <tr> <td>2</td> <td>Room temp.</td> <td>3min.or less</td> </tr> <tr> <td>3</td> <td>125±2°C</td> <td>30±3min.</td> </tr> <tr> <td>4</td> <td>Room temp.</td> <td>3min.or less</td> </tr> </tbody> </table> |  |  | Temp. | Time | 1 | -55±3°C | 30±3min. | 2 | Room temp. | 3min.or less | 3 | 125±2°C | 30±3min. | 4 | Room temp. | 3min.or less |
|  | Temp.      | Time  |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| 1  | -55±3°C    | 30±3min.  |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| 2  | Room temp. | 3min.or less  |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| 3  | 125±2°C    | 30±3min.  |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| 4  | Room temp. | 3min.or less  |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
| Moisture resistance                                    | Appearance | There should be no significant abnormality. The indications should be clear.  | As per 4.22 JIS C 5101-1<br>As per 4.12 JIS C 5101-3<br>After leaving the sample under such atmospheric condition that the temperature and humidity are 60±2°C and 90 to 95% RH,respectively, for 500±12h leave it at room temperature for over 24h and then measure the sample. |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | L.C.       | Less than initial limit   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | ΔC / C     | TCA0G107M8R : Within ±20% of initial value<br>Others : Within ±10% of initial value   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |
|  | Df (tan δ) | TCA0G107M8R : Less than 150% of initial limit<br>Others : Less than initial limit   |  |  |       |      |   |         |          |   |            |              |   |         |          |   |            |              |



| Item                        | Performance        | Test conditions (based on JIS C 5101-1 and JIS C 5101-3)  |
|-----------------------------|--------------------|---|
| Temperature Stability       | Temp.              | -55°C   |
|                             | $\Delta C / C$     | Within 0/-12% of initial value  |
|                             | Df (tan $\delta$ ) | Shall be satisfied the voltage on " Standard list "   |
|                             | L.C.               | -   |
|                             | Temp.              | +85°C   |
|                             | $\Delta C / C$     | TCA0G107M8R : Within +12/0% of initial value<br>Others : Within +10/0% of initial value   |
|                             | Df (tan $\delta$ ) | Shall be satisfied the voltage on " Standard list "   |
|                             | L.C.               | Less than 1000% of initial limit  |
|                             | Temp.              | +125°C  |
|                             | $\Delta C / C$     | Within +15/0% of initial value  |
| Surge voltage               | Appearance         | There should be no significant abnormality. The indications should be clear.  |
|                             | L.C.               | Less than initial limit   |
|                             | $\Delta C / C$     | TCA0G107M8R : Within $\pm 20\%$ of initial value<br>Others : $\pm 10\%$ of initial value  |
|                             | Df (tan $\delta$ ) | Less than initial limit   |
| Loading at High temperature | Appearance         | There should be no significant abnormality. The indications should be clear.  |
|                             | L.C.               | TCA0G107M8R : Less than 125% of initial limit<br>TCA1A226M8R : Less than 125% of initial limit<br>TCA1E105M8R : Less than 125% of initial limit<br>Others : Less than initial limit                     |
|                             | $\Delta C / C$     | TCA0G107M8R : Within $\pm 20\%$ of initial value<br>TCA0J476M8R : Within $\pm 15\%$ of initial value<br>TCA1A226M8R : Within $\pm 15\%$ of initial value<br>Others : Within $\pm 10\%$ of initial value |
|                             | Df (tan $\delta$ ) | Others : Less than initial limit  |
| Terminal strength           | Capacitance        | The measured value should be stable.  |
|                             | Appearance         | There should be no significant abnormality.   |


As per 4.29 JIS C 5101-1  
As per 4.13 JIS C 5101-3


As per 4.23 JIS C 5101-1  
As per 4.15 JIS C 5101-3

After applying the rated voltage for 2000+72/0 h without discontinuation via the serial resistance of 3 $\Omega$  or less at a temperature of 85 $\pm$ 2°C, leave the sample at room temperature / humidity for over 24h and measure the value.

As per 4.35 JIS C 5101-1  
As per 4.9 JIS C 5101-3

A force is applied to the terminal until it bends to 1mm and by a prescribed tool maintain the condition for 5s.  
(See the figure below)




| Item                   |             | Performance  | Test conditions (JIS C 5101-1 and JIS C 5101-3)  |
|------------------------|-------------|--|--|
| Adhesiveness           |             | The terminal should not come off.  | <p>As per 4.34 JIS C 5101-1<br/>                     As per 4.8 JIS C 5101-3<br/>                     Apply force of 5N in the two directions shown in the figure below for 10±1s after mounting the terminal on a circuit board.</p>   |
| Dimensions             |             | Refer to "External dimensions"   | Measure using a caliper of JIS B 7507 Class 2 or higher grade.   |
| Resistance to solvents |             | The indication should be clear   | <p>As per 4.32 JIS C 5101-1<br/>                     As per 4.18 JIS C 5101-3<br/>                     Dip in the isopropyl alcohol for 30±5s, at room temperature.</p>  |
| Solderability          |             | 3/4 or more surface area of the solder coated terminal dipped in the soldering bath should be covered with the new solder. | <p>As per 4.15.2 JIS C 5101-1<br/>                     As per 4.7 JIS C 5101-3<br/>                     Dip speed=25±2.5mm / s<br/>                     Pre-treatment(accelerated aging): Leave the sample on the boiling distilled water for 1 h.<br/>                     Solder temp. : 245±5°C<br/>                     Duration : 3±0.5s<br/>                     Solder : M705<br/>                     Flux : Rosin 25% IPA 75%</p> |
| Vibration              | Capacitance | Measure value should not fluctuate during the measurement.   | <p>As per 4.17 JIS C 5101-1<br/>                     Frequency : 10 to 55 to 10Hz/min.<br/>                     Amplitude : 1.5mm</p>  |
|                        | Appearance  | There should be no significant abnormality.  | <p>Time : 2h each in X and Y directions<br/>                     Mounting : The terminal is soldered on a print circuit board.</p>   |

●Standard products list


| Part No.        | Rated voltage<br>85°C<br>(V) | Category voltage<br>125°C<br>(V) | Surge voltage<br>85°C<br>(V) | Cap.<br>120Hz<br>(μF) | Tolerance<br>(%) | Leakage current<br>25°C<br>1WV.60s<br>(μA) | Df<br>120Hz<br>(%) |              |       | Impedance<br>100kHz<br>(Ω) |
|-----------------|------------------------------|----------------------------------|------------------------------|-----------------------|------------------|--|--------------------|--------------|-------|----------------------------|
|                 |                              |                                  |                              |                       |                  |  | -55°C              | 25°C<br>85°C | 125°C |                            |
| TC A 0G 106 M8R | 4                            | 2.5                              | 5                            | 10                    | ±20              | 0.5  | 12                 | 8            | 10    | 4.2                        |
| TC A 0G 226 M8R | 4                            | 2.5                              | 5                            | 22                    | ±20              | 0.9  | 12                 | 8            | 10    | 3                          |
| TC A 0G 336 M8R | 4                            | 2.5                              | 5                            | 33                    | ±20              | 1.3  | 14                 | 10           | 12    | 3.5                        |
| TC A 0G 476 M8R | 4                            | 2.5                              | 5                            | 47                    | ±20              | 1.9  | 30                 | 12           | 16    | 3.2                        |
| TC A 0G 107 M8R | 4                            | 2.5                              | 5                            | 100                   | ±20              | 4  | 54                 | 30           | 36    | 3                          |
| TC A 0J 335 M8R | 6.3                          | 4                                | 8                            | 3.3                   | ±20              | 0.5  | 10                 | 6            | 8     | 5.6                        |
| TC A 0J 475 M8R | 6.3                          | 4                                | 8                            | 4.7                   | ±20              | 0.5  | 12                 | 8            | 10    | 4.9                        |
| TC A 0J 106 M8R | 6.3                          | 4                                | 8                            | 10                    | ±20              | 0.6  | 12                 | 8            | 10    | 4                          |
| TC A 0J 156 M8R | 6.3                          | 4                                | 8                            | 15                    | ±20              | 0.9  | 12                 | 8            | 10    | 3                          |
| TC A 0J 226 M8R | 6.3                          | 4                                | 8                            | 22                    | ±20              | 1.4  | 14                 | 10           | 12    | 3.5                        |
| TC A 0J 336 M8R | 6.3                          | 4                                | 8                            | 33                    | ±20              | 2.1  | 30                 | 12           | 16    | 3.2                        |
| TC A 0J 476 M8R | 6.3                          | 4                                | 8                            | 47                    | ±20              | 3.0  | 34                 | 18           | 24    | 3.2                        |
| TC A 1A 225 M8R | 10                           | 6.3                              | 13                           | 2.2                   | ±20              | 0.5  | 10                 | 6            | 8     | 5.6                        |
| TC A 1A 335 M8R | 10                           | 6.3                              | 13                           | 3.3                   | ±20              | 0.5  | 12                 | 8            | 10    | 4.9                        |
| TC A 1A 475 M8R | 10                           | 6.3                              | 13                           | 4.7                   | ±20              | 0.5  | 12                 | 8            | 10    | 4.2                        |
| TC A 1A 106 M8R | 10                           | 6.3                              | 13                           | 10                    | ±20              | 1.0  | 12                 | 8            | 10    | 3                          |
| TC A 1A 156 M8R | 10                           | 6.3                              | 13                           | 15                    | ±20              | 1.5  | 14                 | 10           | 12    | 3.5                        |
| TC A 1A 226 M8R | 10                           | 6.3                              | 13                           | 22                    | ±20              | 2.2  | 30                 | 12           | 16    | 3.2                        |
| TC A 1C 105 M8R | 16                           | 10                               | 20                           | 1                     | ±20              | 0.5  | 10                 | 6            | 8     | 7                          |
| TC A 1C 225 M8R | 16                           | 10                               | 20                           | 2.2                   | ±20              | 0.5  | 10                 | 6            | 8     | 4.9                        |
| TC A 1C 335 M8R | 16                           | 10                               | 20                           | 3.3                   | ±20              | 0.5  | 10                 | 6            | 8     | 4.8                        |
| TC A 1C 475 M8R | 16                           | 10                               | 20                           | 4.7                   | ±20              | 0.8  | 10                 | 6            | 8     | 3.9                        |
| TC A 1C 106 M8R | 16                           | 10                               | 20                           | 10                    | ±20              | 1.6  | 12                 | 8            | 10    | 3.5                        |
| TC A 1D 105 M8R | 20                           | 13                               | 26                           | 1                     | ±20              | 0.5  | 10                 | 6            | 8     | 7                          |
| TC A 1D 475 M8R | 20                           | 13                               | 26                           | 4.7                   | ±20              | 0.9  | 10                 | 6            | 8     | 3.9                        |
| TC A 1E 105 M8R | 25                           | 16                               | 32                           | 1                     | ±20              | 0.5  | 10                 | 6            | 8     | 7                          |
| TC A 1E 335 M8R | 25                           | 16                               | 32                           | 3.3                   | ±20              | 0.8  | 10                 | 6            | 8     | 4.8                        |
| TC A 1E 475 M8R | 25                           | 16                               | 32                           | 4.7                   | ±20              | 1.2  | 12                 | 8            | 10    | 3.4                        |

\* = Under development

●Packaging specifications



●Reel dimensions





# Notice

## Precaution on using ROHM Products

- Our Products are designed and manufactured for application in ordinary electronic equipments (such as AV equipment, OA equipment, telecommunication equipment, home electronic appliances, amusement equipment, etc.). If you intend to use our Products in devices requiring extremely high reliability (such as medical equipment <sup>(Note 1)</sup>, transport equipment, traffic equipment, aircraft/spacecraft, nuclear power controllers, fuel controllers, car equipment including car accessories, safety devices, etc.) and whose malfunction or failure may cause loss of human life, bodily injury or serious damage to property ("Specific Applications"), please consult with the ROHM sales representative in advance. Unless otherwise agreed in writing by ROHM in advance, ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of any ROHM's Products for Specific Applications.

(Note1) Medical Equipment Classification of the Specific Applications

| JAPAN     | USA       | EU         | CHINA     |
|-----------|-----------|------------|-----------|
| CLASS III | CLASS III | CLASS II b | CLASS III |
| CLASS IV  |           | CLASS III  |           |

- ROHM designs and manufactures its Products subject to strict quality control system. However, semiconductor products can fail or malfunction at a certain rate. Please be sure to implement, at your own responsibilities, adequate safety measures including but not limited to fail-safe design against the physical injury, damage to any property, which a failure or malfunction of our Products may cause. The following are examples of safety measures:
  - Installation of protection circuits or other protective devices to improve system safety
  - Installation of redundant circuits to reduce the impact of single or multiple circuit failure
- Our Products are designed and manufactured for use under standard conditions and not under any special or extraordinary environments or conditions, as exemplified below. Accordingly, ROHM shall not be in any way responsible or liable for any damages, expenses or losses arising from the use of any ROHM's Products under any special or extraordinary environments or conditions. If you intend to use our Products under any special or extraordinary environments or conditions (as exemplified below), your independent verification and confirmation of product performance, reliability, etc. prior to use, must be necessary:
  - Use of our Products in any types of liquid, including water, oils, chemicals, and organic solvents
  - Use of our Products outdoors or in places where the Products are exposed to direct sunlight or dust
  - Use of our Products in places where the Products are exposed to sea wind or corrosive gases, including Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, and NO<sub>2</sub>
  - Use of our Products in places where the Products are exposed to static electricity or electromagnetic waves
  - Use of our Products in proximity to heat-producing components, plastic cords, or other flammable items
  - Sealing or coating our Products with resin or other coating materials
  - Use of our Products without cleaning residue of flux (even if you use no-clean type fluxes, cleaning residue of flux is recommended); or Washing our Products by using water or water-soluble cleaning agents for cleaning residue after soldering
  - Use of the Products in places subject to dew condensation
- The Products are not subject to radiation-proof design.
- Please verify and confirm characteristics of the final or mounted products in using the Products.
- In particular, if a transient load (a large amount of load applied in a short period of time, such as pulse. is applied, confirmation of performance characteristics after on-board mounting is strongly recommended. Avoid applying power exceeding normal rated power; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.
- De-rate Power Dissipation (Pd) depending on Ambient temperature (Ta). When used in sealed area, confirm the actual ambient temperature.
- Confirm that operation temperature is within the specified range described in the product specification.
- ROHM shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this document.

## Precaution for Mounting / Circuit board design

- When a highly active halogenous (chlorine, bromine, etc.) flux is used, the residue of flux may negatively affect product performance and reliability.
- In principle, the reflow soldering method must be used on a surface-mount products, the flow soldering method must be used on a through hole mount products. If the flow soldering method is preferred on a surface-mount products, please consult with the ROHM representative in advance.

For details, please refer to ROHM Mounting specification

**Precautions Regarding Application Examples and External Circuits**

1. If change is made to the constant of an external circuit, please allow a sufficient margin considering variations of the characteristics of the Products and external components, including transient characteristics, as well as static characteristics.
2. You agree that application notes, reference designs, and associated data and information contained in this document are presented only as guidance for Products use. Therefore, in case you use such information, you are solely responsible for it and you must exercise your own independent verification and judgment in the use of such information contained in this document. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of such information.

**Precaution for Electrostatic**

This Product is electrostatic sensitive product, which may be damaged due to electrostatic discharge. Please take proper caution in your manufacturing process and storage so that voltage exceeding the Products maximum rating will not be applied to Products. Please take special care under dry condition (e.g. Grounding of human body / equipment / solder iron, isolation from charged objects, setting of ionizer, friction prevention and temperature / humidity control).

**Precaution for Storage / Transportation**

1. Product performance and soldered connections may deteriorate if the Products are stored in the places where:
  - [a] the Products are exposed to sea winds or corrosive gases, including Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, and NO<sub>2</sub>
  - [b] the temperature or humidity exceeds those recommended by ROHM
  - [c] the Products are exposed to direct sunshine or condensation
  - [d] the Products are exposed to high Electrostatic
2. Even under ROHM recommended storage condition, solderability of products out of recommended storage time period may be degraded. It is strongly recommended to confirm solderability before using Products of which storage time is exceeding the recommended storage time period.
3. Store / transport cartons in the correct direction, which is indicated on a carton with a symbol. Otherwise bent leads may occur due to excessive stress applied when dropping of a carton.
4. Use Products within the specified time after opening a humidity barrier bag. Baking is required before using Products of which storage time is exceeding the recommended storage time period.

**Precaution for Product Label**

QR code printed on ROHM Products label is for ROHM's internal use only.

**Precaution for Disposition**

When disposing Products please dispose them properly using an authorized industry waste company.

**Precaution for Foreign Exchange and Foreign Trade act**

Since concerned goods might be fallen under listed items of export control prescribed by Foreign exchange and Foreign trade act, please consult with ROHM in case of export.

**Precaution Regarding Intellectual Property Rights**

1. All information and data including but not limited to application example contained in this document is for reference only. ROHM does not warrant that foregoing information or data will not infringe any intellectual property rights or any other rights of any third party regarding such information or data.
2. ROHM shall not have any obligations where the claims, actions or demands arising from the combination of the Products with other articles such as components, circuits, systems or external equipment (including software).
3. No license, expressly or implied, is granted hereby under any intellectual property rights or other rights of ROHM or any third parties with respect to the Products or the information contained in this document. Provided, however, that ROHM will not assert its intellectual property rights or other rights against you or your customers to the extent necessary to manufacture or sell products containing the Products, subject to the terms and conditions herein.

**Other Precaution**

1. This document may not be reprinted or reproduced, in whole or in part, without prior written consent of ROHM.
2. The Products may not be disassembled, converted, modified, reproduced or otherwise changed without prior written consent of ROHM.
3. In no event shall you use in any way whatsoever the Products and the related technical information contained in the Products or this document for any military purposes, including but not limited to, the development of mass-destruction weapons.
4. The proper names of companies or products described in this document are trademarks or registered trademarks of ROHM, its affiliated companies or third parties.

**General Precaution**

1. Before you use our Products, you are requested to carefully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any ROHM's Products against warning, caution or note contained in this document.
2. All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sales representative.
3. The information contained in this document is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.