



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## SPECIFICATION

- Part No. : **TG.09.0113**
- Product Name : 4G/3G/2G Cellular Hinged SMA(M) Mount Monopole
- Feature : 700MHz to 3800MHz  
LTE\*/GSM/CDMA/HSPA/UMTS  
700\*/850/900/1700/1800/1900/2100/2300/3500/3700  
Rotatable hinge design for optimal reception  
\*LTE 700MHz Band Compatible only when connected  
directly on ground plane lengths of 60mm or more  
RoHS Compliant



## 1. Introduction

The TG.09 Penta-band Cellular Hinged Rotatable SMA antenna is a high efficiency monopole antenna. Compared to other much larger antennas on the market, it has superior wide-band high efficiency characteristics. This antenna is used by many of the leading wireless device providers in the world marketplace.

The unique rotatable hinge design enables the user to rotate the antenna to the best angle for an optimal cellular signal reception. As the upper antenna element can move in any direction, it also reduces damage from impact force from any angle to the antenna, compared to traditional hinged right angle or fixed right angle designs or straight antennas.

The tiny dimensions of this antenna coupled with excellent RF performance and an aesthetic high end design feel make it the ideal cellular antenna for routers, vehicle tracking devices, telematics devices, remote monitoring systems, and POS devices.

The TG.09, as all monopole antennas works best connected directly to the ground-plane of the device main-board. Taoglas offers support services to characterize antenna efficiency on your individual device ground-plane.

The TG.09 antenna also supports LTE 700MHz band applications when it is directly connected to ground-planes with lengths above 60mm.

Please contact Taoglas regional support center first if you wish to do PTCRB or network approvals with this antenna attached to your device, so we can check RF integration is correct and do a pre-test first to ensure optimized passive and active performance and a smooth and quick certification approval process.

This antenna also comes in a white version. TG.09.0113W

## 2. Specification

ELECTRICAL										
Communication System	4G/3G/2G Cellular									
	700 LTE	AMPS	GSM	DCS	PCS	UMTS	2300 LTE	2700 LTE	3500 LTE	3700 LTE
Frequency (MHz)	703~803	824 ~ 896	880 ~ 960	1710 ~ 1880	1850 ~ 1990	1710 ~ 2170	2300~2400	2490~2690	3400~3600	3600~3800
Efficiency (free space)*	18%	22%	22%	25%	30%	30%	17%	32%	28%	43%
Gain (dBi, free space)*	-3.0	-2.6	-3.0	0.9	0.9	0.9	-1.3	1.1	1.8	3.1
Efficiency (mounted on PCB)*	52%	58%	57%	61%	58%	54%	31%	59%	36%	37%
Gain (dBi, mounted on PCB)*	0.8	1.7	1.8	3.4	3.4	3.4	2.3	3.7	4.3	2.6
Impedance	50Ω									
Polarization	Linear									
Radiation Pattern	Omnidirectional									
Input Power	10W									
MECHANICAL										
Antenna Length	72 ± 1.5 mm									
Antenna Diameter	10 ± 0.3 mm									
Casing	POM									
Connector	SMA Male (Brass)									
Weight	8g									
ENVIRONMENTAL										
Temperature Range	-40°C to 85°C									
Storage Temperature	-40°C ~ +85°C									
Humidity	Non-condensing 65°C 95% RH									

\* Average efficiency and peak gain of antenna sitting 180° in Free Space and on 150\*90mm ground plane at the side of the PCB. Please refer to section 3 for testing detail.


### 3. Antenna Characteristics

#### 3.1 Test Setup


The TG.09 was measured and tested in four different environments

- a. Free space
- b. On the edge of a 150\*90mm ground plane - common size for IoT devices. TG.09 is mounted on the 90mm edge for testing.
- c. In the center of a 300\*300mm ground plane – simulate the effect of mounting in the center of a big ground plane.
- d. On the edge of a 300\*300mm ground plane - simulates the effect of mounting TG.09 on top of a large gateway/router.

Straight Position




Free Space



150mm x 90mm  
Ground Plane




300mm x 300mm  
Ground Plane Edge



300mm x 300mm  
Ground Pane Center


Antenna in 90° Bend Position




Free Space





150mm x 90mm  
Ground Plane



300mm x 300mm  
Ground Plane Edge





300mm x 300mm  
Ground Plane Center





Chamber Setup

### 3.2 Return Loss





### 3.3 VSWR









### 3.4 Efficiency



### 3.5 Peak Gain




### 3.6 Average Gain




# 4. Radiation Patterns


## 4.1 TG.09 in Free Space – Straight




## 4.2 TG.09 in Free Space – 90°




### 4.3 TG.09 on 150\*90mm Ground Plane – Straight



## 4.4 TG.09 on 150\*90mm Ground Plane – 90°




### 4.5 TG.09 on 300\*300mm Ground Plane Center – Straight







### 4.6 TG.09 on 300\*300mm Ground Plane Center – 90°



### 4.7 TG.09 on 300\*300mm Ground Plane Edge – Straight




### 4.8 TG.09 on 300\*300mm Ground Plane Edge – 90°




# 5.3D Radiation Pattern


## 5.1 Free Space – Straight




## 5.2 Free Space – 90°




### 5.3 150\*90mm Ground Plane – Straight



### 5.4 150\*90mm Ground Plane – 90°




## 5.5 300\*300mm Ground Plane Center – Straight





## 5.6 300\*300mm Ground Plane Center – 90°



## 5.7 300\*300mm Ground Plane Edge – Straight

