



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



- Ultra wide 4:1 input voltage 3 W DC/DC converter in a compact DIP-24 plastic case
- I/O isolation 5000 VACrms rated for 250 VACrms working voltage
- Certification according to IEC/EN/ES 60601-1 3rd edition for 2xMOPP
- Risk management process according to ISO 14971 including risk management file
- Acceptance criteria for electronic assemblies according to IPC-A-610 Level 3
- Low leakage current < 2µA
- Extended operating temperature range -40°C to 90°C.
- EMC compliance to IEC 60601-1-2 4th edition and EN55032 class A
- Operating up to 5000m altitude
- 5 year product warranty



The THM-3WI series is a range of medical 3 Watt DC/DC converters in DIP-24 plastic package and with ultra-wide 4:1 input voltage range. They provide a reinforced isolation system for 5000 VACrms isolation and a very low leakage current of less than 2 µA. The units are approved to IEC/EN/ES 60601-1 3rd edition for 2 × MOPP (Means Of Patient Protection) and come along with an ISO 14971 risk management file. Design and production conform to the quality management system ISO 13485. With a high efficiency of up to 87% and highest grade components the converters can reliably operate in an ambient temperature range of -40°C up to +90°C. They constitute a reliable solution not only for medical equipment but also for demanding ranges of application such as transportation, control & measurement or IGBT drivers.

Models				
Order code	Input voltage range	Output voltage	Output current max.	Efficiency typ.
THM 3-0510WI	4.5 – 9 VDC (5 VDC nominal)	3.3 VDC	1000 mA	81.0 %
THM 3-0511WI		5.0 VDC	600 mA	84.5 %
THM 3-0512WI		12 VDC	250 mA	85.5 %
THM 3-0513WI		15 VDC	200 mA	87.5 %
THM 3-0515WI		24 VDC	125 mA	85.5 %
THM 3-0521WI		±5.0 VDC	±300 mA	83.0 %
THM 3-0522WI		±12 VDC	±125 mA	86.0 %
THM 3-0523WI		±15 VDC	±100 mA	86.0 %
THM 3-2410WI	9.0 – 36 VDC (24 VDC nominal)	3.3 VDC	1000 mA	82.0 %
THM 3-2411WI		5.0 VDC	600 mA	84.5 %
THM 3-2412WI		12 VDC	250 mA	87.0 %
THM 3-2413WI		15 VDC	200 mA	87.0 %
THM 3-2415WI		24 VDC	125 mA	87.0 %
THM 3-2421WI		±5.0 VDC	±300 mA	83.0 %
THM 3-2422WI		±12 VDC	±125 mA	87.5 %
THM 3-2423WI		±15 VDC	±100 mA	86.0 %
THM 3-4810WI	18 – 75 VDC (48 VDC nominal)	3.3 VDC	1000 mA	81.0 %
THM 3-4811WI		5.0 VDC	600 mA	84.0 %
THM 3-4812WI		12 VDC	250 mA	87.0 %
THM 3-4813WI		15 VDC	200 mA	86.5 %
THM 3-4815WI		24 VDC	125 mA	86.5 %
THM 3-4821WI		±5.0 VDC	±300 mA	83.0 %
THM 3-4822WI		±12 VDC	±125 mA	86.0 %
THM 3-4823WI		±15 VDC	±100 mA	86.0 %

Input Specifications

Input current no load	5 Vin models: 20 mA typ. 24 Vin models: 6 mA typ. 48 Vin models: 4 mA typ.
Surge voltage (3 s max.)	5 Vin models: 16 V max. 24 Vin models: 50 V max. 48 Vin models: 100 V max.
Start-up voltage	5 Vin models: 4.5 VDC (or lower) 24 Vin models: 9 VDC (or lower) 48 Vin models: 18 VDC (or lower)
Startup time	30 ms
Under voltage shut down	5 Vin models: 4 VDC typ. 24 Vin models: 8 VDC typ. 48 Vin models: 16 VDC typ.
EMC emissions	– Conducted & Radiated input suppression – Application note for filter class B proposal EN 55011 limits to IEC 60601-1-2 4th edition EN 55032 class A (internal filter) www.tracopower.com/overview/thm3wi
EMC immunity	– Generic for Medical equipment – ESD (electrostatic discharge) – Radiated immunity – Fast transient / surge (with external input capacitor / diode) – Conducted immunity – Magnetic field immunity IEC/EN 60601-1-2 4th edition EN 61000-4-2, air ±8 kV, contact ±6 kV, perf. criteria A EN 61000-4-3, 10 V/m, perf. criteria A EN 61000-4-4, ±2 kV, perf. criteria A EN 61000-4-5, ±2 kV perf. criteria A 5 Vin models: Nippon chemi-con KY 1000 µF/ 25 V and reverse diode (Vishay V10P45) in parallel 24 Vin models: Nippon chemi-con KY 470 µF/ 50 V 48 Vin models: Nippon chemi-con KY 330 µF/ 100 V EN 61000-4-6, 10 Vrms, perf. criteria A EN 61000-4-8 100 A/m, continuous, perf. criteria A 1000 A/m, 1 sec., perf. criteria A
External input fuse required (recommended values, slow blow type)	5 Vin models: 2.5 A 24 Vin models: 1.5 A 48 Vin models: 1 A

Output Specifications

Voltage set accuracy	±1 % max.
Regulation	– Input variation single output: 0.2 % max. dual output: 0.5 % max. – Load variation (0 – 100 %) single output: 0.2 % max. dual output: 1.0 % max. – Cross regulation dual output: 5.0 % max. (asymmetrical load 25/100%)
Minimum load	not required
Ripple and noise (20 MHz Bandwidth)	3.3 & 5.0 Vout models: 30 mVp-p typ. with cap. 10 µF/25V X7R MLCC 12 & 15 Vout models: 40 mVp-p typ. with cap. 10 µF/25V X7R MLCC 24 Vout models: 50 mVp-p typ. with cap. 4.7 µF/50V X7R MLCC
Transient response	– Recovery time (25% load step change) 250 µs typ.
Over load protection	at 150 % typ. of Iout rated (hiccup mode)
Short circuit protection	Continuous, automatic recovery
Over voltage protection	– Single output 3.3 Vout models: 3.7 – 5.0 VDC 5.0 Vout models: 5.6 – 7.0 VDC 12 Vout models: 13.5 – 16.0 VDC 15 Vout models: 18.3 – 22.0 VDC 24 Vout models: 29.1 – 34.5 VDC – Dual output ±5 Vout models: 5.6 – 7.0 VDC ±12 Vout models: 13.5 – 18.2 VDC ±15 Vout models: 17.0 – 22.0 VDC

General Specifications

Capacitive load	– Single output	3.3 Vout models: 1'050 µF max. 5.0 Vout models: 750 µF max. 12 Vout models: 130 µF max. 15 Vout models: 100 µF max.
	– Dual output	24 Vout models: 39 µF max. ±5 Vout models: 430 µF max. (each output) ±12 Vout models: 75 µF max. (each output) ±15 Vout models: 56 µF max. (each output)
Temperature ranges	– Operating (designed for) – Rated according to IEC/EN 60601-1 – Case temperature – Storage temperature	–40°C to +90°C (without derating) –40°C to +80°C (without derating) +105°C max. –55°C to +125°C
Thermal impedance		18°C/W
Humidity (non condensing)		5 % to 95 % rel H max.
Isolation voltage (50 Hz, 60 s)	– to meet ES/IEC/EN 60601-1	5000 VACrms, rated for 250 VACrms working voltage, 2 × MOPP
Clearance/creepage		8 mm min.
Leakagecurrent (at 240 VAC, 60 Hz)		2 µA max.
Isolation capacitance (input/output)		17 pF max.
Altitude during operation		5000 m
Temperature coefficient		±0.02 %/K typ.
Reliability, calculated MTBF (MIL-HDBK-217F at +25°C, ground benign)		6'400'000 h
Switching frequency		150 kHz ±15 kHz (pulse width modulation)
Vibration and thermal shock resistance		according to MIL-STD-810F
Safety standards/approvals – Medical equipment		ANSI/AAMI ES60601-1:2005/(R)2012, IEC/EN60601-1 3rd edition www.tracopower.com/overview/thm3wi
	– Certification documents	
Environmental compliance – Reach		www.tracopower.com/info/reach-declaration.pdf
	– RoHS	RoHS directive 2011/65/EU

Physical Specifications

Casing material	non-conductive black plastic
Base material	non-conductive black plastic
Potting material	silicone (UL94 V-0 rated)
Package weight	14 g (0.48 oz)
Soldering temperature	265°C / 10 s max.




- The component is not be used in an oxygen rich environment.
- The component is not to be used in conjunction with flammable anaesthetics and agents.
- The component has to be disposed appropriately. Please refer to local regulations (Waste Electrical and Electronic Equipment).
- A modification of the component is not allowed.

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.


Outline Dimensions

Standard pinning



Standard Pinout		
Pin	Single	Dual
2	-Vin (GND)	-Vin (GND)
11	No con.	-Vout
14	+Vout	+Vout
16	-Vout	Common
22	+Vin (Vcc)	+Vin (Vcc)
23	+Vin (Vcc)	+Vin (Vcc)

Optional pinning: suffix **-A1**



Optional Pinout		
Pin	Single	Dual
1	+Vin (Vcc)	+Vin (Vcc)
11	No pin	Common
12	-Vout	No pin
13	+Vout	-Vout
15	No pin	+Vout
23	-Vin (GND)	-Vin (GND)
24	-Vin (GND)	-Vin (GND)

Remark: No suffix **-A1** for 5 Vin models. Corresponding parts are with THM 3 series by default. see www.tracopower.com/overview/thm3

Dimensions in [mm], () = Inch
 Tolerances ± 0.5 (± 0.02)
 Pin $\varnothing 0.6 \pm 0.1$ (0.024 ± 0.004)
 Pin pitch tolerances ± 0.25 (± 0.01)