

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







AMPROBE°



Data Sheet

THWD-5 Relative Humidity, Temperature Meter with Dew Point, Wet Bulb and Flexible Probe

The THWD-5 psychrometer is a microprocessor-based tester designed for HVAC and Plant Maintenance engineers and technicians. Easy and quick access to Wet bulb and Dew point values as well as Relative Humidity and Temperature. The THWD-5 is equipped with an extended probe for easy target access, a large dual LCD display, and is tripod mountable.

- Four measurements in one meter
- Relative Humidity, Temperature, Dew Point and Wet Bulb
- Extended probe for easy target access
- Large digital dual display with backlight
- Measure both relative humidity and temperature together
- Temperature in °C or °F, front panel selectable
- 0.1 degree resolution for temperature
- Minimum and Maximum measurements stored
- Data Hold to freeze last measurement reading
- Tripod mountable
- Includes deluxe hard carrying case, batteries and users manual

No hassle warranty

No waiting.





(note: \$500 MSLP limit)



THWD-5 RH, Temperature, DP, WB with Flex Probe

Data Sheet

Specifications

| • | |
|------------------------|--------------------------------------------------------------------------------|
| Range | RH: 0 to 100% |
| | Temperature: -10 to 60°C (14 to 140°F) |
| | DP: -73.4 to 59.9°C (-100 to 139.8°F) |
| | WB: -13.4 to 59.9°C (7.88 to 139.8°F) |
| Accuracy | RH: $\pm 3\%$ from 10 to 90% at 25°C and $\pm 5\%$ for others |
| | Temperature: ±0.6°C (±1°F) |
| Response Time | 60 seconds |
| Resolution | 0.1°C / 0.1°F |
| General Specifications | |
| Battery Life | 100 hours w/o backlight; 50 hours with backlight |
| Power Supply | 4 X 1.5V AAA Size (NEDA 24G or IEC R03) battery |
| Low Battery Indication | The "Ē∄" is displayed when the battery voltage drops below the operating level |
| Dimension | 175 x 69.85 x 33 mm (6.89 x 2.75 x 1.30 in.) |
| Weight | 0.869 Kg (1.92 Lb) |
| Environmental | |
| Operating Humidity | 100% RH |
| Operating Temperature | 0 to 50°C / 32 to122°F |
| Storage Temperature | -20 to 60°C / -4 to140°F |
| Altitude | 2000m, indoor operation |

Agency Approvals & Certifications



EN61326-1 This product complies with requirements of the following European Community Directives: 89/336/EEC (Electromagnetic Compatibility) and 73/23/EEC (Low Voltage) as amended by 93/68/EEC (CE Marking). However, electrical noise or intense electromagnetic fields in the vicinity of the equipment may disturb the measurement circuit. Measuring instruments will also respond to unwanted signals that may be present within the measurement circuit. Users should exercise care and take appropriate precautions to avoid misleading results when making measurements in the presence of electronic interference.

INCLUDED & REPLACEMENT PARTS

Carrying Case Instruction Manual

Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

Amprobe® Test Tools Europe

Amprobe Test Tools Europe Beha-Amprobe GmbH In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2008 Amprobe Test Tools, All rights reserved. 7/2008 3358058 Rev A