



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Description

The TLC271 operational amplifier combines a wide range of input offset voltage grades with low offset voltage drift and high input impedance. In addition, the TLC271 offers a bias-select mode that allows the user to select the best combination of power dissipation and AC performance for a particular application.

Using the bias-select option, these devices can be programmed to fit a wide range of applications. Three offset voltage grades are available, ranging from the low-cost TLC271 (10mV) to the TLC271B (2mV) low-offset version. The devices are offered in both commercial and industrial operating temperature ranges.

The extremely high input impedance and low bias currents, in conjunction with good common-mode and supply voltage rejection make these devices an excellent choice for high performance designs.


The devices also feature low-voltage single-supply operation with a common-mode input voltage range which includes the negative rail.

Features

- Wide range of supply voltages over specified temperature range:
0°C to 70°C . . . 3 V to 16 V
-40°C to 85°C . . . 4 V to 16 V
- Single-Supply Operation
- Common-Mode Input Voltage Range
- Extends Below the Negative Rail
- Low Noise:
20 nV/√Hz Typical @ f = 1kHz
(High-Bias Mode)
- Output Voltage Range Includes Negative Rail
- High Input Impedance
- ESD-Protection Circuitry
- Designed-In Latch-Up Immunity
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

Pin Assignments

(Top View)



Applications

With the programmability options of the TLC271, a designer can choose a very low current option allowing for extended battery life or choose a higher current option for more performance. It is possible to switch performance modes as the application demands change.

The TLC271 is well suited for many consumer audio, industrial and other low power applications.

- Audio
Microphone Preamplifier
Filtering – Equalizers
Signal Amplification
- Industrial
Power Supply
Instrumentation
Metering
- Medical
Portable Meters and Measurement
Instrumentation

Notes:

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

Ordering Information

TLC271-XXX - X



None: 10mV

A: 5mV

B: 2mV

C: Commercial

I: Industrial

S: SO-8

13: Tape & Reel

Device	Package Code	Offset Voltage	Operating Temperature Range	Packaging (Note 4)	13" Tape and Reel	
					Quantity	Part Number Suffix
TLC271CS-13	S	10mV	0 to 70°C	SO-8	2500/Tape & Reel	-13
TLC271ACS-13	S	5mV	0 to 70°C	SO-8	2500/Tape & Reel	-13
TLC271BCS-13	S	2mV	0 to 70°C	SO-8	2500/Tape & Reel	-13
TLC271IS-13	S	10mV	-40 to 85°C	SO-8	2500/Tape & Reel	-13
TLC271AIS-13	S	5mV	-40 to 85°C	SO-8	2500/Tape & Reel	-13
TLC271BIS-13	S	2mV	-40 to 85°C	SO-8	2500/Tape & Reel	-13

Note: 4. Pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.

Pin Descriptions

Pin Name	Pin number	Description
OFFSET N1	1	Offset Control Inverting Input
IN-	2	Inverting Input
IN+	3	Non-Inverting Input
GND	4	Ground
OFFSET N2	5	Offset Control Non-Inverting Input
OUT	6	Output
V _{DD}	7	Supply
BIAS SELECT	8	Bias Mode Select

Absolute Maximum Ratings (Notes 5, 6, 7, 8, 9)

Symbol	Parameter	Rating	Unit
V_{DD}	Supply Voltage (Note 6)	18	V
V_{ID}	Differential Input Voltage (Note 7)	$\pm V_{DD}$	V
V_{IN}	Input Voltage Range (either input)	-0.3 to V_{DD}	V
I_{IN}	Input Current	± 5	mA
I_o	Output Current	± 30	mA
	Output Short-Circuit to GND (Note 8)	Continuous	—
P_D	Power Dissipation (Note 9)	1065	mW
T_A	Operating Temperature Range	C Grade 0 to +70	°C
		I Grade -40 to +85	
T_J	Operating Junction Temperature	150	°C
T_{ST}	Storage Temperature Range	-65 to +150	°C
ESD HBM	Human Body Model ESD Protection (1.5kΩ in series with 100pF)	1.5	kV

- Notes:
- 5. Stresses beyond those listed under absolute maximum ratings may cause permanent damage to the device. These are stress ratings only; functional operation of the device at these or any other conditions beyond those indicated under recommended operating conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
 - 6. All voltage values, except differential voltages, are with respect to ground.
 - 7. Differential input voltages are at IN_+ with respect to IN_- .
 - 8. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.
 - 9. For operating at high temperatures, the TLC271 must be derated 8.5mW/°C to zero based on a +150°C maximum junction temperature and a thermal resistance of +117 °C/W when the device is soldered to a printed circuit board, operating in a still air ambient.

Recommended Operating Conditions

Symbol	Parameter	C grade		I grade		Unit
		Min	Max	Min	Max	
V_{DD}	Supply Voltage	3	16	4	16	V
V_{IC}	Common Mode Input Voltage	$V_{DD} = 5V$	-0.2	3.5	-0.2	V
		$V_{DD} = 10V$	-0.2	8.5	-0.2	
T_A	Operating Free Air Temperature	0	+70	-40	+85	°C

Electrical Characteristics

High Bias Mode								
Parameter			Conditions	T _A	TLC271C, TLC271AC, TLC271BC			Unit
					V _{DD} = 5V		V _{DD} = 10V	
V _I ^o	Input Offset Voltage	TLC271C	V _o = 1.4V, V _{IC} = 0V, R _S = 50Ω, R _L = 10kΩ	+25°C	—	1.1	10	—
		TLC271AC		0 to +70°C	—	—	12	—
		TLC271BC		+25°C	—	0.9	5	—
				0 to 70°C	—	—	6.5	—
				25°C	—	0.34	2	—
				0 to +70°C	—	—	3	—
α _{V_I^o}	Average Temperature Coefficient of Input Offset Voltage	—	+25°C to 70°C	—	1.8	—	2	μV/°C
I _I ^o	Input Offset Current (Note 10)	V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25°C	—	0.1	60	—	0.1
			+70°C	—	7	300	—	7
I _{IB}	Input Bias Current (Note 10)	V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25°C	—	0.6	60	—	0.7
			+70°C	—	40	600	—	50
V _{ICR}	Common Mode Input Voltage (Note 11)	—	+25°C	-0.2 to 4	-0.3 to 4.2	—	-0.2 to 9	-0.3 to 9.2
			0 to +70°C	-0.2 to 3.5	—	—	-0.2 to 8.5	—
V _H	High Level Output Voltage	V _{ID} = 100mV, R _L = 10kΩ	+25°C	3.2	3.8	—	8	8.5
			0°C	3	3.8	—	7.8	8.5
			+70°C	3	3.8	—	7.8	8.4
V _L	Low Level Output Voltage	V _{ID} = -100mV, I _L = 0	+25°C	—	0	50	—	0
			0°C	—	0	50	—	0
			+70°C	—	0	50	—	0
A _{VD}	Large Signal Differential Voltage Gain	R _L = 10kΩ (Note 12)	+25°C	5	23	—	10	36
			0°C	4	27	—	7.5	42
			+70°C	4	20	—	7.5	32
CMRR	Common Mode Rejection Ratio	V _{IC} = V _{ICRmin}	+25°C	65	80	—	65	85
			0°C	60	84	—	60	88
			+70°C	60	85	—	60	88
k _{SVR}	Supply Voltage Rejection Ratio ($\Delta V_{DD}/\Delta V_I$)	V _{DD} = 5V to 10V, V _o = 1.4V	+25°C	65	95	—	65	95
			0°C	60	94	—	60	94
			+70°C	60	96	—	60	96
I _{I(SEL)}	Input Current (BIAS SELECT)	V _{I(SEL)} = 0	+25°C	—	-1.4	—	—	-1.9
I _{DD}	Supply Current	V _o = V _{DD} /2, V _{IC} = V _{DD} /2, No load	+25°C	—	675	1600	—	950
			0°C	—	775	1800	—	1125
			+70°C	—	575	1300	—	750
							2000	2200
							750	1700

Notes: 10. The typical values of input bias current and input offset current below 5pA were calculated.

11. This range also applies to each input individually.

12. At V_{DD} = 5 V, V_o = 0.25 V to 2 V; at V_{DD} = 10 V, V_o = 1 V to 6 V.

Electrical Characteristics

High bias mode			Conditions	T _A	TLC271I, TLC271AI, TLC271BI						Unit			
Parameter		V _{DD} = 5V			V _{DD} = 10V			Min	Typ	Max				
Min	Typ				Min	Typ.	Max							
V _I ^o	Input Offset Voltage	TLC271I V _o = 1.4V, V _{IC} = 0V, R _S = 50Ω, R _L = 10kΩ	+25 °C	—	1.1	10	—	1.1	10	—	mV			
			-40 to 85 °C	—	—	13	—	—	13	—				
			+25 °C	—	0.9	5	—	0.9	5	—				
		TLC271AI V _o = V _{DD} /2, V _{IC} = V _{DD} /2	-40 to 85 °C	—	—	7	—	—	7	—				
			+25 °C	—	0.34	2	—	0.39	2	—				
			-40 to 85 °C	—	—	3.5	—	—	3.5	—				
α _{V_I^o}	Average Temperature Coefficient of Input Offset Voltage	—	+25 to 85 °C	—	1.8	—	—	2	—	—	μV/°C			
I _I ^o	Input Offset Current (Note 13)	V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25 °C	—	0.1	60	—	0.1	60	—	pA			
			+85 °C	—	24	1000	—	26	1000	—				
I _{IB}	Input Bias Current (Note 13)	V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25 °C	—	0.6	60	—	0.7	60	—	pA			
			+85 °C	—	200	2000	—	220	2000	—				
V _{ICR}	Common Mode Input Voltage (Note 14)	—	+25 °C	-0.2 to 4	-0.3 to 4.2	—	-0.2 to 9	-0.3 to 9.2	—	—	V			
			-40 to +85 °C	-0.2 to 3.5	—	—	-0.2 to 8.5	—	—	—	V			
V _H	High Level Output Voltage	V _{ID} = 100mV, R _L = 10kΩ	+25 °C	3.2	3.8	—	8	8.5	—	—	V			
			-40 °C	3	3.8	—	7.8	8.5	—	—				
			+85 °C	3	3.8	—	7.8	8.5	—	—				
V _L	Low Level Output Voltage	V _{ID} = -100mV, I _L = 0	+25 °C	—	0	50	—	0	50	—	mV			
			-40 °C	—	0	50	—	0	50	—				
			+85 °C	—	0	50	—	0	50	—				
A _{VD}	Large Signal Differential Voltage Gain	R _L = 10kΩ (Note 15)	+25 °C	5	23	—	10	36	—	—	V/mV			
			-40 °C	3.5	32	—	7	46	—	—				
			+85 °C	3.5	19	—	7	31	—	—				
CMRR	Common Mode Rejection Ratio	V _{IC} = V _{ICRmin}	+25 °C	65	80	—	65	85	—	—	dB			
			-40 °C	60	81	—	60	87	—	—				
			+85 °C	60	86	—	60	88	—	—				
k _{SVR}	Supply Voltage Rejection Ratio (ΔV _{DD} /ΔV _I ^o)	V _{DD} = 5V to 10V, V _o = 1.4V	+25 °C	65	95	—	65	95	—	—	dB			
			-40 °C	60	92	—	60	92	—	—				
			+85 °C	60	96	—	60	96	—	—				
I _{I(SEL)}	Input Current (BIAS SELECT)	V _{I(SEL)} = 0	+25 °C	—	-1.4	—	—	-1.9	—	—	μA			
I _{DD}	Supply Current	V _o = V _{DD} /2, V _{IC} = V _{DD} /2, No load	+25 °C	—	675	1600	—	950	2000	—	μA			
			-40 °C	—	950	2200	—	1375	2500	—				
			+85 °C	—	525	1200	—	725	1600	—				

Notes: 13. The typical values of input bias current and input offset current below 5pA were calculated.

14. This range also applies to each input individually.

15. At V_{DD} = 5 V, V_o = 0.25 V to 2 V; at V_{DD} = 10 V, V_o = 1 V to 6 V.

Electrical Characteristics

High bias mode: $V_{DD} = 5V$

Parameter		Conditions		T_A	TLC271C, TLC271AC, TLC271BC			Unit
					Min	Typ	Max	
SR	Slew Rate at Unity Gain	$R_L = 10k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25 °C	—	3.6	—	V/ μ s
				0 °C	—	4	—	
				+70 °C	—	3	—	
				+25 °C	—	2.9	—	
			$V_{I(PP)} = 2.5V$	0 °C	—	3.1	—	
				+70 °C	—	2.5	—	
				+25 °C	—	25	—	
				See Figure 93	—	—	—	
V_n	Equivalent Input Noise Voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25 °C	—	25	—	nV/ \sqrt{Hz}
B^o_M	Maximum Output Swing Bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 10k\Omega$ See Figure 92	$V_{I(PP)} = 1V$	+25 °C	—	200	—	kHz
				0 °C	—	220	—	
				+70 °C	—	140	—	
B_1	Unity Gain Bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25 °C	—	2.2	—	MHz
				0 °C	—	2.5	—	
				+70 °C	—	1.8	—	
ϕ_m	Phase Margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25 °C	—	49°	—	—
				0 °C	—	50°	—	
				+70 °C	—	46°	—	

High bias mode: $V_{DD} = 10V$

Parameter		Conditions		T_A	TLC271C, TLC271AC, TLC271BC			Unit
					Min	Typ	Max	
SR	Slew Rate at Unity Gain	$R_L = 10k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25 °C	—	5.3	—	V/ μ s
				0 °C	—	5.9	—	
				+70 °C	—	4.3	—	
				+25 °C	—	4.6	—	
			$V_{I(PP)} = 5.5V$	0 °C	—	5.1	—	
				+70 °C	—	3.8	—	
				+25 °C	—	25	—	
				See Figure 93	—	—	—	
B^o_M	Maximum Output Swing Bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 10k\Omega$ See Figure 92	$V_{I(PP)} = 1V$	+25 °C	—	200	—	kHz
				0 °C	—	220	—	
				+70 °C	—	140	—	
B_1	Unity Gain Bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25 °C	—	2.2	—	MHz
				0 °C	—	2.5	—	
				+70 °C	—	1.8	—	
ϕ_m	Phase Margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25 °C	—	49°	—	—
				0 °C	—	50°	—	
				+70 °C	—	46°	—	

Electrical Characteristics

High bias mode: $V_{DD} = 5V$

Parameter		Conditions		T_A	TLC271I, TLC271AI, TLC271BI			Unit
					Min	Typ	Max	
SR	Slew rate at unity gain	$R_L = 10k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	3.6	—	V/ μ s
				-40°C	—	4.5	—	
				+85°C	—	2.8	—	
		See Figure 92	$V_{I(PP)} = 2.5V$	+25°C	—	2.9	—	
				-40°C	—	3.5	—	
				+85°C	—	2.3	—	
V_n	Equivalent input noise voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25°C	—	25	—	nV/ \sqrt{Hz}
B_{oM}	Maximum output swing bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 10k\Omega$ See Figure 92		+25°C	—	320	—	kHz
				-40°C	—	380	—	
				+85°C	—	250	—	
B_1	Unity gain bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94		+25°C	—	1.7	—	MHz
				-40°C	—	2.6	—	
				+85°C	—	1.2	—	
ϕ_m	Phase margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94		+25°C	—	46°	—	—
				-40°C	—	49°	—	
				+85°C	—	43°	—	

High bias mode: $V_{DD} = 10V$

Parameter		Conditions		T_A	TLC271I, TLC271AI, TLC271BI			Unit
					Min	Typ	Max	
SR	Slew rate at unity gain	$R_L = 10k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	5.3	—	V/ μ s
				-40°C	—	6.8	—	
				+85°C	—	4	—	
		See Figure 92	$V_{I(PP)} = 5.5V$	+25°C	—	4.6	—	
				-40°C	—	5.8	—	
				+85°C	—	3.5	—	
V_n	Equivalent input noise voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25°C	—	25	—	nV/ \sqrt{Hz}
B_{oM}	Maximum output swing bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 10k\Omega$ See Figure 92		+25°C	—	200	—	kHz
				-40°C	—	260	—	
				+85°C	—	130	—	
B_1	Unity gain bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94		+25°C	—	2.2	—	MHz
				-40°C	—	3.1	—	
				+85°C	—	1.7	—	
ϕ_m	Phase margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94		+25°C	—	49°	—	—
				-40°C	—	52°	—	
				+85°C	—	46°	—	

Electrical Characteristics

Medium bias mode								
Parameter			Conditions	TA	TLC271C, TLC271AC, TLC271BC			Unit
					V _{DD} = 5V		V _{DD} = 10V	
V _I	Input Offset Voltage	TLC271C	V _o = 1.4V, V _{IC} = 0V, R _S = 50Ω, R _L = 100kΩ	+25°C	—	1.1	10	—
		TLC271AC		0 to +70°C	—	—	12	—
		TLC271BC		+25°C	—	0.9	5	—
				0 to +70°C	—	—	6.5	—
				+25°C	—	0.25	2	—
				0 to +70°C	—	—	3	—
αV _I	Average temperature coefficient of input offset voltage			25 to +70°C	1.7		2.1	
I _I	Input offset current (Note 16)	V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25°C	—	0.1	60	—	0.1
			+70°C	—	7	300	—	7
I _{IB}	Input bias current (Note 16)	V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25°C	—	0.6	60	—	0.7
			+70°C	—	40	600	—	50
V _{ICR}	Common mode input voltage (Note 17)		+25°C	-0.2 to 4	-0.3 to 4.2	—	-0.2 to 9	-0.3 to 9.2
			0 to +70°C	-0.2 to 3.5	—	—	-0.2 to 8.5	—
V _{OH}	High level output voltage	V _{ID} = 100mV, R _L = 100kΩ	+25°C	3.2	3.9	—	8	8.7
			0°C	3	3.9	—	7.8	8.7
			+70°C	3	4	—	7.8	8.7
V _{OL}	Low level output voltage	V _{ID} = -100mV, I _O = 0	+25°C	—	0	50	—	0
			0°C	—	0	50	—	0
			+70°C	—	0	50	—	0
AVD	Large signal differential voltage gain	R _L = 100kΩ (Note 18)	+25°C	25	170	—	25	275
			0°C	15	200	—	15	320
			+70°C	15	140	—	15	230
CMRR	Common mode rejection ratio	V _{IC} = V _{ICRmin}	+25°C	65	91	—	65	94
			0°C	60	91	—	60	94
			+70°C	60	92	—	60	94
k _{SVR}	Supply voltage rejection ratio (ΔV _{DD} /ΔV _I)	V _{DD} = 5V to 10V, V _o = 1.4V	+25°C	70	93	—	70	93
			0°C	60	92	—	60	92
			+70°C	60	94	—	60	94
I _{I(SEL)}	Input current (BIAS SELECT)	V _{I(SEL)} = 0	+25°C	—	-130	—	-160	—
I _{DD}	Supply current	V _o = V _{DD} /2, V _{IC} = V _{DD} /2, No load	+25°C	—	105	280	—	143
			0°C	—	125	320	—	173
			+70°C	—	85	220	—	110
280								

- Notes:
- 16. The typical values of input bias current and input offset current below 5pA were calculated.
 - 17. This range also applies to each input individually.
 - 18. At V_{DD} = 5 V, V_o = 0.25 V to 2 V; at V_{DD} = 10 V, V_o = 1 V to 6 V.

Electrical Characteristics

Medium bias mode												
Parameter			Conditions	T _A	TLC271I, TLC271AI, TLC271BI						Unit	
					V _{DD} = 5V			V _{DD} = 10V				
V _I ^o	Input Offset Voltage	TLC271I TLC271AI TLC271BI	V _o = 1.4V, V _{IC} = 0V, R _S = 50Ω, R _L = 100kΩ	+25 °C	—	1.1	10	—	1.1	10	mV	
				-40 to +85 °C	—	—	13	—	—	13		
				+25 °C	—	0.9	5	—	0.9	5		
				-40 to +85 °C	—	—	7	—	—	7		
				+25 °C	—	0.25	2	—	0.26	2		
				-40 to +85 °C	—	—	3.5	—	—	3.5		
α _{V_I^o}	Average temperature coefficient of input offset voltage		V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25 to +85 °C	1.7			2.1			μV/°C	
I _{I^o}	Input offset current (Note 19)			+25 °C	—	0.1	60	—	0.1	60	pA	
I _{IB}	Input bias current (Note 19)		V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25 °C	—	0.6	60	—	0.7	60	pA	
V _{ICR}	Common mode input voltage (Note 20)			+85 °C	—	200	2000	—	220	2000		
V _H	High level output voltage		V _{ID} = 100mV, R _L = 100kΩ	+25 °C	-0.2 to 4	-0.3 to 4.2	—	-0.2 to 9	-0.3 to 9.2	—	V	
				-40 to +85 °C	-0.2 to 3.5	—	—	-0.2 to 8.5	—	—	V	
				+25 °C	3.2	3.9	—	8	8.7	—	V	
V _L	Low level output voltage		V _{ID} = -100mV, I _L = 0	-40 °C	3	3.9	—	7.8	8.7	—		
				+85 °C	3	4	—	7.8	8.7	—		
				+25 °C	—	0	50	—	0	50	mV	
A _{VD}	Large signal differential voltage gain		R _L = 100kΩ (Note 21)	-40 °C	—	0	50	—	0	50		
				+85 °C	—	0	50	—	0	50		
				+25 °C	25	170	—	25	275	—	V/mV	
CMRR	Common mode rejection ratio		V _{IC} = V _{ICRmin}	-40 °C	15	270	—	15	390	—		
				+85 °C	15	130	—	15	220	—		
				+25 °C	65	91	—	65	94	—	dB	
K _{SVR}	Supply voltage rejection ratio (ΔV _{DD} /ΔV _{I^o})		V _{DD} = 5V to 10V, V _o = 1.4V	-40 °C	60	90	—	60	93	—		
				+85 °C	60	90	—	60	94	—		
				+25 °C	70	93	—	70	93	—	dB	
I _{I(SEL)}	Input current (BIAS SELECT)		V _{I(SEL)} = 0	-40 °C	60	91	—	60	91	—		
				+85 °C	60	94	—	60	94	—		
				+25 °C	—	-130	—	—	-160	—	nA	
I _{DD}	Supply current		V _o = V _{DD} /2, V _{IC} = V _{DD} /2, No load	+25 °C	—	105	280	—	143	300	μA	
				-40 °C	—	158	400	—	225	450		
				+85 °C	—	80	200	—	103	260		

Notes: 19. The typical values of input bias current and input offset current below 5pA were calculated.

20. This range also applies to each input individually.

21. At V_{DD} = 5 V, V_o = 0.25 V to 2 V; at V_{DD} = 10 V, V_o = 1 V to 6 V.

Electrical Characteristics

Medium bias mode: $V_{DD} = 5V$		Parameter	Conditions	T_A	TLC271C, TLC271AC, TLC271BC			Unit			
					Min	Typ	Max				
SR	Slew rate at unity gain				+25°C	—	0.43				
	$R_L = 100k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	0°C	—	0.46	—	V/ μ s				
			+70°C	—	0.36	—					
			+25°C	—	0.4	—					
		$V_{I(PP)} = 2.5V$	0°C	—	0.43	—					
			+70°C	—	0.34	—					
			25°C	—	32	—	nV/ \sqrt{Hz}				
			0°C	—	55	—					
B ^o M	Maximum output swing bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 100k\Omega$ See Figure 92	See	+70°C	—	60	—	kHz			
				+25°C	—	50	—				
				0°C	—	525	—				
B ₁	Unity gain bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	See	+70°C	—	600	—	MHz			
				+25°C	—	400	—				
				0°C	—	40°	—				
ϕ_m	Phase margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	See Figure 94	+70°C	—	41°	—	—			
				+25°C	—	39°	—				
				0°C	—	—	—				
Medium bias mode: $V_{DD} = 10V$		Parameter	Conditions	T_A	TLC271C, TLC271AC, TLC271BC			Unit			
					Min	Typ	Max				
SR	Slew Rate at Unity Gain	$R_L = 100k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.62	—	V/ μ s			
				0°C	—	0.67	—				
				+70°C	—	0.51	—				
				+25°C	—	0.56	—				
			$V_{I(PP)} = 5.5V$	0°C	—	0.61	—	kHz			
				+70°C	—	0.46	—				
				+25°C	—	35	—				
				0°C	—	40	—				
B ^o M	Maximum Output Swing Bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 100k\Omega$ See Figure 92	See	+70°C	—	30	—	MHz			
				+25°C	—	635	—				
				0°C	—	710	—				
B ₁	Unity Gain Bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	See	+70°C	—	510	—	—			
				+25°C	—	43°	—				
				0°C	—	44°	—				
ϕ_m	Phase Margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	See Figure 94	+70°C	—	42°	—				

Electrical Characteristics

Medium bias mode: $V_{DD} = 5V$									
Parameter		Conditions		T_A	TLC271I, TLC271AI, TLC271BI		Unit		
					Min	Typ			
SR	Slew rate at unity gain	$R_L = 100k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.43	—		
				-40°C	—	0.51	—		
				+85°C	—	0.35	—		
		See Figure 92	$V_{I(PP)} = 2.5V$	+25°C	—	0.4	—		
				-40°C	—	0.48	—		
				+85°C	—	0.32	—		
V_n	Equivalent input noise voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25°C	—	32	—		
$B^{\circ}M$	Maximum output swing bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 100k\Omega$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	55	—		
				-40°C	—	75	—		
				+85°C	—	45	—		
B_1	Unity gain bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	525	—		
				-40°C	—	770	—		
				+85°C	—	370	—		
ϕ_m	Phase margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	40°	—		
				-40°C	—	43°	—		
				+85°C	—	38°	—		
Medium bias mode: $V_{DD} = 10V$									
Parameter		Conditions		T_A	TLC271I, TLC271AI, TLC271BI		Unit		
					Min	Typ			
SR	Slew Rate at Unity Gain	$R_L = 100k\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.62	—		
				-40°C	—	0.77	—		
				+85°C	—	0.47	—		
		See Figure 92	$V_{I(PP)} = 5.5V$	+25°C	—	0.56	—		
				-40°C	—	0.7	—		
				+85°C	—	0.44	—		
V_n	Equivalent Input Noise Voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25°C	—	32	—		
$B^{\circ}M$	Maximum Output Swing Bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 100k\Omega$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	35	—		
				-40°C	—	45	—		
				+85°C	—	25	—		
B_1	Unity Gain Bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	635	—		
				-40°C	—	880	—		
				+85°C	—	480	—		
ϕ_m	Phase Margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	43°	—		
				-40°C	—	46°	—		
				+85°C	—	41°	—		

Electrical Characteristics

Low bias mode												
Parameter			Conditions	T _A	TLC271C, TLC271AC, TLC271BC					Unit		
					V _{DD} = 5V			V _{DD} = 10V				
					Min	Typ	Max	Min	Typ.			
V _I ^o	Input Offset Voltage	TLC271C	V _o = 1.4V, V _{IC} = 0V, R _S = 50Ω, R _L = 1MΩ	+25°C	—	1.1	10	—	1.1	10	mV	
		TLC271AC		0 to +70°C	—	—	12	—	—	12		
		TLC271BC		+25°C	—	0.9	5	—	0.9	5		
				0 to +70°C	—	—	6.5	—	—	6.5		
				+25°C	—	0.24	2	—	0.26	2		
				0 to +70°C	—	—	3	—	—	3		
αV _I ^o	Average Temperature Coefficient of Input Offset Voltage		—	+25 to +70°C	1.1			1			μV/°C	
I _I ^o	Input Offset Current (Note 22)		V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25°C	—	0.1	60	—	0.1	60	pA	
				+70°C	—	7	300	—	8	300		
I _{IB}	Input Bias Current (Note 22)		V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25°C	—	0.6	60	—	0.7	60	pA	
				+70°C	—	40	600	—	50	600		
V _{ICR}	Common Mode Input Voltage (Note 23)		—	+25°C	-0.2 to 4	-0.3 to 4.2	—	-0.2 to 9	-0.3 to 9.2	—	V	
				0 to +70°C	-0.2 to 3.5	—	—	-0.2 to 8.5	—	—	V	
V _H	High Level Output Voltage		V _{ID} = 100mV, R _L = 1MΩ	+25°C	3.2	4.1	—	8	8.9	—	V	
				0°C	3	4.1	—	7.8	8.9	—		
				+70°C	3	4.2	—	7.8	8.9	—		
V _L	Low Level Output Voltage		V _{ID} = -100mV, I _L = 0	+25°C	—	0	50	—	0	50	mV	
				0°C	—	0	50	—	0	50		
				+70°C	—	0	50	—	0	50		
A _{VD}	Large Signal Differential Voltage Gain		R _L = 1MΩ (Note 24)	+25°C	50	520	—	50	870	—	V/mV	
				0°C	50	700	—	50	1030	—		
				+70°C	50	380	—	50	660	—		
CMRR	Common Mode Rejection Ratio		V _{IC} = V _{ICRmin}	+25°C	65	94	—	65	97	—	dB	
				0°C	60	95	—	60	97	—		
				+70°C	60	95	—	60	97	—		
k _{SVR}	Supply Voltage Rejection Ratio (ΔV _{DD} /ΔV _I ^o)		V _{DD} = 5V to 10V, V _o = 1.4V	+25°C	70	97	—	70	97	—	dB	
				0°C	60	97	—	60	97	—		
				+70°C	60	98	—	60	98	—		
I _{I(SEL)}	Input Current (BIAS SELECT)		V _{I(SEL)} = 0	+25°C	—	65	—	—	95	—	nA	
I _{DD}	Supply Current		V _o = V _{DD} /2, V _{IC} = V _{DD} /2, No load	+25°C	—	10	17	—	14	23	μA	
				0°C	—	12	21	—	18	33		
				+70°C	—	8	14	—	11	20		

Notes:

- 22. The typical values of input bias current and input offset current below 5pA were calculated.

- 23. This range also applies to each input individually.

- 24. At V_{DD} = 5 V, V_o = 0.25 V to 2 V; at V_{DD} = 10 V, V_o = 1 V to 6 V.

Electrical Characteristics

Low bias mode											
Parameter			Conditions	T _A	TLC271I, TLC271AI, TLC271BI						Unit
					V _{DD} = 5V			V _{DD} = 10V			
V _I ^o	Input Offset Voltage	TLC271I	V _o = 1.4V, V _{IC} = 0V, R _S = 50Ω, R _L = 1MΩ	+25 °C	—	1.1	10	—	1.1	10	mV
		TLC271AI		-40 to +85 °C	—	—	13	—	—	13	
		TLC271BI		+25 °C	—	0.9	5	—	0.9	5	
				-40 to +85 °C	—	—	7	—	—	7	
				+25 °C	—	0.24	2	—	0.26	2	
				-40 to +85 °C	—	—	3.5	—	—	3.5	
α _{V_I^o}	Average Temperature Coefficient of Input Offset Voltage			+25 to +85 °C	1.1			1			μV/°C
I _I ^o	Input Offset Current (Note 25)		V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25 °C	—	0.1	60	—	0.1	60	pA
I _{IB}	Input Bias Current (Note 25)			+85 °C	—	24	1000	—	26	1000	
V _{ICR}	Common Mode Input Voltage (Note 26)		V _o = V _{DD} /2, V _{IC} = V _{DD} /2	+25 °C	—	0.6	60	—	0.7	60	pA
		+85 °C		—	200	2000	—	220	2000		
		—	+25 °C	-0.2 to 4	-0.3 to 4.2	—	-0.2 to 9	-0.3 to 9.2	—	V	
			-40 to +85 °C	-0.2 to 3.5	—	—	-0.2 to 8.5	—	—	V	
V _H	High Level Output Voltage		V _{ID} = 100mV, R _L = 1MΩ	+25 °C	3	4.1	—	8	8.9	—	V
		-40 °C		3	4.1	—	7.8	8.9	—		
		+85 °C		3	4.2	—	7.8	8.9	—		
V _L	Low Level Output Voltage		V _{ID} = -100mV, I _L = 0	+25 °C	—	0	50	—	0	50	mV
		-40 °C		—	0	50	—	0	50		
		+85 °C		—	0	50	—	0	50		
A _{VD}	Large Signal Differential Voltage Gain		R _L = 1MΩ (Note 27)	+25 °C	50	520	—	50	870	—	V/mV
		-40 °C		50	900	—	50	1550	—		
		+85 °C		50	330	—	50	585	—		
CMRR	Common Mode Rejection Ratio		V _{IC} = V _{ICRmin}	+25 °C	65	94	—	65	97	—	dB
		-40 °C		60	95	—	60	97	—		
		+85 °C		60	95	—	60	98	—		
k _{SVR}	Supply Voltage Rejection Ratio (ΔV _{DD} /ΔV _I ^o)		V _{DD} = 5V to 10V, V _o = 1.4V	+25 °C	70	97	—	70	97	—	dB
		-40 °C		60	97	—	60	97	—		
		+85 °C		60	98	—	60	98	—		
I _{I(SEL)}	Input Current (BIAS SELECT)		V _{I(SEL)} = 0	+25 °C	—	65	—	—	95	—	nA
I _{DD}	Supply Current		V _o = V _{DD} /2, V _{IC} = V _{DD} /2, No load	+25 °C	—	10	17	—	14	23	μA
		-40 °C		—	16	27	—	25	43		
		+85 °C		—	17	13	—	10	18		

Notes: 25. The typical values of input bias current and input offset current below 5pA were calculated.

26. This range also applies to each input individually.

27. At V_{DD} = 5 V, V_o = 0.25 V to 2 V; at V_{DD} = 10 V, V_o = 1 V to 6 V.

Electrical Characteristics

Low bias mode: $V_{DD} = 5V$									
Parameter		Conditions		T_A	TLC271C, TLC271AC, TLC271BC		Unit		
					Min	Typ			
SR	Slew Rate at Unity Gain	$R_L = 1M\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.03	—		
				0°C	—	0.04	—		
				+70°C	—	0.03	—		
		See Figure 92	$V_{I(PP)} = 2.5V$	+25°C	—	0.03	—		
				0°C	—	0.03	—		
				+70°C	—	0.02	—		
V_n	Equivalent Input Noise Voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25°C	—	68	—		
B^o_M	Maximum Output Swing Bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 1M\Omega$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	5	—		
				0°C	—	6	—		
				+70°C	—	4.5	—		
B_1	Unity Gain Bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	85	—		
				0°C	—	100	—		
				+70°C	—	65	—		
ϕ_m	Phase Margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	34°	—		
				0°C	—	36°	—		
				+70°C	—	30°	—		
Low bias mode: $V_{DD} = 10V$									
Parameter		Conditions		T_A	TLC271C, TLC271AC, TLC271BC		Unit		
					Min	Typ			
SR	Slew Rate at Unity Gain	$R_L = 1M\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.05	—		
				0°C	—	0.05	—		
				+70°C	—	0.04	—		
		See Figure 92	$V_{I(PP)} = 5.5V$	+25°C	—	0.04	—		
				0°C	—	0.05	—		
				+70°C	—	0.04	—		
V_n	Equivalent Input Noise Voltage	$F = 1kHz$, $R_S = 20\Omega$ See Figure 93		+25°C	—	68	—		
B^o_M	Maximum Output Swing Bandwidth	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 1M\Omega$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	1	—		
				0°C	—	1.3	—		
				+70°C	—	0.9	—		
B_1	Unity Gain Bandwidth	$V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	110	—		
				0°C	—	125	—		
				+70°C	—	90	—		
ϕ_m	Phase Margin	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$ See Figure 94	$V_{I(PP)} = 1V$	+25°C	—	38°	—		
				0°C	—	40°	—		
				+70°C	—	34°	—		

Electrical Characteristics

Low bias mode: $V_{DD} = 5V$

Parameter		Conditions	T_A	TLC271I, TLC271AI, TLC271BI			Unit
				Min	Typ	Max	
SR	Slew Rate at Unity Gain	$R_L = 1M\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.03	—
				-40°C	—	0.04	—
				+85°C	—	0.03	—
				+25°C	—	0.03	—
		See Figure 92	$V_{I(PP)} = 2.5V$	-40°C	—	0.04	—
				+85°C	—	0.02	—
				+25°C	—	68	—
				+25°C	—	nV/ \sqrt{Hz}	—
B ^o M	Maximum Output Swing Bandwidth	See Figure 92	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 1M\Omega$	+25°C	—	5	—
				-40°C	—	7	—
				+85°C	—	4	—
B ₁	Unity Gain Bandwidth	See Figure 94	$V_I = 10mV$, $C_L = 20pF$	+25°C	—	85	—
				-40°C	—	130	—
				+85°C	—	55	—
ϕ_m	Phase Margin	See Figure 94	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$	+25°C	—	34°	—
				-40°C	—	38°	—
				+85°C	—	28°	—

Low bias mode: $V_{DD} = 10V$

Parameter		Conditions	T_A	TLC271I, TLC271AI, TLC271BI			Unit
				Min	Typ	Max	
SR	Slew Rate at Unity Gain	$R_L = 1M\Omega$, $C_L = 20pF$ See Figure 92	$V_{I(PP)} = 1V$	+25°C	—	0.05	—
				-40°C	—	0.06	—
				+85°C	—	0.03	—
				+25°C	—	0.04	—
		See Figure 92	$V_{I(PP)} = 5.5V$	-40°C	—	0.05	—
				+85°C	—	0.03	—
				+25°C	—	68	—
				+25°C	—	nV/ \sqrt{Hz}	—
B ^o M	Maximum Output Swing Bandwidth	See Figure 92	$V_o = V_{oH}$, $C_L = 20pF$, $R_L = 1M\Omega$	+25°C	—	1	—
				-40°C	—	1.4	—
				+85°C	—	0.8	—
B ₁	Unity Gain Bandwidth	See Figure 94	$V_I = 10mV$, $C_L = 20pF$	+25°C	—	110	—
				-40°C	—	155	—
				+85°C	—	80	—
ϕ_m	Phase Margin	See Figure 94	$F = B_1$, $V_I = 10mV$, $C_L = 20pF$	+25°C	—	38°	—
				-40°C	—	42°	—
				+85°C	—	32°	—

Typical Performance Characteristics Table Index of Graphs

			Figure		
			High Bias Mode	Medium Bias Mode	Low Bias Mode
V_{I^o}	Input Offset Voltage	Distribution	1,2	31,32	61,62
$V_{^H}$	High Level Output Voltage	vs. High Level Output Current	3,4	33,34	63,64
		vs. Supply Voltage	5	35	65
		vs. Free Air Temperature	6	36	66
$V_{^L}$	Low Level Output Voltage	vs. Common Mode Input Voltage	7,8	37,38	67,68
		vs. Differential Input Voltage	9	39	69
		vs. Free Air Temperature	10	40	70
		vs. Low Level Output Current	11,12	41,42	71,72
A_{VD}	Large Signal Differential Voltage Gain	vs. Supply Voltage	13	43	73
		vs. Free Air Temperature	14	44	74
I_{IB}	Input Bias Current	vs. Free Air Temperature	15	45	75
	I_{I^o}	vs. Free Air Temperature	15	45	75
V_{IC}	Common Mode Input Voltage	vs. Supply Voltage	16	46	76
I_{DD}	Supply Current	vs. Supply Voltage	17	47	77
		vs. Free Air Temperature	18	48	78
SR	Slew Rate	vs. Supply Voltage	19	49	79
		vs. Free Air Temperature	20	50	80
I_{sel}	Bias Select Current	vs. Supply Voltage	21	51	81
$V_{^o(PP)}$	Maximum Peak to Peak Output Voltage	vs. Frequency	22	52	82
B_1	Unity Gain Bandwidth	vs. Free Air Temperature	23	53	83
		vs. Supply Voltage	24	54	84
A_{VD}	Large Signal Differential Voltage Gain	vs. Frequency	29,30	59,60	89,90
ϕ_m	Phase Margin	vs. Supply Voltage	25	55	85
		vs. Free Air Temperature	26	56	86
		vs. Capacitive Load	27	57	87
V_n	Equivalent Input Noise Voltage	vs. Frequency	28	58	88
ϕ_{shift}	Phase Shift	vs. Frequency	29,30	59,60	89,90

Typical Performance Characteristics High Bias Mode




Figure 1




Figure 2




Figure 3




Figure 4

Typical Performance Characteristics High Bias Mode




Figure 5




Figure 6




Figure 7




Figure 8

Typical Performance Characteristics High Bias Mode




Figure 9




Figure 10




Figure 11




Figure 12

Typical Performance Characteristics High Bias Mode




Figure 13




Figure 14




Figure 15




Figure 16

Typical Performance Characteristics High Bias Mode




Figure 17




Figure 18




Figure 19




Figure 20

Typical Performance Characteristics High Bias Mode




Figure 21




Figure 22




Figure 23




Figure 24

Typical Performance Characteristics High Bias Mode




Figure 25




Figure 26




Figure 27




Figure 28

Typical Performance Characteristics High Bias Mode




Figure 29




Figure 30

Typical Performance Characteristics Medium Bias Mode




Figure 31




Figure 32

Typical Performance Characteristics Medium Bias Mode




Figure 33




Figure 34




Figure 35




Figure 36