



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## TAA-Compliant Protect It! 6-Outlet Surge Protector, 6-ft. Cord, 990 Joules, 2 x USB Charging ports (2.1A), Black Housing

MODEL NUMBER: TLP606USBBTAA



### Highlights

- Compliant with the Federal Trade Agreement Act (TAA) for GSA schedule purchases
- 6 outlet / 6-ft. cord
- 990 joule rating
- 2.1 amp dual port USB charger

### Package Includes

- TLP606USBBTAA surge suppressor
- Instruction manual with warranty information

### Description

Tripp Lite's TLP606USBBTAA offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. USB charging ports offer fast charging for smartphones, tablets, MP3 players and other portable devices.

TLP606USBBTAA offers 6 total outlets, 6 foot cord, 2 USB charging ports and diagnostic LED to warn of suppressor damage. AC suppression rated at 990 joules shields equipment from surges and line noise. Attractive cool grey suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 6 NEMA5-15R/6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/990 joules/400V UL1449 3rd Edition

### Features

- Compliant with the Federal Trade Agreement Act (TAA) for GSA schedule purchases
- 6 outlets
- 6-ft. cord
- 2 USB charging ports - 2.1 amp total
- Surge suppression rating: 990 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED



- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

## Specifications

| OVERVIEW                           |  |
|------------------------------------|--|
| UPC Code                           | 037332183088   |
| OUTPUT                             |  |
| Frequency Compatibility            | 50 / 60 Hz   |
| Output Receptacles                 | (6) 5-15R  |
| Output (Watts)                     | 1875   |
| Circuit Breaker (amps)             | 15   |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker  |
| Transformer Accommodation          | Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 3 transformers total |
| Outlet Orientation                 | Single row of 6 outlets  |
| Right-Angle Outlets                | No   |
| INPUT                              |  |
| Nominal Input Voltage(s) Supported | 120V AC  |
| Recommended Electrical Service     | 120V (110-125V)  |
| Input Connection Type              | NEMA 5-15P   |
| Input Cord Length (ft.)            | 6  |
| Input Cord Length (m)              | 1.83   |
| Input Cord Gauge Type              | 14 gauge, SJT  |
| Voltage Compatibility (VAC)        | 120  |
| Maximum Surge Amps                 | 35500  |
| Right-Angle Plug                   | No   |
| USER INTERFACE, ALERTS & CONTROLS  |  |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch                                  |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status   |
| SURGE / NOISE SUPPRESSION          |  |



|  |  |
|--|--|
| AC Suppression Joule Rating                                | 990  |
| AC Suppression Response Time                               | < 1 ns   |
| Protection Modes   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression   |
| Clamping Voltage (RMS)                                     | 150  |
| UL1449 Let Through Rating                                  | 400V   |
| <b>DATALINE SURGE SUPPRESSION</b>                          |  |
| Telephone/DSL Protection                                   | No   |
| Cable (Coax) Protection                                    | No   |
| Network (Ethernet) Protection                              | No   |
| <b>PHYSICAL</b>  |  |
| Shipping Dimensions (hwd / in.)                            | 1.80 x 14.60 x 4.80  |
| Shipping Dimensions (hwd / cm)                             | 4.57 x 37.08 x 12.19   |
| Shipping Weight (lbs.)                                     | 1.20   |
| Shipping Weight (kg)                                       | 0.54   |
| Material of Construction                                   | Plastic  |
| Integrated Keyhole Mounting Tabs                           | Keyhole mounting tabs enable wall mounting   |
| Housing Color  | Black  |
| Receptacle Color   | Black  |
| Color (AC Line Cord)                                       | Black  |
| Outlets Measurement (Center to Center)                     | 28.5mm   |
| Anti-Microbial Protected                                   | No   |
| <b>CERTIFICATIONS</b>                                      |  |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3rd EDITION   |
| UL1363 (Power Tap)   | UL1363   |
| cUL / CSA (Canada)   | cUL  |
| Approvals  | Exceeds IEEE 587 category A&B specifications   |
| <b>WARRANTY</b>  |  |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 &nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> &nbsp; |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>