

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Eco-Surge 7-Outlet, Surge Protector, 4-ft Cord, 1400 Joules, Timer-Controlled

MODEL NUMBER: TLP74TG











Highlights

- Timer-controlled outlets
- Two separate outlet banks
- 1400 joules
- 7 outlet / 4-ft cord
- Diagnostic LEDs

Package Includes

- TLP74TG ECO-SURGE
 Home/Business Theater Surge
 Suppressor
- Instruction manual with warranty information

Description

Tripp Lite's TLP74TG offers reliable, GREEN surge technology that protects your computer and peripherals as well as the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. Convenient, multiple programmable timers allow users to set the exact time a device is turned on and off. The unit has 2 separate banks of outlets so you can program up to 20 timer options. The TLP74TG has 7 total outlets, 4 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 1400 joules shields equipment from surges and line noise. Designed with an attractive cool gray suppressor housing, the TLP74TG provides 1 designated transformer outlet but can accommodate up to 4 transformer plug outlets offering convenient protection of desktop computer equipment and accessories. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals
- Programmable timer controls the output based on user settings. The timer can be set to automatically
 power connected ON and OFF based on time of day and day of the week for up to 20 possible timer
 settings.
- Two sets of timer-controlled outlet banks allow the user to connect equipment with varying timer settings.
- 1400 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 7 surge-protected NEMA 5-15R AC outlets safeguard and entire home/business theater system while accommodating up to 4 large transformers
- 2 diagnostic LEDs alert user to protection and grounded status



- Lighted on/off switch with integrated circuit breaker protects against dangerous system overload
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

Specifications

OVERVIEW		
UPC Code	037332161352	
ОИТРИТ		
Output Volt Amp Capacity (VA)	15	
Output Watt Capacity (Watts)	1875	
Frequency Compatibility	60 Hz	
Output Receptacles	(7) 5-15R	
Transformer Accommodation	1 Designated transformer outlet but can accommodate up to 4	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMAP - NEMA5-15P	
Input Cord Length (ft.)	4	
Input Cord Length (m)	1.22	
Input Cord Gauge Type	14 AWG 3C SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	19500	
Right-Angle Plug	No	
USER INTERFACE, ALERTS & CONTROLS		
Front Panel LCD Display	AM/PM LCD Clock	
Switches	Combination AC circuit breaker and 2 position lighted on/off power switch	
LED Indicators	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1400	
AC Suppression Response Time	< 1 ns	



Shipping Dimensions (hwd / cm) 34.80 x shipping Weight (lbs.) Shipping Weight (lbs.) Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 1.56 x 3 Unit Dimensions (hwd / cm) 3.96 x 8 Unit Weight (lbs.) 1.43 Unit Weight (kg) 0.65 Material of Construction Color (AC Line Cord) Outlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES	x 2.200 x 5.700 5.59 x 14.48 3.54 x 11.22 3.99 x 28.50	
DATALINE SURGE SUPPRESSION Telephone/DSL Protection Cable (Coax) Protection No No No No No No No No No	x 2.200 x 5.700 5.59 x 14.48	
PATALINE SURGE SUPPRESSION Telephone/DSL Protection No Dable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) Juit Dimensions (hwd / cm) Juit Weight (lbs.) Juit Weight (lbs.) Juit Weight (kg) Juit	x 2.200 x 5.700 5.59 x 14.48	
Telephone/DSL Protection Cable (Coax) Protection No Network (Ethernet) Protection 13.700 x 34.80 x s 34.80 x s 34.80 x s 34.80 x s 35.81 No Network (Ethernet) Protection No Network (Ethernet) Protection No Network (Ethernet) Protected No Network (Ethernet) No Network (Et	5.59 x 14.48 3.54 x 11.22	
Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) Juit Dimensions (hwd / cm) Juit Weight (lbs.) Juit Weight (kg) Material of Construction Color (AC Line Cord) Outlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES	5.59 x 14.48 3.54 x 11.22	
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) Juit Dimensions (hwd / in.) Juit Weight (lbs.) Juit Weight (lbs.) Juit Weight (lbs.) Juit Weight (kg)	5.59 x 14.48 3.54 x 11.22	
Chipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) Juit Dimensions (hwd / cm) Juit Weight (lbs.) Juit Weight (lbs.) Juit Weight (kg)	5.59 x 14.48 3.54 x 11.22	
Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) O.68 Unit Dimensions (hwd / in.) Juit Dimensions (hwd / cm) Juit Weight (lbs.) Juit Weight (kg) O.65 Material of Construction Color (AC Line Cord) Dutlets Measurement (Center to Center) Anti-Microbial Protected DEPECIAL FEATURES	5.59 x 14.48 3.54 x 11.22	
Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (lbs.) Shipping Weight (kg) O.68 Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) Juit Weight (lbs.) Juit Weight (kg) O.65 Material of Construction Color (AC Line Cord) Outlets Measurement (Center to Center) Anti-Microbial Protected SPECIAL FEATURES	5.59 x 14.48 3.54 x 11.22	
Shipping Weight (lbs.) Shipping Weight (kg) O.68 Unit Dimensions (hwd / in.) Juit Dimensions (hwd / cm) Juit Weight (lbs.) Juit Weight (kg) O.65 Material of Construction Color (AC Line Cord) Outlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES	3.54 x 11.22	
Shipping Weight (kg) Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) Unit Weight (lbs.) Unit Weight (kg) Uni		
Unit Dimensions (hwd / in.) Jnit Dimensions (hwd / cm) Jnit Weight (lbs.) Jnit Weight (kg) Material of Construction Color (AC Line Cord) Dutlets Measurement (Center to Center) Anti-Microbial Protected Distance SPECIAL FEATURES		
Unit Dimensions (hwd / cm) 3.96 x 8. Unit Weight (lbs.) 1.43 Unit Weight (kg) 0.65 Material of Construction Color (AC Line Cord) Outlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES		
Unit Weight (lbs.) Juit Weight (kg) Juit Weight (lbs.) Juit Weight (kg) Juit Weight (k	3.99 x 28.50	
Unit Weight (kg) Material of Construction Color (AC Line Cord) Outlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES		
Material of Construction plastic Color (AC Line Cord) gray Cutlets Measurement (Center to Center) Distance Anti-Microbial Protected No SPECIAL FEATURES		
Color (AC Line Cord) Gray Dutlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES		
Outlets Measurement (Center to Center) Anti-Microbial Protected No SPECIAL FEATURES		
Anti-Microbial Protected No SPECIAL FEATURES		
SPECIAL FEATURES	e between standard outlets = 28.5mm; Distance between standard outlet and transformer outlet = 57mm	
Green Energy-Saving Features Schedul		
	lable daily hours of economy mode operation	
CERTIFICATIONS		
JL1449 3rd Edition (AC Suppression) UL1449	3rd Edition	
JL1363 (Power Tap) UL1363		
JL497A (Communications) UL497A	\	
FCC Part 68 (Communications) FCC Part	art 68	
cUL / CSA (Canada) cUL		
Approvals Exceeds	s IEEE 587 category A&B specifications	
WARRANTY		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$75,000 Ultimate Lifetime Insurance

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies