# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## Eco-Surge 7-Outlet Surge Protector, 6-ft. Cord, 1080 Joules, Individually-Controlled

#### MODEL NUMBER: TLP76MSG











#### Description

Tripp Lite's TLP76MSG offers reliable, GREEN surge technology that protects your computer and peripherals as well as the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. The TLP76MSG has one always on outlet for those peripherals that need constant power like a fax machine, DVR or router. It also offer convenient, individual outlet switches that allow users to select which device is turned on and off. The TLP76MSG has 7 total outlets, 6 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 1080 joules shields equipment from surges and line noise. Designed with an attractive cool gray suppressor housing, the TLP76MSG can accommodate up to 4 transformer plug outlets offering convenient protection of desktop computer equipment and accessories. \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

#### Features

- Energy-saving green outlets allow individual outlet control using illuminated power switches for cutting power to peripherals not in use.
- Six green outlets have their own illuminated ON/OFF switch for cutting power to peripherals when they
  are not in use. One "Always On" outlet provides continuous power for devices such as DVRs (TiVo),
  cable and satellite boxes, modems, routers and fax machines.
- In addition to the individual illuminated outlet switches, an illuminated Master Switch controls power to all outlets (except the Always On outlet) at once. It can override other "ON" settings to cut power to all switched outlets at once.
- Protected (Green) LED assures protection is present & Always On (Red) LED indicates that the Always On outlet is receiving power.
- 1080 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans).

#### Highlights

- Individual outlet control
- 1080 joules
- 7 outlet / 6-ft cord
- Diagnostic LEDs

#### **Package Includes**

- TLP76MSG ECO-SURGE Home/Business Theater Surge Suppressor
- Instruction manual with warranty information



• Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

### **Specifications**

| OVERVIEW                           |   |  |
|------------------------------------|---|--|
| UPC Code                           | 037332166074  |  |
| Ουτρυτ                             |   |  |
| Output Volt Amp Capacity (VA)      | 120   |  |
| Output Watt Capacity (Watts)       | 1800  |  |
| Frequency Compatibility            | 60 Hz   |  |
| Output Receptacles                 | (7) 5-15R   |  |
| Transformer Accommodation          | Supports 1 large transformer without covering remaining outlets, accepts up to 4 transformers total |  |
| Right-Angle Outlets                | No  |  |
| INPUT                              |   |  |
| Nominal Input Voltage(s) Supported | 120V AC   |  |
| Recommended Electrical Service     | 120V (110-125V)   |  |
| Input Connection Type              | NEMAP - NEMA5-15P   |  |
| Input Cord Length (ft.)            | 6   |  |
| Input Cord Length (m)              | 1.83  |  |
| Input Cord Gauge Type              | 14 AWG, 3 COND, SJT   |  |
| Voltage Compatibility (VAC)        | 120   |  |
| Maximum Surge Amps                 | 72000   |  |
| Right-Angle Plug                   | No  |  |
| USER INTERFACE, ALERTS & CONTROLS  |   |  |
| Switches                           | 1 x Lighted Master Switch & 6 x Lighted Receptacle Switches   |  |
| LED Indicators                     | Protected (Green)" & Always On Receptacle (Red)   |  |
| SURGE / NOISE SUPPRESSION          |   |  |
| AC Suppression Joule Rating        | 1080  |  |
| AC Suppression Response Time       | < 1 ns  |  |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression.                 |  |
| Clamping Voltage (RMS)             | 150   |  |



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

| UL1449 Let Through Rating                                     | 400v  |
|---|---|
| EMI / RFI Filtering   | Up to 40dB  |
|   |   |
| DATALINE SURGE SUPPRESSION                                    |   |
| Telephone/DSL Protection                                      | No  |
| Cable (Coax) Protection                                       | No  |
| Network (Ethernet) Protection                                 | No  |
| PHYSICAL  |   |
| Shipping Dimensions (hwd / in.)                               | 2.00 x 4.20 x 17.00   |
| Shipping Dimensions (hwd / cm)                                | 5.08 x 10.67 x 43.18  |
| Shipping Weight (lbs.)  | 1.80  |
| Shipping Weight (kg)  | 0.82  |
| Unit Dimensions (hwd / in.)                                   | 1.40 x 3.40 x 15  |
| Unit Dimensions (hwd / cm)                                    | 3.56 x 8.64 x 38.1  |
| Unit Weight (lbs.)  | 1.54  |
| Unit Weight (kg)  | 0.70  |
| Material of Construction                                      | Plastic   |
| Integrated Keyhole Mounting Tabs                              | Keyhole mounting slots enable wall mounting   |
| Color (AC Line Cord)  | Cool Gray   |
| Anti-Microbial Protected                                      | No  |
| CERTIFICATIONS  |   |
| UL1449 3rd Edition (AC<br>Suppression)                        | UL1449 3rd Edition  |
| UL1363 (Power Tap)  | UL1363  |
| cUL / CSA (Canada)  | cUL   |
| Approvals   | Exceeds IEEE 587 category A&B specifications  |
| WARRANTY  |   |
| Product Warranty Period<br>(Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$25,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies