

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







building a smarter, unified business foundation

WORLDWIDE

[CHANGE] ENGLISH


REGISTER / LOG IN

FOLLOW US



SOLUTIONS

PRODUCTS AND SERVICES SUPPORT ABOUT US







TM2A-C39 Add to BOM | Add to Favorites

Cable Tie Mounts — User Supplied Adhesives

Product Details Related Documents

Std. Pallet Volume (cf) 58.480000 Std. Cin. Volume (cf) 0.1624 Std. Cin. Weight (b) 0.9000 Std. Pkg. Oly. 100 Rolf-Scompliancy Status Compliant Part Description Cable Tie Mounts – User Supplied Adhesives Product Type Cable Tie Mounts – User Supplied Adhesive Material Heat Stabilized Nylon 6.6 Color Natural UL Recognized E138677 Length (mm) 16.0 Length (mm) 7.0 Width (mm) 10.8 Width (mm) 0.43 Height (n) 0.28 CE Complant CT-ACC2 / 10.96 Ferring Description Cable Tie Mount , User App Adh., .43" (10.9mm)W Type Tie Mount , User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount		
Sid. Cin. Volume (d) 0.1624 Sid. Cin. Weight (b) 0.9000 Sid. Pkg. City. 100 RoHS Compliancy Status Compliant Part Description Cable Tie Mounts – User Supplied Adhesives Product Type Cable Tie Mounts – User Supplied Adhesive Material Heat Stabilized Nylon 6.6 Color Natural UL Recognized E136577 Length (mm) 16.0 Length (mm) 7.0 Width (mm) 10.8 Width (mm) 10.8 Width (in) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Priding Description Cable Tie Mount, User App Adh., 43* (10.9mm)W Type Tie Mount - User Supplied Adhesive User With Cable Ties M. I. S Environment Indoor Style Tie Mount	Std. Pallet Weight (lb)	324.0000
Std. Chr. Weight (Ib)	Std. Pallet Volume (cf)	58.480000
Side Pig Qiy. RoHS Compliancy Status Compliant Part Description Cable Tie Mounts — User Supplied Adhesives Product Type Cable Tie Mounts - User Supplied Adhesive Material Heat Stabilized Nylon 6.6 Color Natural UL Recognized E136577 Length (mm) 16.0 Length (in.) 0.63 Height (mm) 7.0 Width (mm) 10.8 Width (in.) 0.43 Height (in.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used Width Cable Ties M, I, S Environment Indoor Style Tie Mount Indoor	Std. Ctn. Volume (cf)	0.1624
Rehts Compliancy Status Compliant	Std. Ctn. Weight (lb)	0.9000
Part Description Cable Tie Mounts — User Supplied Adhesives Product Type Cable Tie Mounts - User Supplied Adhesive Material Heat Stabilized Nylon 6.6 Color Natural UL Recognized E136577 Length (mm) 16.0 Length (mm) 0.63 Height (mm) 7.0 Width (mm) 10.8 Width (mm) 0.43 Height (In.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43* (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Std. Pkg. Qty.	100
Product Type	RoHS Compliancy Status	Compliant
Heat Stabilized Nylon 6.6	Part Description	Cable Tie Mounts — User Supplied Adhesives
Color Natural UL Recognized E136577 Length (mm) 16.0 Length (ln.) 0.63 Height (mm) 7.0 Width (mm) 10.8 Width (ln.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Product Type	Cable Tie Mounts - User Supplied Adhesive
Length (mm) 16.0	Material	Heat Stabilized Nylon 6.6
Length (mm) 16.0 Length (in.) 0.63 Height (mm) 7.0 Width (mm) 10.8 Width (in.) 0.43 Height (in.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., 43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Color	Natural
Length (In.) 0.63 Height (mm) 7.0 Width (mm) 10.8 Width (In.) 0.43 Height (In.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	UL Recognized	E136577
Height (mm) 7.0	Length (mm)	16.0
Width (nm) 10.8 Width (ln.) 0.43 Height (ln.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Length (In.)	0.63
Width (In.) 0.43 Height (In.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Height (mm)	7.0
Height (In.) 0.28 CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Width (mm)	10.8
CE Compliant CT-ACC2 / 10.96 Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Width (In.)	0.43
Flammability Rating V-2 Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Height (In.)	0.28
Pricing Description Cable Tie Mount, User App Adh., .43" (10.9mm)W Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	CE Compliant	CT-ACC2 / 10.96
Type Tie Mount - User Supplied Adhesive Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Flammability Rating	V-2
Mounting Method User Supplied Adhesive Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Pricing Description	Cable Tie Mount, User App Adh., .43" (10.9mm)W
Used With Cable Ties M, I, S Environment Indoor Style Tie Mount	Туре	Tie Mount - User Supplied Adhesive
Environment Indoor Style Tie Mount	Mounting Method	User Supplied Adhesive
Style Tie Mount	Used With Cable Ties	M, I, S
TIO MOUNT	Environment	Indoor
Min. Order Qty. 100.0000	Style	Tie Mount
	Min. Order Qty.	100.0000