

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







AMPROBE°

Data Sheet



No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

TMA-20HW Hot Wire Anemometer

The Hot Wire anemometer technology eliminates the use of bearings and rotating parts. Because of this fact the meter is durable and provides good and stable accuracy of the measurements. It is used for indoor air quality and HVAC / R technicians measuring Heat / Ventilation, / Air conditioning / Refrigeration, wind flow and temperature in residential, commercial and industrial air conditioning systems.

- Highly accurate thermometer with 0.1% basic accuracy for precise measurements
- Fast response telescopic probe for use in hard to reach places
- Air Flow Volume (CFM, CMM)
- Instant, Avg, 2/3 Vmax Flow Measurements
- Velocity m / s, f t / min, knots, km / hr, mph
- Data hold & Maximum / Minimum with Time stamp
- Data Memory and Real function (99 sets)
- Large backlit LCD display with 5 parameters
- Auto Power ON / OFF setting
- Simple and safe to use





TMA-20HW Hot Wire Anemometer

Data Sheet

General Specifications

Display	Triple display, 4 digit LCD reading.	
Sampling Rate	Once per second	
Response Time	< 2 seconds	
Manual Memory Capacity	5 X 99 sets. (Direct reading from LCD display)	
Operating Conditions	0°C ~ 40°C (32°F ~ 104°F) 10 ~ 80% R.H.	
Power Source	6 X AAA Battery	
Battery Life	Approx. 10 hours	
Dimensions	360.7 X 216 X63.5mm (L14.2 X W8.5 X H2.5 in) with case	
Weight	1043g (2.3 Lbs) with case	
Probe Dimensions / Weight	Wire length: 2.2 meter (7.2 ft) Probe length: 1.2 meter (3.9 ft) Probe diameter of tip: 9.0 mm (0.35 in.) Probe diameter of base: 28.0 mm (1.1 in.) Probe weight: 165 g (0.36 lbs)	

Electrical Specification

Feature	Range	Accuracy
Air Flow	0.1 to 30.0 m/s	±3% of reading
	0.2 to 110 km/hr	±1%FS
	10 to 6000 ft/min	
	0.1 to 59 knots	
	0.12 to 68 MPH	
Air Flow Volume	0 to 999900 CFM	±(1.2% rdg + 5 dgts) up to
	0 to 999900 CMM	400V Hz**
Temperature	-20°C to +60°C	±0.5°C, ±0.9°F
	4°F to +140°F	·
Humidity	0 to 100%RH	±3%RH
Included Accessories	Batteries, Hard Carrying case	

Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com

Everett, WA 98203 Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0



©2010 Amprobe Test Tools. All rights reserved. 6/2010 TMA-20HW Rev A