

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# **AMPROBE**°

**Data Sheet** 



The Hot Wire anemometer technology eliminates the use of bearings and rotating parts. Because of this fact the meter is durable and provides good and stable accuracy of the measurements. It is used for indoor air quality and HVAC / R technicians measuring Heat / Ventilation, / Air conditioning / Refrigeration, wind flow and temperature in residential, commercial and industrial air conditioning systems.

- Highly accurate thermometer with 0.1% basic accuracy for precise measurements
- Fast response telescopic probe for use in hard to reach places
- Air Flow Volume (CFM, CMM)
- Instant, Avg, 2/3 Vmax Flow Measurements
- Velocity m / s, f t / min, knots, km / hr, mph
- Relative Humidity and Temperature Measurement
- Data hold & Maximum / Minimum with Time stamp
- Data Memory and Real function (99 sets)
- 512KB auto data-logging capacity
- Large backlit LCD display with 5 parameters
- Auto Power ON / OFF setting
- USB interface
- Simple and safe to use



## No hassle warranty

No waiting.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



#### **TMA-21HW Hot Wire Anemometer**

**Data Sheet** 

**General Specifications** 

Display	Triple display, 4 digit LCD reading.	
Sampling Rate	once per second	
Response Time	< 2 seconds	
Manual Memory Capacity	5 X 99 sets. (Direct reading from LCD display)	
Operating Conditions	0°C ~ 40°C (32°F ~ 104°F) 10 ~ 80% R.H.	
Power Source	6 X AAA Battery	
Battery Life	Approx. 10 hours	
Dimensions	360.7 X 216 X63.5mm ( L14.2 X W8.5 X H2.5 in) with case	
Weight	1043g ( 2.3 Lbs) with case	
Probe Dimensions / Weight		
_	Wire length : 2.2 meter (7.2 ft)	
	Probe length : 1.2 meter (3.9 ft)	
	Probe diameter of tip: 15.0 mm (0.59 in.)	
	Probe diameter of base: 28.0 mm (1.1 in.)	
	Probe weight: 165 g (0.36 lbs)	

**Electrical Specification** 

±3% of reading
±3/0 01 reduing
±1%FS
±(1.2% rdg + 5 dgts) up to
400V Hz**
±0.5°C, ±0.9°F
±3%RH
g case, USB Cable, and CD Software

#### **Amprobe® Test Tools**

website: www.Amprobe.com email: info@amprobe.com

Everett, WA 98203 Tel: 877-AMPROBE

#### **Amprobe® Test Tools Europe**

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0



©2010 Amprobe Test Tools. All rights reserved. 6/2010 TMA-21HW\_DS Rev A