

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## **AMPROBE**°

**Data Sheet** 



## No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

# **TMD-10 Dual Temperature Meter**

The Amprobe TMD-10 is a completely portable dual input thermometer. With a digital dual display that displays T1, T2 and T1-T2. Choose between Celsius or Fahrenheit degrees measurement results. The TMD-10 will store and later display your minimum and maximum values. Will measure temperature with either Type K or Type J thermocouples. Ships as a complete kit with carrying case, two Type K probes, battery and manual.

- Compatible with K and J type thermocouples
- Dual temperature for easy Super-Heat and Sub-Cool calculations
- Selectable °F or °C
- Min/Max recording
- Delta reading (T1 T2)
- Data Hold function to retain reading on the screen for later viewing
- **■** Low battery indication
- Auto-Power off
- Offset Mode to compensate for error in the thermocouple
- Includes carrying case, battery, and two K-type probes, Users Manual





#### **TMD-10 Dual Temperature Meter**

#### **Data Sheet**

#### **Specifications**

•	
General Specifications	
Display	Dual 5-digit LCD displays
Overrange indication	"OL" stands for positive temperature
	"-OL" stands for negative temperature
Zero	Automatic
Low battery indication	The "== "sign will appear while battery is low
Power Supply	9V NEDA 1604, IEC 6F22, JIS 006P battery.
Battery life	approx. 200 hours
Auto power off	approx. 15 minutes
Measurement rate	0.5 sec
Operating environment	0°C to 50°C (32°F to 122°F); < 80% RH
Storage temperature	0°C to 50°C (32°F to 122°F); < 80% RH
Sensor	Type K and J thermocouples
Altitude	2000m, indoor operation
Dimensions	130 x 56 x 38 mm (5.1 x 2.2 x 1.5 in.)
Weight	170g (0.37 lb.) battery included
Electrical (23°C ± 5°C, < 80% F	
Temperature scale	°C or °F
Thermocouple type	K-type: -200°C to 1370°C (-328°F to 2498°F) J-type: -200°C to 1050°C (-328°F to 1922°F)
Resolution	0.1 degree C or F
Accuracy	± (0.05% rdg + 0.7°C), ± (0.05% rdg + 1.4°F)
Input protection	24V DC or AC
Temperature Coefficient	$\pm$ (0.01% rdg + 0.03°C per °C); $\pm$ (0.01% rdg + 0.06°F per °F) outside the specified + 18°C to + 28°C (+ 64°F to + 82°F) range
Calibration	Yearly
Agency Approvals & Certifica	tions
C E-EMC	EN61326-1

#### **Amprobe® Test Tools**

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

#### **Amprobe® Test Tools Europe**

Amprobe Test Tools Europe Beha-Amprobe GmbH In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2008 Amprobe Test Tools. All rights reserved. 10/2008 3360423 Rev A