

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



#### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## **AMPROBE**®

**Data Sheet** 



### No hassle warranty

No waiting.





Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

#### **TMD-56**

# Multilogger Thermometer with USB Download

Amprobe TMD-56 thermometer with USB download capability is a professional choice for HVAC/R technicians, electricians, research, industrial process, and quality control. This model comes with a dual inputs that allows easy access to easy super-heat and sub-cool temperature measurement as well as cut-out and in temperature measurements.

- Backlit triple-display
- **■** Built in memory
  - 16 sets, Maximum 16000 data points
- Data-logging:
  - 256 samples with real-time data per channel
- Easy Data Recall with up and down key: T1, T2, T1-T2, Time and Memory Location
- Thermocouple Offset Adjustment
- REC, MAX, MIN, MAX-MIN, Average, Relative Zero and HOLD functions
- Resolution 0.1°C/1°C, 0.1°F/1°F
- Warning beeper with Hi/Lo setting
- User selectable recording interval
- Real time clock with calendar





#### **TMD-56 Multilogger Thermometer with USB Download**

**Data Sheet** 

#### **General Specifications**

Display	4½ digit liquid crystal display (LCD) with a maximum reading of 19999.
Polarity	Automatic, positive implied, negative polarity indication.
Low Battery Indication	The "==" is displayed when the battery voltage drops below the operating level.
Auto Power Off	30 minutes
Measurement Rate	2.5 times / second.
Operating Environment	0°C to 50°C (32°F to 122°F) <80% R.H.
Storage Environment	-20°C to 60°C (-4°F to 140°F) <70% R.H. with battery removed from meter.
Accuracy	Stated accuracy at 23°C ±5°C, <75% R.H.
Power	1.5V x 4pcs AAA size
Battery Life	120 hours
Dimensions	L241.3 X W157.98 XH76.2mm (9.5 X 6.22 X3 in
Weight	Approx. 365g (0.8lb) including batteries.



#### **TMD-56 Multilogger Thermometer with USB Download**

**Data Sheet** 

#### **Electrical Specifications**

=:eeti::ea: ppeti::eat		
Temperature Scale	User selectable Celcius or Fahrenheit	
Measurement Range	Thermocouple Type Range	
	K-TYPE (0.1°): -200°C to 1372°C (-328°F to 2501°F)	
	J-TYPE (0.1°): -210°C to 1200°C (-346°F to 2192°F)	
	T-TYPE (0.1°): -200°C to 400°C (-328°F to 752°F)	
	E-TYPE (0.1°): -210°C to 1000°C (-346°F to 1832°F)	
	R-TYPE (1°): 0°C to 1767°C (32°F to 3212°F)	
	S-TYPE (1°): 0°C to 1767°C ( 32°F to 3212°F)	
	N-TYPE (0.1°): -50°C to 1300°C (-58°F to 2372°F)	
Accuracy	K/J/T/E-TYPE	
	±(0.05% rdg + 0.3°C) -50°C to 1372°C	
	±(0.05% rdg + 0.7°C) -50°C to -210°C	
	±(0.05% rdg + 0.6°F) -58°F to 2501°F	
	±(0.05% rdg + 1.4°F) -58°F to -346°F	
	N-TYPE	
	±(0.05% rdg + 0.8°C) -50°C to 0°C	
	±(0.05% rdg + 0.4°C) 0°C to 1300°C	
	±(0.05% rdg + 1.6°F) -58°F to 32°F	
	±(0.05% rdg + 0.8°F) 32°F to 2372°F	
	R/S-TYPE	
	±(0.05% rdg + 2°C) 0°C to 1767°C	
	±(0.05% rdg + 4°F) 32°F to 3212°F	
Included accessories	Users manual, Battery (4), USB cable, Software CD, K type thermocouple (2)	



#### **TMD-56 Multilogger Thermometer with USB Download**

**Data Sheet** 



#### **Amprobe® Test Tools**

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

#### **Amprobe® Test Tools Europe**

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2010 Amprobe Test Tools. All rights reserved. 6/2010 TMD-56\_DS Rev A