



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



High Voltage PNP Epitaxial Planar Transistor

SOT-223



Pin Definition:

1. Base
2. Collector
3. Emitter

Features

- Low Saturation Voltages
- High Breakdown Voltage

Structure

- Epitaxial Planar Type
- PNP Silicon Transistor

PRODUCT SUMMARY

BV_{CBO}	-560V
BV_{CEO}	-560V
I_C	-150mA
V_{CE(SAT)}	-0.5V @ I _C =-50mA, I _B =-10mA

Ordering Information

Part No.	Package	Packing
TSA1765CW RPG	SOT-223	2.5Kpcs / 13" Reel

Note: "G" denotes for Halogen Free

Absolute Maximum Rating (Ta = 25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Collector-Base Voltage	V _{CBO}	-560	V
Collector-Emitter Voltage	V _{CEO}	-560	V
Emitter-Base Voltage	V _{EBO}	-7	V
Collector Current	I _C	-150	mA
Collector Current(Pulse)	I _{CP}	-500	
Base Current	I _B	-50	
Total Power Dissipation @ T _C =25°C	P _{tot}	2	W
Operating Junction Temperature	T _J	+150	°C
Operating Junction and Storage Temperature Range	T _{STG}	- 55 to +150	°C

Electrical Specifications (Ta = 25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Collector-Base Breakdown Voltage	I _C = -1mA, I _E = 0	BV _{CBO}	-560	--	--	V
Collector-Emitter Breakdown Voltage	I _C = -1mA, I _B = 0	BV _{CEO}	-560	--	--	V
Emitter-Base Breakdown Voltage	I _E = -10uA, I _C = 0	BV _{EBO}	-7	--	--	V
Collector Cutoff Current	V _{CB} = -560V, I _E = 0	I _{CBO}	--	--	-100	nA
Emitter Cutoff Current	V _{EB} = -7V, I _C = 0	I _{EBO}	--	--	-100	nA
Collector-Emitter Saturation Voltage	I _C = -20mA, I _B = -2mA	V _{CE(SAT)} 1	--	--	-0.2	V
	I _C = -50mA, I _B = -10mA	V _{CE(SAT)} 2	--	--	-0.5	
Base-Emitter Saturation Voltage	I _C = -50mA, I _B = -10mA	V _{BE(SAT)} 1	--	--	-1.0	V
Base-Emitter on Voltage	V _{CE} = -10V, I _C = -50mA	V _{BE(ON)}	--	--	-1.0	V
DC Current Transfer Ratio	V _{CE} = -10V, I _C = -1mA	h _{FE} 1	150	--	--	
	V _{CE} = -10V, I _C = -50mA	h _{FE} 2	80	--	300	
	V _{CE} = -10V, I _C = -100mA	h _{FE} 3	--	15	--	
Transition Frequency	V _{CE} = -20V, I _E =-10mA	f _T	50	--	--	MHz
Output Capacitance	V _{CB} = -20V, f=1MHz	Cob	--	--	8	pF

Electrical Characteristics Curve ($T_a = 25^\circ\text{C}$, unless otherwise noted)

Figure 1. Static Characteristics




Figure 2. DC Current Gain




Figure 3. VCE(SAT) v.s. VBE(SAT)




Figure 4. Power Derating






Figure 5. Safety Operation Area




SOT-223 Mechanical Drawing



Unit: Millimeters

Marking Diagram



Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr

S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec

L = Lot Code

TSA1765

High Voltage PNP Epitaxial Planar Transistor

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.