



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




REV. Status

PRELIMINARY
05/30/01 YS



PRELIMINARY 1
CHANGED A.2
AND A.4.
10/02/01 YS

ADSL TRANSFORMER FOR USE WITH CENTILLIUM CT-L53SC08 ANNEX A AND CT-L76SC08 ANNEX C IC CHIP SET



- A. Electrical Specifications (@ 25°C);
1. Primary Open circuit Inductance; $850\mu\text{H} \pm 10\%$ @ 10KHz, 0.1Vrms Measured (1-4) with 2 and 3 shorted
 2. Leakage Inductance; $5\mu\text{H} \text{ MAX}$ @ 100KHz, 0.1Vrms Measured (1-4) with 2 and 3, 8 and 6, 7 and 5 shorted
 3. Turns Ratio; (1-4):(8-5)=1:1 $\pm 2\%$
 4. DC Resistance; $1.1\Omega \text{ MAX}$ measured (1-3)
 $1.1\Omega \text{ MAX}$ measured (2-4)
 $1.0\Omega \text{ MAX}$ measured (8-6)
 $1.25\Omega \text{ MAX}$ measured (7-5)
 5. Dielectric Strength; 1875Vrms 1 second @ Pri to Sec
- B. Marking; TTC-4087, TAMURA, date code and country of origin
- C. Safety; Complies with UL1950 3rd Edition and EN60950
- D. Schematic and Mounting Footprint;



MODEL NUMBER
TTC-4087



- D. Mechanical Specifications;
Dimensions without tolerances are for reference only.



PREPARED BY:

D. Rund

ENGINEER:

Y. Sekiguchi

QUALITY CONTROL:

D. Kelley

APPROVED:

J. Coleman

DWG CONTROL NO.
P-A1-12821
ACAD\TTC\A1128211.DWG

REV
PR1

ADSL
TRANSFORMER

TAMURA CORPORATION OF AMERICA
43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

TTC-4087

MODEL SPECIFICATION

DIM: mm(In) SCL: 2/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.