

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







TELECOMMUNICATION SMD MODEM TRANSFORMER COMPATIBLE WITH V.90 TECHNOLOGIES REV. Status A. Electrical Specifications (@ 25°C) NUMBER REVISION 07/26/01 MP 1. Primary Impedance; 600Ω REVISION A UL# E208555 2. Secondary Impedance; 525Ω CHANGED PAD LAYOUT 3. Insertion Loss: 1.60dB MAX @ 1KHz, 0dBm & DIMENSION 4. Frequency Response; ±0.25dB @ 200Hz to 4KHz, 0dBm ON E. 12/14/01 MP 5. Longitudianl Balance; White dot 60dB MIN @ 200Hz to 4KHz, 0dBm indicates 6. Return Loss; 20dB MIN @ 200Hz to 4KHz, 0dBm pin 1 7. DC Resistance; 6 $(4-1):63 \Omega \pm 15\%$ $(10-7):82 \Omega \pm 15\%$ Country of origin 8. Turns Ratio; $(4-1):(10-7)=1:1.00 \pm 2\%$ 9. Total Harmonic Distortion; Date -80dB MAX @ 600Hz, -10dBm (-86dB TYP) Code 10. Dielectric Strength; 1875Vrms 1 second @ Pri-Sec B. Marking; TTC-5005, TAMURA, date code and country of origin C. Safety; UL1950 3rd Edition, UL60950 19.60±0.25[0.772±0. D. Schematic: 2.50±0.25[0.098±0.010] **SEC** <u>PRI</u> $1.30\pm0.$ **0**Γ0.05 1±0.004] 600 Ω 2.54 ± 0.25 $\boxed{0.100\pm0.010}$ Suggested Pad Layout E. Mechanical Specifications 13.50[0.532]MAX 14.00[0.550]TYP 40[0.4 XAM[O 18.50[0.728]MAX 2.54[0.100]TYP 8 PLACES PREPARED BY: D. Rund DWG CONTROL NO. REV **ENGINEER:** TELECOMMUNICATION V.90 P-A1-12559 TTC-5005 MODEM TRANSFORMER M. Pitchai ACAD\TTC\A1125591.DWG CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624 QUALITY CONTROL: MODEL SPECIFICATION 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624 (909) 699-1270 FAX 9096769482 DIM: mm(In) SCL: 2/1 D. Kelley SH: 1 0F APPROVED: PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING. J. Coleman