



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



TEWA TEMPERATURE SENSORS

HIGH PRECISION NTC THERMISTORS AND TEMPERATURE SENSORS

Specification of Epoxy Coated NTC Thermistor

PART NUMBER: **TTS-3KC3-BZ**

No. of pages: 2


Date: **24.09.2015**

Revision: **00**

FEATURES:

Sensing Element	Epoxy Coated NTC Thermistor
No-load resistance at 25°C	3000 Ω
Tolerances from 0°C to 70°C	± 0.2°C
Beta(25/85) Constant	3977K ± 1%
Operating temperature range	-40°C ÷ 125°C
Response Time in well stirred liquid bath	~1 sec.
Response Time in still air	~10 sec.
Typical Dissipation Constant in still air	0.75mW/°C
RoHS Compatible	YES

DRAWING:



TEWA TEMPERATURE SENSORS

HIGH PRECISION NTC THERMISTORS AND TEMPERATURE SENSORS

PART NUMBER: **TTS-3KC3-BZ**

R/T CHARACTERISTIC:

Resistance 3 000 Ohms at 25°C				
Tolerance 0.2°C From 0°C to 70°C				
B(25/85) 3977 ± 1%				
Material no. 3				
Temp (°C)	R/R(25C) (Ohms)		Temp (°C)	R Value (Ohms)
-40	33,566800		-40	100700,4
-35	24,219300		-35	72657,9
-30	17,668200		-30	53004,6
-25	13,024200		-25	39072,6
-20	9,697300		-20	29091,9
-15	7,289400		-15	21868,2
-10	5,529700		-10	16589,1
-5	4,231400		-5	12694,2
0	3,265100		0	9795,3
5	2,539500		5	7618,5
10	1,990300		10	5970,9
15	1,571400		15	4714,2
20	1,249400		20	3748,2
25	1,000000		25	3000
30	0,805600		30	2416,8
35	0,653010		35	1959,03
40	0,532490		40	1597,47
45	0,436690		45	1310,07
50	0,360100		50	1080,3
55	0,298510		55	895,53
60	0,248710		60	746,13
65	0,208230		65	624,69
70	0,175160		70	525,48
75	0,148010		75	444,03
80	0,125620		80	376,86
85	0,107060		85	321,18
90	0,091610		90	274,83
95	0,078698		95	236,09
100	0,067863		100	203,59
105	0,058730		105	176,19
110	0,051006		110	153,02
115	0,044448		115	133,34
120	0,038859		120	116,58
125	0,034082		125	102,25
130	0,029982		130	89,95
135	0,026454		135	79,36
140	0,023408		140	70,22
145	0,020770		145	62,31
150	0,018478		150	55,43