



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



LCD Flat Panel Controller with Built-in NTSC/PAL/SECAM Decoder and Analog T-CON

TW8807

Introduction



Applications

- LCD TVs for home and mobile use
- Rear seat entertainment
- Portable DVD, PMP and HMD (Head Mount Display)

Features

The TW8807 is a low cost high quality TFT panel controller with embedded NTSC/PAL/SECAM TV decoder. It incorporates all the features required to create multi-purpose LCD TV systems in a single package. It contains all the circuits required to adapt standard NTSC/PAL/SECAM analog TV input signals for display on various TFT LCD panel types. An integrated timing controller and three DACs allows direct interface with analog LCD panels. Its versatile 5 analog inputs allow CVBS, S-video signal to be connected simultaneously.

Other features include: high quality adaptive 4H Comb Filter, downscaling to QVGA output resolution, 2D de-interlacer and panoramic scaler, and multi-window programmable OSD. It also includes image enhancement functions, such as black and white stretch, 2D peaking, CTI, and favorite color enhancement to further improve picture quality. To support analog panel, it also includes cost saving features like charge pump booster and programmable panel offset control.

Analog Video Decoder

NTSC (M, 4.43) and PAL (B, D, G, H, I, M, N, N combination), PAL (60), SECAM with automatic format detection

- Advanced synchronization processing for VCR trick play signal
- Two 10-bit ADCs and analog clamping circuit
- Built-in analog anti-aliasing filter
- Fully programmable static gain or automatic gain control for the Y or CVBS channel
- Programmable white peak control for the Y or CVBS channel
- Software selectable analog inputs allows any of the following combinations:
 - Up to 4 composite video
 - UP to 1 S-Video
- 4-H adaptive comb filter Y/C separation
- PAL delay line for color phase error correction
- Digital PLL for both color and horizontal locking
- Programmable hue, brightness, saturation, contrast, sharpness, Gamma control, and noise suppression
- Automatic color control and color killer
- Detection of level of copy protection according to Macrovision standard

TFT PANEL SUPPORT

- Supports a wide variety of Analog active matrix TFT panels
- Supports delta RGB 8 bits digital pixel format

ON SCREEN DISPLAY

- Built-in OSD controller with integrated character ROM and programmable RAM font
- Multi-window OSD support with color palette
- Supports OSD overlay with alpha blending

IMAGE CONTROL

- Programmable hue, brightness, saturation, contrast
- Sharpness control with vertical peaking
- Programmable color transient improvement control
- Built-in de-interlacing engine

- Independent RGB gain and offset controls
- Panorama / Water-glass scaling
- YCbCr hue adjustment
- Programmable Gamma correction tables

POWER MANAGEMENT

- Supports Panel power sequencing
- Supports DPMS for monitor power management
- 1.8 / 3.3 V operation

TIMING CONTROLLER (TCON)

- Support programmable interface signals for control column (source) driver / row (gate) driver

MISCELLANEOUS

- Supports 2-wire serial bus interface
- Spread spectrum PLL
- Programmable panel VCOM offset control
- Dual charge pumping circuit with feedback sensing
- 5V tolerant I/O
- Power-down mode
- Typical power consumption less than 500mW
- Single 27MHz crystal
- 64-pin LQFP package

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9001 quality systems.

Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality.

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com