



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Energy
Efficient Solutions
optimized for low power

Quick Start Guide

TWR-K53N12 for low-power
MCU with analog, USB and
segment LCD



TOWER SYSTEM

Get to Know the TWR-K53N512




Figure 1: Front Side of TWR-K53N512 Module Not Including TWRPI.

TWR-K53N512 Freescale Tower System



The TWR-K53N512 microcontroller module is part of the Freescale Tower System, a modular development platform that enables rapid prototyping and tool re-use through reconfigurable hardware. Take your design to the next level and begin constructing your Tower System today by visiting freescale.com/Tower for additional Tower System microcontroller modules and compatible peripherals.




Figure 2: Front Side of TWR-K53N512 Module with TWRPI-SLCD Attached.




Figure 3: Back Side of TWR-K53N512 Module.

Configuration Instructions

In this Quick Start Guide, you will learn how to set up the TWR-K53N512 module and run the default demonstration.

1 Install the Software and Tools

Install the P&E Micro Kinetis Tower Toolkit to install the OSJTAG and USB-to-serial drivers. These can be found on the DVD under “Software.”

2 Configure the Hardware

Install the included battery into the VBAT (RTC) battery holder. Then, plug in the included segment LCD Tower plug-In (TWRPI-SLCD) into the touch/SLCD TWRPI socket. Finally, connect one end of the USB cable to the PC and the other end to the power/OSJTAG mini-B connector on the TWR-K53N512 module. Allow the PC to automatically configure the USB drivers if needed.

3 Tilt the Board

Tilt the board side to side to see the LEDs on E1–E2 light up as it is tilted.

4 Navigate the Segment LCD

The segment LCD toggles all the segments on and off. Press SW2 to cycle between viewing the seconds, hours and minutes, potentiometer percent and temperature.

5 Explore Further by Conducting Lab 1: TWR-K53N512 Quick Start Demo

Explore all the features and capabilities of the pre-programmed demo by reviewing the “TWR-K53N512 Quick Start Demo Labs” document located on the DVD under “Documentation” or at freescale.com/TWR-K53N512.

6 Learn More About the Kinetis K50 Microcontrollers

Find more MQX™ and bare-metal labs and software for the Kinetis K50 micro controllers at freescale.com/TWR-K53N512.

Jumper Options

The following is a list of all the jumper options. The default installed jumper settings are shown in **Red**.

Jumper	Option	Setting	Description
J1	ADC1_DM1 Input Selection	ON	ADC1_DM1 reads POTENTIOMETER
		OFF	ADC1_DM1 reads MEDICAL CONNECTOR
J3	FlexBus Address Latch Selection	2-3	Enable FlexBus address latch
		1-2	Disable FlexBus address latch
J4	Medical Connector J19 Pin3 Selection	1-2	Select I2C1_SCL connection to MEDICAL CONNECTOR
		2-3	Select FTM2_CH1 connection to MEDICAL CONNECTOR
J5	IR Transmitter Connection	OFF	Disconnect PTD7/CMT_IRO from IR transmitter circuit (IRDA)
		ON	Connect PTD7/CMT_IRO to IR transmitter circuit (IRDA)
J6	FlexBus or SSI0 Selection	ON	Use PTE7 for Flex bus
		OFF	Use PTE7 for SSI0

Jumper Option		Setting	Description
J7	Ethernet/TOUCH PAD TWRPI Selection	ON	Use PTB0 for Ethernet
		OFF	Use PTB0 for TOUCH PAD TWRPI
J11	Clock Input Source Selection	1-2	Connect main EXTAL to on-board 50 MHz clock
		2-3	Connect EXTAL to the CLKIN0 signal on the elevator connector
J12	SD Card/TOUCH PAD TWRPI Selection	OFF	Use PTE2 for SD card reader (SD/MMC SKT)
		ON	Use PTE2 for TOUCH PAD TWRPI
J14	IR Transmitter Filter Selection	OFF	IR input to CMP0_IN0 is not low-pass filtered by a 0.1 uF cap
		ON	IR input to CMP0_IN0 is low-pass filtered by a 0.1 uF cap
J15	MCU Power Connection	ON	Connect on-board 3.3V supply to MCU
		OFF	Isolate MCU from power (connect an ammeter to measure current)

Jumper	Option	Setting	Description
J16	VBAT Power Connection	1-2	Connect VBAT to on-board 3.3V supply
		2-3	Connect VBAT to the higher voltage between on-board 3.3V supply or coin-cell supply
J17	On-Board 50 MHz Power Connection	ON	Connect on-board 3.3V supply to on-board 50 MHz OSC
		OFF	Disconnect on-board 3.3V supply to on-board 50 MHz OSC
J18	VREGIN Power Connection	ON	Connect USB0_VBUS from Elevator to VREGIN
		OFF	Disconnect USB0_VBUS from Elevator to VREGIN
J20	SD Card/GENERAL PURPOSE TWRPI Selection	OFF	Use PTE1 for SD card reader (SD/MMC SKT)
		ON	Use PTE1 for GENERAL PURPOSE TWRPI

Jumper	Option	Setting	Description
J21	Accelerometer Power Connection	ON	Connect accelerometer to on-board 3.3V supply
		OFF	Disconnect accelerometer from on-board 3.3V supply
J22	Off-Board Power input	Always OFF	J22 pin 1 can be connected to an off-board external power source. This board is only tested with 3.3V. Care should be taken not to connect to a voltage that is out of the components specification
		Always OFF	J22 pin 2 can be connected to the ground of the off-board external power source
J24	Off or On Board Power Input Selection	1-2	Board SYS_PWR is powered from on-board 3.3V regulator
		2-3	Board SYS_PWR is powered from off-board supply from J22 pin 2
J25	JTAG Board Power Connection	OFF	Disconnect on-board 5V supply to JTAG port
		ON	Connect on-board 5V supply to JTAG port (supports powering board from JTAG pod supporting 5V supply output)

Jumper Option		Setting	Description
J26	SD Card/GENERAL PURPOSE TWRPI Selection	OFF	Use PTE0 for SD card reader (SD/MMC SKT)
		ON	Use PTE0 for GENERAL PURPOSE TWRPI
J28	OSJTAG Bootloader Selection	OFF	Debugger mode
		ON	OSJTAG bootloader mode (OSJTAG firmware reprogramming)
J29	Ethernet/TOUCH PAD TWRPI Selection	ON	Use PTB1 for Ethernet
		OFF	Use PTB1 for TOUCH PAD TWRPI
J32	TOUCH PAD/SLCD TWRPI Selection	1-2	PTB10_LCD_P10 pin is connected to J8 pin 3 for SLCD TWRPI
		2-3	PTB0_TSI0_CH0 pin is connected to J8 pin 3 for TOUCH PAD TWRPI. Make sure J29 and J7 are off to avoid conflict with Ethernet

Jumper Option		Setting	Description
J33	TOUCH PAD/SLCD TWRPI Selection	1-2	PTB11_LCD_P11 pin is connected to J8 pin 5 for SLCD TWRPI
		2-3	PTB1_TSIO_CH6 pin is connected to J8 pin 5 for TOUCH PAD TWRPI. Make sure J29 and J7 are off to avoid conflict with Ethernet
J34	On-Board 50 MHz Enable Source	OFF	On-board 50 MHz osc is enabled if J17 jumper is on. No need to have any jumper on J34
		1-2	On-board 50 MHz osc is enabled if J17 jumper is on
		2-3	On-board 50 MHz osc enable by GPIO PTA19 allowing MCU to turn off clock for lower power consumption

For more information about this and other Tower System modules and kits, please visit freescale.com/TWR-K53N512, freescale.com/Kinetis and freescale.com/Tower.

Freescale and the Freescale logo are trademarks of Freescale Semiconductor, Inc., Reg. U.S. Pat. & Tm. Off. The Energy-Efficient Solutions logo and Kinetis are trademarks of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners. © 2011 Freescale Semiconductor, Inc.

Doc Number: K53N512QSG / REV 0
Agile Number: 926-78598 / REV A

