

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









TYS8040221M-10

PHYSICAL DIMENSIONS:


Α	8.00	±	0.30
В	8.00	±	0.30
С	4.00	<u>+</u>	0.20 0.30
D	2.45	±	0.30
Ε	3.10	±	0.30




RECOMMENDED SOLDERING CONDITIONS



LAND PATTERNS FOR REFLOW SOLDERING






ELECTRICAL SPECIFICATION

	Min	Nom	Max
INDUCTANCE (uH) L @ 100 KHz/1V ± 20%	176	220	264
DCR (Ω)		0.599	0.7787


CHARACTERISTICS OF TEMPERATURE RISE





Saturation Current(A)	0.85
SRF (MHz)	3.5
Temperature Rise Current (A)	0.80

CURRENT VS INDUCTANCE DROP IN RATES



NOTES:

- 1.OPERATION TEMPERATURE RANGE: -40°C~+125°C (INCLUDING SELF-HEATING).
- 2.STORAGE TEMPERATURE RANGE (PACKAGING CONDITIONS): -10°C TO +40°C AND RH 70% (MAX.)
- 3.UNLESS OTHERWISE SPECIFIED, THE STANDARD ATMOSPHERIC CONDITIONS FOR MEASUREMENT/TEST AS:
 A. AMBIENT TEMPERATURE: 20±15°C.
- B. RELATIVE HUMIDITY: 65%±20%.
- 4.SATURATION CURRENT IS THE DC CURRENT AT WHICH THE INDUCTANCE DROPS OFF APPROXIMATELY 30% FROM ITS VALUE WITHOUT CURRENT.(AMBIENT TEMPERATURE 25±5°C)

5.TEMPERATURE RISE CURRENT (IRMS):

DC CURRENT THAT CAUSES THE TEMPERATURE RISE (△T ≤40°C) FROM 25°C AMBIENT.

		DIMENSIONS ARE IN mm .			This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			Laird			
ı					PROJECT/PART NUMBER:	- 11	SEA	PART TO		DRAWN BY:	
	С	CHANGE DIMENSIONS C/D/E	08/18/16		TYS8040221M-10		С		WER CTOR	QIU	
	В	CHANGE TEMP. FROM −25°C~+125°C	12/26/12		DATE: 06/01/12	SCALE: NTS		75	SHEET:		
	Α	ORIGINAL DRAFT	06/01/12	QIU		TOOL		13			
	REV	DESCRIPTION	DATE	INT			-		1 of 1		