imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

6-ft. USB A/B Cable (A Male to Right Angle Adjustable B Male Connector)

MODEL NUMBER: U013-006



Description

Tripp Lite's 6-ft. Adjustable "B" connector USB A/B device cable is designed to connect a USB device to the USB port on a computer or USB hub. Adjustable angle connector allows the cable to exit at any angle...perfect where space is limited. This high quality cable delivers the performance and reliability you expect from a USB cable. The cable features gold plated contacts for superior conductivity. It is manufactured with molded connectors which include integral strain relief to ensure durability. Double shielding provides maximum EMI/RFI protection. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Two elbow joints allow for Up-Down-Left-Right exit configurations where space constraints are an issue
- Premium double-shielded USB 2.0 cable with tinned copper braid and aluminum Mylar foil feature twisted data lines
- Gold plated copper contacts provide superior conductivity
- · Molded connectors which include integral strain relief to ensure durability
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
UPC Code	037332122339
Technology	USB (all versions); USB 2.0 (High Speed)
INPUT	
Cable Length (ft.)	6

Highlights

- Adjustable "B" connector allows for multiple exit configurations
- Premium double-shielded cables with tinned copper braid and aluminum mylar foil feature twisted 28/20 AWG data linesPremium double-shielded USB 2.0 cable with tinned copper braid and aluminum mylar foil feature twisted data lines
- Gold plated contacts provide superior conductivity for low and high speed devices

System Requirements

• USB port and device

Package Includes

6ft USB A/B Cable w/Adjustable

Angle B Connector



Cable Length (m)	1.00	
Cable Length (m)	1.83	
PHYSICAL		
Shipping Dimensions (hwd / in.)	9.250 × 6.750 × 0.500	
Shipping Dimensions (hwd / cm)	23.50 x 17.14 x 1.27	
Shipping Weight (lbs.)	0.2300	
Shipping Weight (kg)	0.10	
Color	Black	
CONNECTIONS		
Side A - Connector 1	USB A (MALE)	
Side B - Connector 1	USB B (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies