

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

## USB 2.0 Active Extension Cable (A M/F), 16-ft.

MODEL NUMBER: U026-016





#### Description

Tripp Lite's 16-ft. USB 2.0 Extension Cable is a bus powered extension cable that can be used to increase the length of a device cable without the worry of signal loss and potential performance problems. USB limits a cable's length to 16ft. Any length above 16 feet requires the use of an active cable such as this one. This cable has a signal booster built in. The overall cable length can be extended up to 80ft. by daisy-chaining up to 5 of these active cables. The U026-016 provides up to 150mA of power to the connected device. If your device requires more than 150mA of power, it will either need to have its own power supply or need to be plugged into a powered USB 2.0 hub (such as U222-004-R) that is connected to the U026-016. Use a standard 6' 10' or 15' USB cable to reach the desired distance.

#### **Features**

- Extend a USB 2.0 signal passed the 16 ft. (5 m.) distance limitation
- Works together with standard USB 2.0 cables
- Bus powered signal booster
- Daisychain up to 5 cables to extend the signal up to 80 ft. passed the 16 ft. (5 m.) distance limitation
- The U026-016 provides up to 150mA of power to the connected device. If your device requires more
  than 150mA of power, it will either need to have its own power supply; or, to be plugged into a powered
  USB 2.0 hub (such as U222-004-R) that is connected to the U026-016.

#### **Highlights**

- Premium double-shielded cables with tinned copper braid and aluminum mylar foil feature twisted 28/22 AWG data/power lines
- Gold plated contacts provide superior conductivity for low and high speed devices (1.5 to 480 Mbps.)
- Active extension cable regenerates USB signal for extra-long distances: daisychain up to 80-ft. in most applications

### **System Requirements**

- A USB 2.0 port and USB 2.0 device are required to achieve USB 2.0 speeds. A USB 1.1 port and/or device can be used, but you will not be able to achieve USB 2.0 speeds.
- The U026-016 provides up to 150mA of power to the connected device. If your device requires more than 150mA of power, it will either need to have its own power supply; or, to be plugged into a powered USB 2.0 hub (such as U222-004-R) that is connected to the U026-016.

#### **Package Includes**

• 16-ft. USB 2.0 Extension Cable (USB A M/F)

## **Specifications**





OVERVIEW	
UPC Code	037332120588
Technology	USB 2.0 (High Speed); USB (all versions)
INPUT	
Cable Length (ft.)	16
Cable Length (m)	4.9
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.000 x 4.500 x 5.900
Shipping Dimensions (hwd / cm)	2.54 x 11.43 x 14.99
Shipping Weight (lbs.)	0.4000
Shipping Weight (kg)	0.18
Color	Black
ENVIRONMENTAL	
Storage Temperature Range	-20 to 80 C (-4 to 176 F)
Operating Temperature	-20 to 80 C (-4 to 176 F)
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	USB A (FEMALE)
CERTIFICATIONS	
Certifications	RoHS-Compliant
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>