



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## 10-Port USB 2.0 Hub

MODEL NUMBER: **U222-010-R**



### Description

Tripp Lite's 10-port USB 2.0 hub is the most versatile and powerful hub on the market. This USB 2.0 hub allows you to connect up to ten USB devices to a single USB port on your computer. Features two swivel ports, for easy connection of MP3, flash drive and similar devices. This unit meets or exceeds USB 2.0 Specifications for Hi-Speed data transmission rates up to 480Mbps. Perfect for both the mobile and desktop user. While the hub will function perfectly in virtually all cases without needing external power, a multi-voltage AC adapter (100-240V) is included in the event you are connecting power hungry devices. The U222-010-R is backwards compatible so that it will function with both USB 2.0 and USB 1.1 devices. Over-current protection safeguards connected equipment from overvoltages. Includes a Hub to Computer USB Cable - 3ft USB "A" Male to 5-pin Mini-B male.

### Features

- USB 2.0 Hi-Speed Hub, 10 Ports
- Hub to Computer USB Cable - 3ft USB "A" Male to 5-pin Mini-B male
- 2 Swivel ports for easy connection of MP3, flash drive and similar devices
- Backward compatible with USB 1.1
- Supports data transfer rates up to 480Mbps
- External power not required
- Plug-and-play/hot-swappable allows you to add or remove a device at any time
- Per-port overcurrent protection
- Bus-powered or self-powered
- Supports USB 2.0 spec up to 500mA per port
- On bus-power, 500mA from the USB 2.0 computer port is shared between the hub ports
- The included external power supply provides 2.5A of power, to be shared between the hub ports (up to 500mA per port)

### Highlights

- USB 2.0 Hi-Speed Hub, 10-Ports
- 2 Swivel ports for easy connection of MP3, flash drive and similar devices
- Backward compatible with USB 1.1
- Compatible with all major operating systems
- Supports USB 2.0 spec up to 500mA per port

### Package Includes

- U222-010-R 10-Port USB 2.0 Hub
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2.5A)
- Hub to Computer USB Cable - 3ft USB "A" Male to 5-pin Mini-B male



- Compact, multi-voltage power supply (100-240V) provided in the event you are connecting power hungry devices
- Compatible with all major operating systems

## Specifications

OVERVIEW	
UPC Code	037332155443
AC Adapter	Input: 100-240VAC, 50/60Hz, 0.5A; Output: 5V, 2.5A
Technology	USB 2.0 (High Speed); USB (all versions)
INPUT	
Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.5A
External Power Supply Output Specs (V / A)	5V / 2.5A
External Power Supply Cord Length (ft.)	5
External Power Supply DC Barrel Connector Specs	OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve
External Power Supply Plug(s)	NEMA 1-15P North America
External Power Supply Certifications	FCC; UL; cUL; RoHS
Bus Powered	No
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Blue (Power)
PHYSICAL	
Shipping Dimensions (hwd / in.)	8.700 x 6.300 x 3.200
Shipping Weight (lbs.)	0.9000
Shipping Weight (kg)	0.41
Unit Packaging Type	Clamshell
Unit Dimensions (hwd / in.)	0.75 x 6.1 x 2.9
Unit Weight (lbs.)	0.4
Unit Weight (kg)	0.18
Material of Construction	ABS
Color	White



<b>ENVIRONMENTAL</b>	
Operating Temperature Range	50 to 104 F (10 to 40 C)
Storage Temperature Range	14 to 176 F (-10 to 80 C)
Relative Humidity	0% to 90 RH, Non-Condensing
BTUs	8.5 BTU/Hr
<b>CONNECTIONS</b>	
Ports	10
Side A - Connector 1	USB MINI-B 5-PIN (FEMALE)
Side B - Connector 1	(10) USB A (FEMALE)
Connector Plating	Nickel
<b>FEATURES &amp; SPECIFICATIONS</b>	
USB Specification	USB 2.0 (up to 480 Mbps)
Driver Required	No
<b>CERTIFICATIONS</b>	
Certifications	Tested to CE, FCC, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>