



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Virtual 7.1-Channel USB External Sound Card

MODEL NUMBER: **U237-001**



Adds external microphone, speaker and/or headphone ports, as well as volume and mute controls, to your computer or laptop via USB port. An inexpensive replacement for damaged sound cards or audio connectors.

Description

The U237-001 Virtual 7.1-Channel USB External Sound Card plugs into your computer or laptop's USB port to provide easy-to-access audio-in and audio-out ports. A convenient, inexpensive replacement for a damaged sound card or audio connectors, the U237-001 lets you plug a microphone, speakers and/or headphones into its 3.5 mm audio jacks and enjoy rich, vibrant sound. By installing the Xear™ 3D Virtual 7.1-Channel Surround Sound software (included), you'll be able to customize the audio settings.

In addition to the two audio ports, the U237-001 features volume controls, microphone and speaker muting buttons, and LEDs that indicate audio status, activity and microphone/speaker mute. It's plug-and-play, with the USB audio driver automatically installing upon connection to a USB port. Compatible with Windows® 2000™ and later, Mac OS X® and Linux. Xear 3D software compatible with Windows XP, 7 and 8™.

Features

Adds an External Sound Card to Your Computer's USB Port

- Dual 3.5 mm audio jacks for connecting microphone, speakers and/or headphones
- Inexpensive replacement for damaged sound card or audio connectors
- Easy-access volume controls
- Microphone/speaker muting buttons
- LEDs indicate status, activity and mute

Xear 3D Virtual 7.1-Channel Surround Sound Software

- Customizable audio settings

Highlights

- Customizable audio settings via included CD software
- Supports 3D and virtual 7.1-channel surround sound
- LEDs indicate status, activity and speaker/microphone mute
- Plug and play—no external power supply required
- Compatible with Windows, Mac and Linux

System Requirements

- Available USB-A port
- 3.5 mm stereo speakers, headphones and/or microphone
- Windows 2000 and later, Mac OS X or Linux
- Windows XP, 7 and 8 (Xear 3D software)

Package Includes

- U237-001 Virtual 7.1-Channel USB External Sound Card
- Xear 3D Virtual 7.1-Channel Sound Software CD
- Owner's manual



- Supports 3D and virtual 7.1-channel surround sound
- Preset sound effects with 10-band equalizer
- Software compatible with Windows XP, 7 and 8

Easy to Use

- Plug and play—no external power supply required
- USB driver automatically installs upon connection
- Unit compatible with Windows 2000 and later, Mac OS X and Linux

Specifications

OVERVIEW	
UPC Code	037332192745
Technology	Stereo Audio; USB (all versions); USB 2.0 (High Speed)
INPUT	
Bus Powered	Yes
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Red (Speaker/Mic Mute), Green (Active)
PHYSICAL	
Shipping Dimensions (hwd / in.)	5.800 x 2.170 x 4.200
Shipping Dimensions (hwd / cm)	14.73 x 5.51 x 10.67
Shipping Weight (lbs.)	0.1000
Shipping Weight (kg)	0.05
Unit Packaging Type	Clamshell
Unit Dimensions (hwd / in.)	0.55 x 2.2 x 1
Unit Weight (lbs.)	0.02
Unit Weight (kg)	0.01
Material of Construction	PVC
Color	Black
ENVIRONMENTAL	
Operating Temperature Range	32 to 104 F (0 to 40 C)
Storage Temperature Range	14 to 131 F (-10 to 55 C)
Relative Humidity	5% to 90% RH, Non-Condensing



BTUs	1.7 BTU/Hr
Power Consumption (Watts)	0.5
CONNECTIONS	
Ports	2
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	(2) 3.5MM (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
Audio Specification	7.1 Surround Sound
Driver Required	No
CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH, WEEE
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>