



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



OCDemon™ from Macraigor Systems

Make your debugging a little bit easier ...



[\[Home \]](#) | [\[Hardware Products \]](#) | [\[Software Products \]](#) | [\[CPUs \]](#) | [\[Tools, etc. \]](#) | [\[FAQ \]](#) | [\[Partners \]](#) | [\[News \]](#)

Wiggler

Raven

usb2Demon™

USBWIGGLER™

usb2Sprite™

mpDemon™

Adapters

usbWiggler™...

Connects to USB 1.1 and USB 2 (Hi-Speed) systems ...

The usbWiggler™ is a Universal Serial Bus interface for JTAG and BDM debugging. Faster than the classic parallel port Wiggler, it is a stable, easy to use device and is fully compatible with all of our software. In addition, it is a true USB 2.0 high speed device.

Note that the usbWiggler can be upgraded later to the clock speeds of a usb2Demon.

The usbWiggler™ is a mid-cost interface used in the design, debug, and programming of microprocessor based embedded systems. One side of the usbWiggler interfaces to the USB port of a host IBM compatible PC and the other side connects to an OCD (On-Chip Debug) port of the target system. This port may be JTAG, E-JTAG, OnCE, COP, BDM or any of several other types of connections. When connected to a USB 2.0 port on your PC, the usbWiggler will operate up to Hi-Speed USB rates (480Mb/s). 32-bit Windows platforms only at this time.

MAKE SURE WE SUPPORT YOUR TARGET PROCESSOR. [CLICK HERE!](#)

NOW SUPPORTED UNDER LINUX.

\$250.00

PURCHASE

Sample download speeds in Bytes per second:

ARM7: 43,000

ARM9: 49,000

AU1xx0: 12,000

MPC82xx: 20,000

MPC85xx: 144,000

PPC440: 39,000

XScale: 119,000