



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832



Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CFP2 / CFP4

The CFP2 and CFP4 (surface mount receptacle connector) are considered as a candidate of future generation of multi hundred Gbps system. Both are 0.6mm pitch with the CFP2 having 104 positions and the CFP4 having 56 positions. They are rated for 28 Gbps per channel with resonance dampening for improved signal integrity. Both the CFP2 and CFP4 have a plug connector on the mating interface that improves accuracy and aids in achieving high speed performance.



Specification Highlights

The CFP2 and CFP4 interconnect systems are comprised of insert molding assemblies for top side contacts and press-fit cage assemblies.

Current Mechanical Characteristics

	CFP2	CFP4
• RSS Tolerance	0.19mmMin	
• Host Depth (mm)	84.5	67
• Host Height (mm)	12.9	10
• Ports in 365(445)mm Faceplate	8(10)	16(19)
• Max Insertion Force with Heat-sink:	6N	
• Max Insertion Force without Heat-sink:	4.5N	
• Max Withdrawal Force with Heat-sink:	5.4N	4.0N
• Max Withdrawal Force without Heat-sink:	3.9N	2.5N

Materials

- Cage
 - o Base Material: Copper Alloy
 - o Heat Sink: Aluminum Alloy

Options

- Heat Sink
- Dust Cover
- Connector Cover
- EMI Gasket

Electrical Characteristics

- Operating Voltage: 3.3 V

CFP2/CFP4 Host Connector

U99 - X XXX - X 0 0 T

U99 SERIES DESIGNATION

X STYLE
 B - CFP2 Connector
 C - CFP4 Connector

XXX NUMBER OF POSITIONS
 104 - CFP2 Connector
 056 - CFP4 Connector (To be Toolled)

PACKAGING
 T - Tape and Reel Packaging

OPTION 2
 0 - Standard

OPTION 1
 0 - Standard

CONTACT PLATING
 2 - 30 μm Gold Plating on Mating Area; Matte Tin Plating on Termination
 3 - 15 μm Gold Plating on Mating Area; Matte Tin Plating on Termination

CFP2/CFP4 Plug Connector

U56 - X XXX - X 0 0 T

U56 SERIES DESIGNATION

X STYLE
 B - CFP2 Connector
 C - CFP4 Connector

XXX NUMBER OF POSITIONS
 104 - CFP2 Connector
 056 - CFP4 Connector (To be Toolled)

PACKAGING
 T - Tape and Reel Packaging

OPTION 2
 0 - Standard

OPTION 1
 0 - Standard

CONTACT PLATING
 2 - 30 μm Gold Plating on Mating Area; Matte Tin Plating on Termination
 3 - 15 μm Gold Plating on Mating Area; Matte Tin Plating on Termination

CFP2/CFP4 Cage

U98 - X X X 0 - 0 0 X X

U98 SERIES DESIGNATION

X STYLE
 B - CFP2 single row
 C - CFP4 single row

X NUMBER OF PORT IN ROW
 1 - Nx1 ports
 2 - Nx2 ports
 3 - Nx3 ports (To be Toolled)
 4 - Nx4 ports (To be Toolled)
 6 - Nx6 ports (To be Toolled)

X HEAT SINK OPTION
 1 - No Heat Sink and No Clip Shipped
 2 - Fin Style (Black Oxide) Heat Sink and Clip (H=10.75mm)
 *Other custom heat sink options are available.

PACKAGING
 1 - Tray Packaging
 A - Tray Packaging; Heat Sink and Clip or Light Pipe Shipped Assembled

CONNECTOR COVER
 0 - With Connector Cover and Kickout Springs
 C - With Connector Cover, no Kickout Springs

OPTIONAL DUST COVER
 0 - Without Dust Cover
 D - With Dust Cover (Ship Loose)

PLATING
 1 - Nickel
 2 - Matte Tin

APPLICATION
 1 - Press Fit Pins - 2.5 mm Long