



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





*NOTE: UC40 SHOWN IN PICTURE ABOVE.
UC26 NOT SHOWN.
PICTURE FOR REFERENCE ONLY.



*NOTE: UCACSR SHOWN IN PICTURE ABOVE.
PICTURE FOR REFERENCE ONLY.

CABLE CUTTER BLADES

NOTES, UNLESS OTHERWISE SPECIFIED:

Panduit Cable Cutter Blades are designed to cut:

- Cuts Copper and Aluminum stranded conductor cables using Panduit Crimp, Cut and Punch Tools. Go to www.panduit.com for more information.

Size Chart:

Consult table below to select appropriate Panduit Cable Cutter Blade set for a specific cable outside diameter (O.D.), and compatible Panduit Crimp, Cut and Punch Tool:

Panduit P/N	For Cable OD Size	Compatible with Panduit Tool(s)
UC26	0 to 1.02" (0 to 26 mm)	CT-2920/CCP, CT-920CH/CCP
UC40	0 to 1.57" (0 to 40 mm) 0 to 0.98" (0 to 25 mm)	CT-2920/CCP, CT-920CH/CCP, CT-3001/CCP WITH UAM*
UCACSR	0 to 1.57" (0 to 40 mm) 0 to 0.98" (0 to 25 mm)	CT-2920/CCP, CT-920CH/CCP, CT-3001/CCP WITH UAM*

* UAM for cutting blades sold separately.

Technical Information:

Consult table below for approximate package size and weight information for each product:

Panduit P/N	Weight	Package Size
UC26	0.35 lb (0.161 kg)	5" L x 3.5" W x 0.5" H
UC40	0.28 lb (0.126 kg)	[152.4 L x 88.9 W x 12.7 H] mm
UCACSR	0.41 lb (0.184 kg)	5" L x 3.5" W x 0.75" H [152.4 L x 88.9 W x 19.1 H] mm

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

UCACSR can also cut:

- ACSR wire 954 kcmil (Cardinal)
- 5/8" (20 mm) Standard Guy Strand
- 1/2" (13 mm) EHS Guy Strand
- 1/2" (13 mm) Ground Rod
- 1/2" (13 mm) Rebar (schedule 60)

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	UC** and UCASCR CABLE CUTTER BLADES					
							CUSTOMER DRAWING					
							ITEM REVISION NAME: 00084SLU_DC/00		PANDUIT			
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± ---		MATERIAL: -----			
00	7-29-16	BKA	ACC	JADE	DRAWING RELEASED	010062	THIRD ANGLE PROJECTION		DRAWING NUMBER: 00084SLU_DC			
							DRAWN BY: BKA	DATE: 7-21-16	CHK ACC	SCALE NONE	SHT 1 OF 1	SIZE B