

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







UF15KM series





Ø 5.39 (Ø137) Ø 0.17 ±0.01 (Ø4.2 ±0.2) 6.38 ±0.01 (162 ±0.3) 6.77 ±0.02 (172 ±0.5)

STATIC PRESSURE - IN. OF WATER .60 Ø 5.91 ±0.04 (Ø150 ±0.5) .40 .30 .20 .10 150 250 AIR FLOW (CFM)

(172 x 150 x 55 mm) 6.77 x 5.91 x 2.17 inches

Features: high temp operating temperature range -40°C ~ 90°C

Operating voltage: 115 or 230 VAC

Construction: aluminum die cast frame;

metal Impeller

Bearing option:	ball bearing
Motor:	shaded pole
Air Flow:	exhaust over struts

Protection: thermal

Connection:

Option: tachometer output LEAD WIRE TYPE

القاا	
<u> </u>	0.31 (8)
0.12	(8)
0.12	TERMINAL TYPE

➾

2.17 ±0.02

 (55 ± 0.5)

ΗН

Model No.	Rated Voltage		Input Power		Locked Cur.	Speed			Max. Static Pressure (H ₂ 0)			
	V	HZ	W	Α	Α	RPM	M³/Min.	CFM	MM	INCH	dbA	kg
UF15KM12H	115	60	42	0.47	0.75	3,250	6.5	230	16	0.63	53	1.10
UF15KM23H	230	60	42	0.23	0.37	3,250	6.5	230	16	063	53	1.10

800-453-4569

Cooling Simplified

terminal or 22 AWG lead wire