



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



UL865-N3G

UMTS | HSPA 7.2/5.76 Embedded



Product Description

The UL865-N3G is a 3G-only, North American, dual-band module in the xL865 family. It is based on the latest Intel chipset to protect the developer’s design investments as a long term availability solution. The UL865-N3G features VQFN packaging that is fully pad-level compatible with its 2G and 3G companions, the CL865-DUAL, GL865 V3 Series and UL865 Series.

Key Benefits

- Simple drop-in migration and technology upgrade solution to 3G high-speed performance for designs currently using 2G xL865 VQFN products
- Ideal for fleet management and track-and-tracing application with easy to follow reference designs pairing with Telit GPS and GPS / GLONASS receivers
- Internet application friendly with integrated TCP/IP and UDP/IP stacks
- Voice-capable for applications requiring digital (DVI) interface
- Complete SMT platform for m2m solutions running the customer application inside the module with embedded Python Script Interpreter
- Over-the-Air firmware update via Premium FOTA Management service
- Battery-friendly 1.8V GPIO

Family Concept

The Telit xL865 family was conceived to address system integrators and developers needing to start with low volumes (LCC mounting) as well as those already running high volumes (VQFN mounting). Its ultra-compact package allows integration into very small devices. The family includes products that are pin-to-pin and API compatible in GSM | GPRS, CDMA | 1xRTT and UMTS | HSPA.

Variants

Single variant with band combination for North American applications only

IoT Connectivity Ready

This product is capable of supporting the extensive suite of IoT Connectivity value-added services and connectivity you can use to enhance your application and boost your competitive advantage.

AVAILABLE FOR


- EMEA
- North America
- Latin America
- APAC
- Korea
- Australia

Combine your Cellular module with

Short Range modules



GNSS modules



www.telit.com

Complete, Ready to Use Access to the Internet of Things



UL865-N3G

Product Features

- Supported Frequencies
UMTS | HSPA: 850 / 1900 MHz
- SIM Access Profile
- 3GPP release 7 compliant
- Control via AT commands according to 3GPP TS27.005, 27.007 and customized Telit AT commands
- Serial port multiplexer 3GPP TS27.010
- SIM application Tool Kits 3GPP TS 51.014
- Built in UDP / TCP / FTP / SMTP stack
- Digital voice and SMS
- IP stack with TCP and UDP protocols
- Standard and extended AT command set

Data

HSPA category 6 in Uplink and up to category 8 in Downlink:

- HSUPA up to 5.76 Mbps
- HSDPA up to 7.2 Mbps

Environmental

- Small dimensions 24.4 x 24.4 x 2.6 mm
- Temperature range -40°C to +85°C

Interfaces

- 8 I/O ports maximum including multifunctional I/Os (1.8 V logic level)
- I2S for digital audio interface
- USB 2.0 HS
- UART
- SPI
- 1.8 V / 3 V SIM interface
- 2 A/D plus 1 D/A converters

Approvals

- RoHS Compliant
- FCC, PTCRB, IC (North America)

Electrical

- Output power
 - Class 3 (0.25 W, 24 dBm) @ UMTS
- Supply voltage
 - Nominal: 3.8 VDC
 - Range: 3.4 - 4.2 VDC

Software

- Python* application resources
- Python* version = 2.7.2
- Python* script interpreter (module takes the application code directly in the Python* language)
- Memory: 2 MB of NV memory for the user scripts and 2 MB RAM for the Python engine usage

Additional features

- PFM (Premium FOTA Management) Over-The-Air Update service
- Remote AT commands
- Event monitor



Join the Telit Technical Forum

For a quicker and more rewarding integration experience join the Telit Technical Forum. There you can browse the first open forum covering all IoT topics, get direct support by region (EMEA, North America, Latin America, APAC), take part in this quickly growing IoT community and exchange experiences.