

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



UM30-212112

UM30

ULTRASONIC SENSORS

**SICK**  
Sensor Intelligence.



### Ordering information

| Type        | Part no. |
|-------------|----------|
| UM30-212112 | 6037665  |

Other models and accessories → [www.sick.com/UM30](http://www.sick.com/UM30)



### Detailed technical data

#### Performance

|  |   |
|--|---|
| <b>Operating range, limiting range</b> | 65 mm ... 350 mm, 600 mm  |
| <b>Target</b>                          | Natural objects   |
| <b>Resolution</b>                      | ≥ 0.18 mm   |
| <b>Repeatability</b>                   | ± 0.15 % <sup>1)</sup>  |
| <b>Accuracy</b>                        | ± 1 % <sup>1) 2)</sup>  |
| <b>Temperature compensation</b>        | ✓   |
| <b>Response time</b>                   | 64 ms   |
| <b>Switching frequency</b>             | 12 Hz   |
| <b>Output time</b>                     | 16 ms   |
| <b>Ultrasonic frequency (typical)</b>  | 400 kHz   |
| <b>Detection area (typical)</b>        | See diagrams  |
| <b>Additional function</b>             | Set switching mode: Distance to object (DtO) / Window (Wnd) / Object between sensor and background (ObSB), teach-in of switching output, set levels of switching outputs, Invertable switching output, set on delay switching output, temperature compensation, synchronization of up to 10 sensors, multiplexing: no cross talk of up to 50 sensors, set measurement filters: value filter, filter strength, adjustable sensitivity, foreground suppression and detection area, switch-off display, reset to factory default <sup>3)</sup> |

<sup>1)</sup> Referring to current measurement value.

<sup>2)</sup> Temperature compensation can be switched off, without temperature compensation: 0.17 % / K.

<sup>3)</sup> Functions may vary depending on sensor type.

#### Interfaces

|                                   |                                |
|-----------------------------------|--------------------------------|
| <b>Switching output</b>           | 2 x PNP (200 mA) <sup>1)</sup> |
| <b>Multifunctional input (MF)</b> | 1 x MF                         |
| <b>Hysteresis</b>                 | 5 mm                           |

<sup>1)</sup> PNP: HIGH = V<sub>S</sub> - (< 2 V) / LOW = 0 V.

## Mechanics/electronics

|  |   |
|--|---|
| <b>Supply voltage <math>V_s</math></b> | DC 9 V ... 30 V <sup>1) 2)</sup>  |
| <b>Power consumption</b>               | $\leq 2.4 \text{ W}$ <sup>3)</sup>  |
| <b>Initialization time</b>             | < 300 ms  |
| <b>Design</b>                          | Cylindrical   |
| <b>Housing material</b>                | Nickel-plated brass, PBT<br>Display: TPU<br>Ultrasonic transducer: polyurethane foam, glass epoxy resin |
| <b>Connection type</b>                 | Male connector, M12, 5-pin  |
| <b>Indication</b>                      | LED display, 2 x LED  |
| <b>Weight</b>                          | 150 g   |
| <b>Sending axis</b>                    | Straight  |
| <b>Enclosure rating</b>                | IP67  |
| <b>Protection class</b>                | III   |

<sup>1)</sup> Limit values, reverse-polarity protected Operation in short-circuit protected network: max. 8 A, class 2.

<sup>2)</sup> 15 V ... 30 V when using the analog voltage output.

<sup>3)</sup> Without load.

## Ambient data


|                                      |                   |
|--------------------------------------|-------------------|
| <b>Ambient temperature operation</b> | -25 °C ... +70 °C |
| <b>Ambient storage temperature</b>   | -40 °C ... +85 °C |

## Classifications

|                       |          |
|-----------------------|----------|
| <b>ECl@ss 5.0</b>     | 27270804 |
| <b>ECl@ss 5.1.4</b>   | 27270804 |
| <b>ECl@ss 6.0</b>     | 27270804 |
| <b>ECl@ss 6.2</b>     | 27270804 |
| <b>ECl@ss 7.0</b>     | 27270804 |
| <b>ECl@ss 8.0</b>     | 27270804 |
| <b>ECl@ss 8.1</b>     | 27270804 |
| <b>ECl@ss 9.0</b>     | 27270804 |
| <b>ETIM 5.0</b>       | EC001846 |
| <b>ETIM 6.0</b>       | EC001846 |
| <b>UNSPSC 16.0901</b> | 41111960 |


### Dimensional drawing (Dimensions in mm (inch))

UM30-211, UM30-212, UM30-213




- ① Connection
- ② Display
- ③ Mounting nuts, SW 36 mm

### Connection type




### Connection diagram

UM30-21x112 UM30-21x115 Connector M12, 5-pin



- ① Synchronization and multiplex operation/communication Connect+


Adjustment possible



- ② Display
- ④ Operating elements
- ⑤ Status indicators

Detection area







UM30-212



- ① Detection range dependent on reflection properties, size, and alignment of the object
- ② Limiting range
- ③ Operating range
- ④ Example object: aligned plate 500 mm x 500 mm
- ⑤ Example object: pipe with 27 mm diameter

### Recommended accessories

Other models and accessories → [www.sick.com/UM30](http://www.sick.com/UM30)

|  | Brief description   | Type                   | Part no. |
|--|---|------------------------|----------|
| <b>Mounting brackets and plates</b>  |   |                        |          |
|   | Mounting plate for M30 sensors, steel, zinc coated, without mounting hardware   | BEF-WG-M30             | 5321871  |
|   | Mounting bracket for M30 sensors, steel, zinc coated, without mounting hardware   | BEF-WN-M30             | 5308445  |
| <b>Terminal and alignment brackets</b>   |   |                        |          |
|   | Mounting bracket, M30, axial rotation possible, with threaded mounting hole M6, without mounting hardware                             | BEF-HA-M30A            | 5311527  |
| <b>Plug connectors and cables</b>  |   |                        |          |
|   | Head A: female connector, M12, 5-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PVC, unshielded, 2 m | YF2A15-020VB5XLEAX     | 2096239  |
|   | Head A: female connector, M12, 5-pin, angled, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PVC, unshielded, 2 m   | YG2A15-020VB5XLEAX     | 2096215  |
| <b>Programming and configuration tools</b>   |   |                        |          |
|  | Tool for visualization, configuration and cloning, 3-digit LED display, supply voltage: DV 9 V ... 30 V                               | Connect+ adapter (CPA) | 6037782  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations [www.sick.com](http://www.sick.com)