



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832






Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Power Adapter

Model Name	UV305-0510 (US-DC)	UVE305-0510 (EU-DC)	UN315-1212 (US-LDC)	UNE315-1212 (EU-LDC)
Picture				
Part Number	50500051500003G	50500051500013G	50500151120004G	50500151120014G
Input				
Plug Type	US	EU	US	EU
Input Voltage	100 - 240VAC		100-240 VAC	
Output Voltage	5 VDC		12 VDC	
Connector Type	DC Jack		Lockable DC Jack	
Physical Characteristics				
Jack Outer Diameter (mm)	3.5 mm		5.5 mm	
Jack Inner Diameter (mm)	1.35 mm		2.1 mm	
Jack/Plug Length (mm)	7.5 mm		9.5 mm	
Dimension w/o cord (LxWxH)	58.8 x 28 x 37.6 mm		64.5 x 50.2 x 29.8 mm	
Cord Length(mm)	1500 ±100 mm		1500 ±100 mm	
Weight (g)	60 g	64 g	98 g	103 g
Environmental Limits				
Operating Temperature	0 ~ 40°C (32 ~ 104°F)		0 ~ 40°C (32 ~ 104°F)	
Regulatory Approvals				
Safety	TUV/PSE/CE/FCC	CE/FCC	UL/PSE/FCC	CE/FCC
CEC Level	6	6	6	6

Model Name	UN315-1212 (US-Y)	UNE315-1212 (EU-Y)	UN315-1212 (US)	UN315-1212 (EU)	UN315-1212 (UK)
Picture					
Part Number	50500151120003G	50500151120013G	50500151120208G	50500151120218G	50500151120228G
Input					
Plug Type	US	EU	US	EU	UK
Input Voltage	100-240 VAC			100-240 VAC	
Output Voltage	12 VDC			12 VDC	
Connector Type	Y-Type (BT1-10V), include Terminal Block			DC Jack	
Physical Characteristics					
Jack Outer Diameter (mm)	-			5.5 mm	
Jack Inner Diameter (mm)	-			2.1 mm	
Jack/Plug Length (mm)	10.5 mm			10.5 mm	
Dimension w/o cord (LxWxH)	64.5 x 50.2 x 29.8 mm			63.9 x 49.5 x 29.5 mm	
Cord Length(mm)	1500 ±100 mm			1500 ±100 mm	
Weight (g)	121 g	130 g	110 g	106 g	114 g
Environmental Limits					
Operating Temperature	0 ~ 40°C (32 ~ 104°F)			0 ~ 40°C (32 ~ 104°F)	
Regulatory Approvals					
Safety	UL/PSE/CE/FCC	CE/FCC	UL/PSE/CE/FCC	CE/FCC	CE/FCC
CEC Level	6	6	6	6	6

Atop Technologies, Inc.

TEL : +886-3-5508137 FAX: +886-3-5508131

sales@atop.com.tw

http://www.atop.com.tw



Design and specification are subjected to change without notice.

All product names referenced herein are registered trademarks of their respective companies.

V0.3