



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



UNR911xJ Series (UN911xJ Series)

Silicon PNP epitaxial planar type

For digital circuits

■ Features


- Costs can be reduced through downsizing of the equipment and reduction of the number of parts.
- SS-Mini type package, allowing automatic insertion through tape packing.

■ Resistance by Part Number


	Marking Symbol	(R ₁)	(R ₂)
• UNR9110J (UN9110J)	6L	47 kΩ	—
• UNR9111J (UN9111J)	6A	10 kΩ	10 kΩ
• UNR9112J (UN9112J)	6B	22 kΩ	22 kΩ
• UNR9113J (UN9113J)	6C	47 kΩ	47 kΩ
• UNR9114J (UN9114J)	6D	10 kΩ	47 kΩ
• UNR9115J (UN9115J)	6E	10 kΩ	—
• UNR9116J (UN9116J)	6F	4.7 kΩ	—
• UNR9117J (UN9117J)	6H	22 kΩ	—
• UNR9118J (UN9118J)	6I	0.51 kΩ	5.1 kΩ
• UNR9119J (UN9119J)	6K	1 kΩ	10 kΩ
• UNR911AJ	6X	100 kΩ	100 kΩ
• UNR911BJ	6Y	100 kΩ	—
• UNR911CJ	6Z	—	47 kΩ
• UNR911DJ (UN911DJ)	6M	47 kΩ	10 kΩ
• UNR911EJ (UN911EJ)	6N	47 kΩ	22 kΩ
• UNR911FJ (UN911FJ)	6O	4.7 kΩ	10 kΩ
• UNR911HJ (UN911HJ)	6P	2.2 kΩ	10 kΩ
• UNR911LJ (UN911LJ)	6Q	4.7 kΩ	4.7 kΩ
• UNR911MJ	EI	2.2 kΩ	47 kΩ
• UNR911NJ	EW	4.7 kΩ	47 kΩ
• UNR911TJ (UN911TJ)	EY	22 kΩ	47 kΩ
• UNR911VJ	FC	2.2 kΩ	2.2 kΩ

■ Absolute Maximum Ratings T_a = 25°C

Parameter	Symbol	Rating	Unit
Collector-base voltage (Emitter open)	V _{CBO}	-50	V
Collector-emitter voltage (Base open)	V _{CEO}	-50	V
Collector current	I _C	-100	mA
Total power dissipation	P _T	125	mW
Junction temperature	T _j	125	°C
Storage temperature	T _{stg}	-55 to +125	°C



Internal Connection



(Note) The part numbers in the parenthesis show conventional part number.

■ Electrical Characteristics $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$


Parameter	Symbol	Conditions	Min	Typ	Max	Unit				
Collector-base voltage (Emitter open)	V_{CBO}	$I_C = -10 \mu\text{A}, I_E = 0$	-50			V				
Collector-emitter voltage (Base open)	V_{CEO}	$I_C = -2 \text{mA}, I_B = 0$	-50			V				
Collector-base cutoff current (Emitter open)	I_{CBO}	$V_{CB} = -50 \text{V}, I_E = 0$			-0.1	μA				
Collector-base cutoff current (Emitter open)	I_{CEO}	$V_{CE} = -50 \text{V}, I_B = 0$			-0.5	μA				
Emitter-base cutoff current (Collector open)	UNR9115J/9116J/9117J/911BJ	I_{EBO}				-0.01	mA			
	UNR9110J/9113J/911AJ					-0.1				
	UNR9112J/9114J/911DJ/ 911EJ/911MJ/911NJ/911TJ					-0.2				
	UNR9111J					-0.5				
	UNR911FJ/911HJ					-1.0				
	UNR9119J					-1.5				
	UNR9118J/911CJ/911LJ/911VJ					-2.0				
Forward current transfer ratio	UNR911VJ	h_{FE}	$V_{CE} = -10 \text{V}, I_C = -5 \text{mA}$	6		20	—			
	UNR9118J/911LJ			20						
	UNR9119J/911DJ/911FJ/911HJ			30						
	UNR9111J			35						
	UNR9112J/911EJ			60						
	UNR9113J/9114J/911AJ/ 911CJ/911MJ			80						
	UNR911NJ/911TJ			80	400					
	UNR9110J/9115J/9116J/ 9117J/911BJ			160	460					
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -10 \text{mA}, I_B = -0.3 \text{mA}$				-0.25	V			
								$I_C = -10 \text{mA}, I_B = -1.5 \text{mA}$		
Output voltage high-level	V_{OH}	$V_{CC} = -5 \text{V}, V_B = -0.5 \text{V}, R_L = 1 \text{k}\Omega$	-4.9			V				
Output voltage low-level	V_{OL}	$V_{CC} = -5 \text{V}, V_B = -2.5 \text{V}, R_L = 1 \text{k}\Omega$				-0.2	V			
								UNR9113J/911BJ	$V_{CC} = -5 \text{V}, V_B = -3.5 \text{V}, R_L = 1 \text{k}\Omega$	
								UNR911DJ	$V_{CC} = -5 \text{V}, V_B = -10 \text{V}, R_L = 1 \text{k}\Omega$	
								UNR911EJ	$V_{CC} = -5 \text{V}, V_B = -6 \text{V}, R_L = 1 \text{k}\Omega$	
								UNR911AJ	$V_{CC} = -5 \text{V}, V_B = -5 \text{V}, R_L = 1 \text{k}\Omega$	
Transition frequency	f_T	$V_{CB} = -10 \text{V}, I_E = 1 \text{mA}, f = 200 \text{MHz}$					80	MHz		
							UNR9113J		150	
							UNR911AJ		80	
							UNR911CJ		150	
Input resistance	R_1					-30%	0.51	+30%	k Ω	
							UNR9119J			1.0
							UNR911HJ/911MJ/911VJ			2.2
							UNR9116J/911FJ/911LJ/911NJ			4.7
							UNR9111J/9114J/9115J			10
							UNR9112J/9117J/911TJ			22
							UNR9110J/9113J/911DJ/911EJ			47
							UNR911AJ/911BJ			100

■ Electrical Characteristics (continued) $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$




Parameter		Symbol	Conditions	Min	Typ	Max	Unit
Emitter-base resistance	UNR911CJ	R_2		-30%	47	+30%	k Ω
Resistance ratio	UNR911MJ	R_1/R_2			0.047		—
	UNR911NJ				0.1		
	UNR9118J/9119J			0.08	0.10	0.12	
	UNR9114J			0.17	0.21	0.25	
	UNR911HJ			0.17	0.22	0.27	
	UNR911TJ				0.47		
	UNR911FJ			0.37	0.47	0.57	
	UNR911AJ/911VJ				1.0		
	UNR9111J/9112J/9113J/911LJ			0.8	1.0	1.2	
	UNR911EJ			1.70	2.14	2.60	
	UNR911DJ			3.7	4.7	5.7	




Note) Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

Common characteristics chart









Characteristics charts of UNR9110J














Characteristics charts of UNR9111J






Characteristics charts of UNR9112J









Characteristics charts of UNR9113J














Characteristics charts of UNR9114J






Characteristics charts of UNR9115J









Characteristics charts of UNR9116J














Characteristics charts of UNR9117J






Characteristics charts of UNR9118J









Characteristics charts of UNR9119J







Characteristics charts of UNR911AJ






Characteristics charts of UNR911BJ









Characteristics charts of UNR911CJ














Characteristics charts of UNR911DJ






Characteristics charts of UNR911EJ








Characteristics charts of UNR911FJ












Characteristics charts of UNR911HJ






Characteristics charts of UNR911LJ









Characteristics charts of UNR911MJ














Characteristics charts of UNR911NJ





Characteristics charts of UNR911TJ



Characteristics charts of UNR911VJ





Maintenance/Discontinued

Maintenance/Discontinued includes following four Product lifecycle stage.
 planned maintenance type
 maintenance type
 planned discontinued type
 discontinued type
 Please visit following URL about latest information.
<http://www.semicon.panasonic.co.jp/en/>

Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 - Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.