



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Universal Reversible USB 2.0 Cable (Reversible A to Left-Angle 5Pin Mini B M/M), 3-ft.

MODEL NUMBER: **UR030-003-LAB**



Universal / Reversible "A" connector allows plugging in any direction

### Description

Tripp Lite's UR030-003-LAB, 3-ft, USB 2.0 Universal / Reversible "A" to Left-Angle Mini-B 5-pin device cable, meets or exceeds USB 2.0 Specifications. Connects a Digital camera, PDA, Cell Phone, etc to a USB port on a computer or hub. Backward compatible - can be used with older USB1.1 applications as well. All Tripp Lite USB 2.0 cabling include superior foil shielding for reliable, error-free data communications. Features nickel plated connectors and gold plated copper contacts for superior conductivity. The cable is manufactured with molded connectors and integral strain relief for extra durability and long life.

### Features

- Universal / Reversible "A" connector plugs in any direction
- Left-Angle Mini B connector ideal in situations where space is at a premium, and reduces stress / excessive bending on the cable
- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, Cell Phones, PDA's, etc with 5-Pin Mini-B USB connectors
- Supports faster data transfer rate (1.5 to 480 Mbps) for low speed and high speed devices including multimedia applications
- Premium double-shielded cables with tinned copper braid and aluminum Mylar foil
- Nickel plated connectors and gold plated copper contacts for superior conductivity.
- Molded connectors and integral strain relief for extra durability and long life.

## Specifications

### Highlights

- Universal / Reversible A connector eliminates guess-work as to connector orientation
- Left-Angle Mini B connector ideal in situations where space is at a premium, and reduces stress / excessive bending on the cable
- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, PDA's, etc with Mini-B 5-Pin connectors

### System Requirements

- Any USB device requiring a USB cable with Mini-B 5-Pin connector
- USB2.0 performance only when used with USB2.0 device and USB2.0 controller

### Package Includes

- 3-ft. USB2.0 Universal / Reversible A to Left-Angle Mini-B Device Cable (A Male to 5Pin Mini-B Male)



| <b>OVERVIEW</b>                     |  |
|-------------------------------------|--|
| UPC Code                            | 037332182241                             |
| Technology                          | USB 2.0 (High Speed); USB (all versions) |
| <b>INPUT</b>                        |  |
| Cable Length (ft.)                  | 3  |
| Cable Length (m)                    | 0.9                                      |
| <b>PHYSICAL</b>                     |  |
| Wire Gauge (AWG)                    | 28/28                                    |
| Shipping Dimensions (hwd / in.)     | 0.100 x 7.000 x 10.000                   |
| Shipping Dimensions (hwd / cm)      | 0.25 x 17.78 x 25.40                     |
| Shipping Weight (lbs.)              | 0.1000                                   |
| Shipping Weight (kg)                | 0.05                                     |
| Color                               | Black                                    |
| <b>ENVIRONMENTAL</b>                |  |
| Operating Temperature Range         | -10/+75° C (14 to 167° F)                |
| Storage Temperature Range           | -20 to 80° C (-4 to 176° F)              |
| <b>CONNECTIONS</b>                  |  |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)                  |
| Side B - Connector 1                | USB MINI-B 5-PIN (MALE)                  |
| <b>WARRANTY</b>                     |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty                |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>