



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



MICRO SWITCH
a Honeywell Division

FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING

V3L-3296

CQ-X2787

V3L-3296

CATALOG LISTING

M

ISSUE
3

REPLACES
RELEASE NO. PR-16061

CHECK

REVISIONS

A	PR-16061
MAM	10 DEC 87
B	CQ-76298
JAK	11 NOV 93

CHECK

12 DEC 87



GLH

CHECK

10 DEC 87


MAM


DDM/CAD
DRAWN



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS	ELECTRICAL DATA		SCALE	FULL	DO NOT SCALE PRINT
OPERATING FORCE — — — 88 GRAM MAX	CONTACT ARRANGEMENT S P D T		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ± WEIGHT		
RELEASE FORCE — — — 6 GRAM MIN	L83 15.1A 1/2HP 125, <u>250</u> VAC 1/2A 125 VDC, 1/4A 250 VDC 5A 125 VAC "L" 				
DIFFERENTIAL TRAVEL — — .032 MAX					
OVERTRAVEL — — — .090 MIN					
RELEASE TRAVEL — — — .017 MIN					

