



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Home > Products >> V921 > V921YLFT

You may also like...

V921YLFT

Category:
Generic Part: V921
Market Group: VIDEO
Description: HDMI DUAL PORT RECEIVER



Parameters

| | |
|-------------------------|--------|
| Speed | NA |
| Temperature | C |
| Voltage | 1.8 V |
| Status | Active |
| Sample | Yes |
| Minimum Order Quantity | 500 |
| Factory Order Increment | 500 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

No documents available for this part at this time.

Package

| | |
|----------------------------------|-----------------------------------|
| Package | TQFP 144 (EGG144) |
| Description | TQFP 20 X 20 X 1.0 MM EXPOSED PAD |
| Status | Active |
| Class | PLASTIC |
| Category | Green |
| Pb (Lead) Free | Yes |
| Mark | Y |
| Package Type | TQFP |
| Lead Count | 144 |
| Length | 20.0 mm |
| Width | 20.0 mm |
| Thickness | 1.0 mm |
| Pitch | 0.5 mm |
| Tube / Tray | TRAY |
| Quantity per Tube/Tray | 60 |
| Quantity per Reel | 500 |
| Moisture Sensitivity Level (MSL) | 3 |
| Moisture Exposure Floor Life | 168hrs@<30C/60%RH |
| Peak Reflow Temperature | 260Â°C |
| Rebake Conditions | 48hrs@125C |
| Related Package Documents | view documents |