



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



[Home](#) > [Products](#) > > [V923](#) > [V923YLFT](#)

You may also like...

V923YLFT

Category:
Generic Part: V923
Market Group: VIDEO
Description: HDMI DUAL PORT RECEIVER

Parameters

Speed	NA
Temperature	C
Voltage	1.8 V
Status	Active
Sample	Yes
Minimum Order Quantity	500
Factory Order Increment	500

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

No documents available for this part at this time.

Package

Package	TQFP 144 (EGG144)
Description	TQFP 20 X 20 X 1.0 MM EXPOSED PAD
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	Y
Package Type	TQFP
Lead Count	144
Length	20.0 mm
Width	20.0 mm
Thickness	1.0 mm
Pitch	0.5 mm
Tube / Tray	TRAY
Quantity per Tube/Tray	60
Quantity per Reel	500
Moisture Sensitivity Level (MSL)	3
Moisture Exposure Floor Life	168hrs@<30C/60%RH
Peak Reflow Temperature	260Â°C
Rebake Conditions	48hrs@125C
Related Package Documents	view documents