

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







TECHNICAL DATA SHEET

Rosenberger

TEST CABLE SET RPC-3.50 / RPC-3.50

VA26-3.50M-3.50F-60



Contents

Device	Part number	Quantity	
Cable assembly RPC-3.50 jack / RPC-3.50 plug	LU7-055-600	2	

Documents

Technical data sheet cable assembly: RPC-3.50 jack / RPC-3.50 plug

LU7-055-XXX

TECHNICAL DATA SHEET

Rosenberger

2/2

TEST CABLE SET RPC-3.50 / RPC-3.50

VA26-3.50M-3.50F-60

Electrical data

Impedance 50 Ω

Frequency DC to 26.5 GHz Return loss \geq 26 dB, DC to 4 GHz \geq 20 dB, 4 GHz to 26.5 GHz

Insertion loss \leq 1.62 dB at 26.5 GHz

Phase deviation:

Amplitude stability

Return loss stability

After 90° bending \leq 1.0°, DC to 4 GHz

≤ 3.0°, 4 GHz to 26.5 GHz

Straight after $3x90^{\circ}$ bending $\leq 0.5^{\circ}$, DC to 4 GHz

≤ 1.5°, 4 GHz to 26.5 GHz ≤ 0.03 dB, DC to 4 GHz

≤ 0.05 dB, 4 GHz to 26.5 GHz

 \geq 48 dB, DC to 4 GHz

 \geq 40 dB, 4 GHz to 26.5 GHz

RF-leakage \geq 100 dB up to 1 GHz

Mechanical data

Minimum bend radius 60 mm

Environmental data

www.rosenberger.de

Temperature range -40°C to +85°C compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date		Rev.	Engineering change number	Name	Date
Herbert Babinger	03/08/06	Martin Moder	07/08/17		e00	17-1214	M.Ruf	07/08/17
Rosenberger Hochfrequenztechnik GmbH & Co. KG					Te	el.: +49 8684 18-0		Page
P.O.Box 1260 D-84526 Tittmoning Germany					Fa	x: +49 8684 18-499		

email: info@rosenberger.de