

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## TECHNICAL DATA SHEET

## Rosenberger

TEST CABLE SET RPC-7 / RPC-7

VA26-PC7-PC7-60



## Contents

Device	Part number	Quantity
Cable assembly RPC-7 / RPC-7	LU7-070-600	2

#### **Documents**

Technical data sheet cable assembly: RPC-7 / RPC-7

LU7-070-XXX

### TECHNICAL DATA SHEET

## Rosenberger

2/2

# TEST CABLE SET RPC-7 / RPC-7

## VA26-PC7-PC7-60

#### Electrical data

Impedance 50  $\Omega$ 

Frequency DC to 18 GHz

Return loss  $\geq$  28 dB, DC to 4 GHz  $\geq$  20 dB, 4 GHz to 18 GHz

Insertion loss ≤ 1.30 dB at 18 GHz

Phase deviation:

After 90° bending  $\leq 0.5^{\circ}$ , DC to 4 GHz

 $\leq 2.0^{\circ},~4~\text{GHz}$  to 18 GHz

Straight after  $3x90^{\circ}$  bending  $\leq 0.5^{\circ}$ , DC to 4 GHz

 $\leq$  1.5°, 4 GHz to 18 GHz

Amplitude stability  $\leq$  0.03 dB, DC to 4 GHz

 $\leq 0.05$  dB, 4 GHz to 18 GHz

Return loss stability  $\geq$  48 dB, DC to 4 GHz

 $\geq$  40 dB, 4 GHz to 18 GHz

RF-leakage ≥ 100 dB up to 1 GHz

#### Mechanical data

Minimum bend radius 60 mm

## Environmental data

Temperature range -40°C to +85°C 2002/95/EC (RoHS) compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date		Rev.	Engineering change number	Name	Date
Herbert Babinger	24/02/06	Frank Tatzel	28/02/11		e00	11-0169	Krautenbacher J.	28/02/11
Rosenberger Hochfrequenztechnik GmbH & Co. KG				Te	el.: +49 8684 18-0		Page	
P.O.Box 1260 D-84526 Tittmoning Germany				Fa	ax: +49 8684 18-499			

email: info@rosenberger.de

www.rosenberger.de